# **XLERATOR® HAND DRYER**



ORIGINAL. PATENTED. STILL THE BEST.

SECONDS proven dry time

80%
LESS ENERGY
than conventional dryers

95% COST SAVINGS versus paper towels







## **XLERATOR® HAND DRYER**

MODELS: XL - BW W GR C SB SI SP OPTIONS: -1.1N (Noise Reduction Nozzle) -H (HEPA Filter) -VOLTAGE (See Chart





XL-BW White Thermoset Resin (BMC)



XL-W XL-GR White Epoxy Graphite Textured Painted Painted

#### **FEATURES & BENEFITS**

- 10 Second Dry Time\*
- Adjustable Speed and Sound Control
- Variable Heat High, Medium, Low
- 80% Less Energy Than Conventional Hand Dryers
- 95% Cost Savings Vs. Paper Towels

#### Made In USA Certified®

- 5-Year Limited Warranty
- GreenSpec® Listed and Helps Qualify for several LEED® credits
- A Hygienic Hand Drying Solution
- Over a Decade of Proven Performance
- Virtually Maintenance Free

#### **OPTIONS**

- ✓ HEPA Filtration System: Filters 99.97% of bacteria at 0.3 microns from the air stream.
- 1.1 Noise Reduction Nozzle: Lowers decibel level 9 dB by reducing air deflection noise but increases dry time by approximately 3 seconds.

#### **ONLINE INFORMATION**

- **Product Videos**
- Cost Savings & Carbon Footprint Calculator
- Life Cycle Assessment Study
- Case Studies



- CAD/BIM Images
- AIA/GBCI CEU Courses
- Technical Data Sheet



XL-SP\*\* Custom Special Paint



XL-SI\*\*\* Custom Special Image



XL-C Chrome Plated



XL-SB **Brushed Stainless** Steel

#### **DIMENSIONS**

**Width** 11 <sup>3</sup>/4" (298 mm) **Height** 12 <sup>11</sup>/16" (322 mm) **Depth** 6 <sup>11</sup>/16" (170 mm)

### **ACTIVATION**

**MOUNTING** 

**Automatic Sensor Operated Surface Mounted** 

Note: Heights measured from floor to bottom of dryer.

Women 43" (109 cm)

#### WEIGHT

XL-BW: 15 lbs. (6.8 kgs.) XL-SB: 16 lbs. (7.26 kgs.) XL-W, GR, C, SI, SP: 17 lbs. (7.71 kgs.)

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450VV	4.3-4.5A	460-530W	50/60 Hz	c(UL)us
208-277V	5.6-6.2A	1160-1490W	2.0-2.2A	425-500W	50/60 Hz	c(UL) us
230V	6.1A	1410W	2.2A	500W	50 Hz	Œ


#### **ELECTRICAL**

VOLTS	AMPS	WATTS	NO HEAT AMPS	NO HEAT WATTS	HERTZ	
110-120V	11.3-12.2A	1240-1450W	4.3-4.5A	460-530W	50/60 Hz	c (UL) us
208-277V	5.6-6.2A	1160-1490W	2.0-2.2A	425-500W	50/60 Hz	c (UL) us
230V	6.1A	1410W	2.2A	500W	50 Hz	Œ



**Men** 45" (114 cm)

Anti-Microbial Wall Guards



SUGGESTED MOUNTING HEIGHTS

**ADA-Compliant Recess Kit** 

Width 16 3/8" (416 mm) Height 26" (660 mm) **Depth** 3 3/8" (86 mm) **Weight** 11 lbs. (4.99 kgs.)



Handicapped 37" (94 cm)

Part # 40502









Dry time based on third party testing performed by SGS International on standard XLERATOR hand dryer with 0.8" nozzle to 0.2g or less of residual moisture.

Special Paint powder-coated covers are available in many colors and textures.

Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'

