



2020 PRODUCT GUIDE



we know light.™

TABLE OF CONTENTS

INDOOR LED LUMINAIRES 1-14

LUXTERIOR LED PREMIUM WATTAGE SELECTABLE FLAT PANELS	1
LUXTERIOR LED PREMIUM FLAT PANEL LUMINAIRES	2
LUXTERIOR LED WATTAGE SELECTABLE STANDARD FLAT PANELS	3
LUXTERIOR LED STANDARD FLAT PANEL LUMINAIRES	4
LED WATTAGE SELECTABLE DIRECT TROFFER FLAT PANELS	5
LED DIRECT TROFFER FLAT PANELS	5
LUXTERIOR LED WATTAGE SELECTABLE VOLUMETRIC LUMINAIRES	6
LED LB SERIES LINEAR LOW BAY LUMINAIRES	6
LED HB SERIES LINEAR HIGH BAY LUMINAIRES	6
LED IB SERIES LINEAR HIGH BAY LUMINAIRES	7
LED UFO HIGH BAY LUMINAIRES	8
LED ROUND HIGH BAY LUMINAIRES, GENERATION 2	8
LED VAPOR TIGHT	9
LED WRAP LIGHT	9
LED GENERAL PURPOSE STRIP/ LOW BAY LUMINAIRES	10
LED GENERAL PURPOSE STRIP RETROFIT KIT	10
LED COMMERCIAL DOWNLIGHTS	11
LED RECESSED 4" DOWNLIGHTS	12
LED RECESSED 5/6" DOWNLIGHTS	12
LED RECESSED 4" HI CRI CQ DOWNLIGHTS	12
LED RECESSED 5/6" HI CRI CQ DOWNLIGHTS	12
LED DIMMABLE EDGELIT 4" DOWNLIGHTS	12
LED DIMMABLE EDGELIT 5/6" DOWNLIGHTS	12
LED DESIGNER BEVELED 4" DOWNLIGHTS	13
LED DESIGNER BEVELED 5/6" DOWNLIGHTS	13
LED JUNCTION BOX 5/6" DOWNLIGHTS	13
LED DELUX SERIES ROUND SNAP-IN 6" DOWNLIGHTS	13
LED DELUX SERIES ROUND SNAP-IN TRIM RINGS	13
LED SQUARE SNAP-IN 4" DOWNLIGHTS	14
LED SQUARE SNAP-IN 6" DOWNLIGHTS	14
LED SQUARE SNAP-IN 8" DOWNLIGHTS	14
LED ROUND SNAP-IN 4" DOWNLIGHTS	14
LED ROUND SNAP-IN 6" DOWNLIGHTS	14
LED ROUND SNAP-IN 8" DOWNLIGHTS	14
LED ALLUSION RECESSED 5/6" DOWNLIGHTS	14

OUTDOOR LED LUMINAIRES 15-18

LED ADJUSTABLE WALL PACKS	15
LED FULL CUTOFF WALL PACKS	15
LED NON-CUTOFF WALL PACKS, ACRYLIC LENS	15
LED NON-CUTOFF COMPACT WALL PACKS	16
LED CANOPY LIGHTS	16
LED FLOOD LIGHTS	16
LED POST TOP	17
LED BARN LIGHT LUMINAIRES	17
LED SECURITY LIGHT LUMINAIRE	17
LED AREA LIGHT LUMINAIRES	18

LED PARS 19-26

LED HIGH OUTPUT DIMMABLE ELITE PAR38	19
LED DIMMABLE ELITE PAR38	19-21
LED DIMMABLE ELITE PAR30	22-23
LED DIMMABLE ELITE PAR30 SHORT NECK	23-24
LED DIMMABLE ELITE PAR20	24
LED DIMMABLE SMD PAR38	25
LED DIMMABLE SMD PAR30	25
LED DIMMABLE SMD PAR30 SHORT NECK	25
LED DIMMABLE SMD PAR20	26
LED HIGH OUTPUT, HIGH CRI DIMMABLE ELITE PAR38	26
LED HIGH CRI DIMMABLE ELITE PAR38	26
LED HIGH CRI DIMMABLE ELITE PAR30	26
LED HIGH CRI DIMMABLE ELITE PAR30 SHORT NECK	26

LED BR3 27-28

LED DIMMABLE ELITE BR40	27
LED DIMMABLE ELITE BR30	27
LED DIMMABLE ELITE R20	27
LED DIMMABLE ELITE BR30 2 PACK	28
LED NON DIMMABLE ELITE BR40	28
LED NON DIMMABLE ELITE BR30	28
LED DIMMABLE ELITE COLORED BR30	28

LED A-LAMPS 29-31

LED DIMMABLE ELITE OMNIDIRECTIONAL A-LAMPS	29-30
LED NON DIMMABLE OMNIDIRECTIONAL A-LAMPS	29-30
LED NON DIMMABLE GENERAL PURPOSE A-LAMPS	29-30
LED DIMMABLE ELITE GU24 BASED A-LAMPS	31
LED DIMMABLE ELITE WET LOCATION OMNI A-LAMPS	31
LED DIMMABLE ELITE THREE WAY A-LAMPS	31

LED MR16 32-33

LED DIMMABLE ELITE VALUE GU5.3 MR16	32
LED DIMMABLE ELITE HIGH CRI GU5.3 MR16	32
LED DIMMABLE ELITE GU10 MR16	33

LED PAR16 33

LED DIMMABLE ELITE PAR16	33
--------------------------------	----

LED G25 34

LED DIMMABLE ELITE G25	34
------------------------------	----

LED S14 34

LED NON DIMMABLE WET LOCATION S14	34
---	----

LED DECO LAMPS 35

LED 5W DECO LAMPS	35
LED 4W DECO LAMPS	35

LED ELEVATOR LAMPS 36

LED ELEVATOR LAMPS	36
--------------------------	----

LED FILAMENT LAMPS 36-39

LED DIMMABLE FILAMENT A19 LAMPS	36
LED DIMMABLE FILAMENT ST19 LAMPS	36
LED DIMMABLE FILAMENT B11 DECO LAMPS	37
LED DIMMABLE FILAMENT F11 DECO LAMPS	38
LED DIMMABLE FILAMENT G25 DECO LAMPS	39
LED DIMMABLE FILAMENT G16 DECO LAMPS	39

LED PROLINE LAMPS 40-41

LED DIMMABLE PROLINE PAR38 LAMPS	40
LED DIMMABLE PROLINE PAR30 LAMPS	40
LED DIMMABLE PROLINE PAR20 LAMPS	40
LED DIMMABLE PROLINE BR40 LAMPS	40
LED DIMMABLE PROLINE BR30 LAMPS	40
LED DIMMABLE PROLINE R20 LAMPS	40
LED DIMMABLE PROLINE G25 LAMPS	40
LED DIMMABLE PROLINE B11 LAMPS	40
LED DIMMABLE PROLINE ALL GLASS A19 LAMPS	41
LED NON DIMMABLE PROLINE ALL GLASS A19 LAMPS	41
LED DIMMABLE PROLINE A19 LAMPS	41
LED NON DIMMABLE PROLINE A19 LAMPS	41

THE GOOD LIFE LED LAMPS 42

LED DIMMABLE GOOD LIFE A19 LAMPS	42
LED DIMMABLE GOOD LIFE BR30 LAMPS	42
LED DIMMABLE GOOD LIFE DECO LAMPS	42
LED DIMMABLE GOOD LIFE G25 LAMPS	42
LED DIMMABLE GOOD LIFE ST19 LAMPS	42

LED G4 LAMPS 42

LED NON DIMMABLE G4 LAMPS	42
---------------------------------	----

LED ALLUSION LAMPS 43

LED DIMMABLE ALLUSION PAR38 LAMPS	43
LED DIMMABLE ALLUSION PAR30 LAMPS	43
LED DIMMABLE ALLUSION PAR20 LAMPS	43
LED DIMMABLE ALLUSION MR16 LAMPS	43
LED DIMMABLE ALLUSION SL16 LAMPS	43
LED DIMMABLE ALLUSION 5/6" DOWNLIGHTS	43
LED DIMMABLE ALLUSION BR30 LAMPS	43
LED DIMMABLE ALLUSION A19 LAMPS	43
LED DIMMABLE ALLUSION B11 DECO LAMPS	43

LED PL LAMPS, LED 120-277 LAMPS, LED STARLIGHT SERIES, LED HID REPLACEMENT LAMPS, LED TUBES, CFLS, FLUORESCENT LAMPS, BALLASTS AND FIXTURES LISTED ON INSIDE BACK COVER

INDOOR LED LUMINAIRES



Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
LUXTERIOR 50,000 HOUR LED WATTAGE SELECTABLE PREMIUM FLAT PANEL LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)										
2x2 LED WATTAGE SELECTABLE PREMIUM FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL										
FP2UZDA130K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	3000 3800 4800	130.4 131 126.3	3000	>80	50,000	
FP2UZDA135K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	3000 3800 4800	130.4 131 126.3	3500	>80	50,000	- Emergency Back-Up
FP2UZDA141K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	3000 3800 4800	130.4 131 126.3	4100	>80	50,000	- Single Pack, Assembled
FP2UZDA150K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	3000 3800 4800	130.4 131 126.3	5000	>80	50,000	
2x4 LED WATTAGE SELECTABLE PREMIUM FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL										
FP4UZDA130K	23, 29, 38 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	3250 4000 5200	141.3 137.9 136.8	3000	>80	50,000	
FP4UZDA135K	23, 29, 38 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	3250 4000 5200	141.3 137.9 136.8	3500	>80	50,000	
FP4UZDA141K	23, 29, 38 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	3250 4000 5200	141.3 137.9 136.8	4100	>80	50,000	
FP4UZDA150K	23, 29, 38 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	3250 4000 5200	141.3 137.9 136.8	5000	>80	50,000	- Emergency Back-Up
FP4UZDA230K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29 39 46	4000 5200 6000	137.9 133.3 130.4	3000	>80	50,000	- Single Pack, Assembled
FP4UZDA235K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29 39 46	4000 5200 6000	137.9 133.3 130.4	3500	>80	50,000	
FP4UZDA241K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29 39 46	4000 5200 6000	137.9 133.3 130.4	4100	>80	50,000	
FP4UZDA250K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29 39 46	4000 5200 6000	137.9 133.3 130.4	5000	>80	50,000	
1x4 LED WATTAGE SELECTABLE PREMIUM FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL										
FP1UZDA130K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	3000 3650 4600	130.4 125.9 121.1	3000	>80	50,000	
FP1UZDA135K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	3000 3650 4600	130.4 125.9 121.1	3500	>80	50,000	- Emergency Back-Up
FP1UZDA141K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	3000 3650 4600	130.4 125.9 121.1	4100	>80	50,000	- Single Pack, Assembled
FP1UZDA150K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	3000 3650 4600	130.4 125.9 121.1	5000	>80	50,000	



Luxterior
by TCP



Luxterior
by TCP



Luxterior
by TCP

AVAILABLE ACCESSORIES (ordered separately)

- YHANGER6PK – Y Fit Cable Hanger 6 Pack
- DRVEXTCABLE – 3 FT Driver Extension Cable

- FPSK1 – 1X4 Flat Panel Surface Mount Kit (White)
- FPSK2 – 2X2 Flat Panel Surface Mount Kit (White)
- FPSK4 – 2X4 Flat Panel Surface Mount Kit (White)

- DTFLK1 – 1X4 Recess Mount Flange Kit
- DTFLK2 – 2X2 Recess Mount Flange Kit
- DTFLK4 – 2X4 Recess Mount Flange Kit



Many items are DLC QPL.
Visit www.designlights.org/qpl for a full listing.

¹ Actual wattage may vary by +/- 10%.
² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

For the most up-to-date specs and warranty information, please visit www.tcp.com

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

LUXTERIOR 50,000 HOUR LED PREMIUM FLAT PANEL LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

2x2 LED PREMIUM FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

HFP2UZD2330K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	3000	130.4	3000	>80	50,000	
HFP2UZD2335K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	3000	130.4	3500	>80	50,000	
HFP2UZD2341K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	3000	130.4	4100	>80	50,000	
HFP2UZD2350K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	3000	130.4	5000	>80	50,000	
HFP2UZD2930K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3800	131	3000	>80	50,000	
HFP2UZD2935K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3800	131	3500	>80	50,000	- Emergency
HFP2UZD2941K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3800	131	4100	>80	50,000	Back-Up
HFP2UZD2950K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3800	131	5000	>80	50,000	
HFP2UZD3830K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	4800	126.3	3000	>80	50,000	
HFP2UZD3835K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	4800	126.3	3500	>80	50,000	
HFP2UZD3841K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	4800	126.3	4100	>80	50,000	
HFP2UZD3850K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	4800	126.3	5000	>80	50,000	

2x4 LED WATTAGE SELECTABLE PREMIUM FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

HFP4UZD2330K	23W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	3250	141.3	3000	>80	50,000	
HFP4UZD2335K	23W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	3250	141.3	3500	>80	50,000	
HFP4UZD2341K	23W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	3250	141.3	4100	>80	50,000	
HFP4UZD2350K	23W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	3250	141.3	5000	>80	50,000	
HFP4UZD2930K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	4000	137.9	3000	>80	50,000	
HFP4UZD2935K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	4000	137.9	3500	>80	50,000	
HFP4UZD2941K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	4000	137.9	4100	>80	50,000	
HFP4UZD2950K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	4000	137.9	5000	>80	50,000	- Emergency
HFP4UZD3830K	38W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	5200	136.8	3000	>80	50,000	Back-Up
HFP4UZD3835K	38W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	5200	136.8	3500	>80	50,000	
HFP4UZD3841K	38W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	5200	136.8	4100	>80	50,000	
HFP4UZD3850K	38W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	5200	136.8	5000	>80	50,000	
HFP4UZD4630K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	46	6000	130.4	3000	>80	50,000	
HFP4UZD4635K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	46	6000	130.4	3500	>80	50,000	
HFP4UZD4641K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	46	6000	130.4	4100	>80	50,000	
HFP4UZD4650K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	46	6000	130.4	5000	>80	50,000	

1x4 LED WATTAGE SELECTABLE PREMIUM FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

HFP1UZD2330K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	3000	130.4	3000	>80	50,000	
HFP1UZD2335K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	3000	130.4	3500	>80	50,000	
HFP1UZD2341K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	3000	130.4	4100	>80	50,000	
HFP1UZD2350K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	3000	130.4	5000	>80	50,000	
HFP1UZD2930K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3650	125.9	3000	>80	50,000	
HFP1UZD2935K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3650	125.9	3500	>80	50,000	- Emergency
HFP1UZD2941K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3650	125.9	4100	>80	50,000	Back-Up
HFP1UZD2950K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3650	125.9	5000	>80	50,000	
HFP1UZD3830K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	4600	121.1	3000	>80	50,000	
HFP1UZD3835K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	4600	121.1	3500	>80	50,000	
HFP1UZD3841K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	4600	121.1	4100	>80	50,000	
HFP1UZD3850K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	4600	121.1	5000	>80	50,000	

AVAILABLE ACCESSORIES (ordered separately)

YHANGER6PK – Y Fit Cable Hanger 6 Pack
DRVEXTCABLE – 3 FT Driver Extension Cable

FPSK1 – 1X4 Flat Panel Surface Mount Kit (White)
FPSK2 – 2X2 Flat Panel Surface Mount Kit (White)
FPSK4 – 2X4 Flat Panel Surface Mount Kit (White)

DTFLK1 – 1X4 Recess Mount Flange Kit
DTFLK2 – 2X2 Recess Mount Flange Kit
DTFLK4 – 2X4 Recess Mount Flange Kit

¹ Actual wattage may vary by +/- 10%.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

LUXTERIOR 50,000 HOUR LED WATTAGE SELECTABLE STANDARD FLAT PANEL LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

2x2 LED WATTAGE SELECTABLE STANDARD FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL

FP2UZDB130K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	2700 3200 4100	117.4 110.3 107.9	3000	>80	50,000	
FP2UZDB135K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	2700 3200 4100	117.4 110.3 107.9	3500	>80	50,000	- Emergency Back-Up
FP2UZDB141K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	2700 3200 4100	117.4 110.3 107.9	4100	>80	50,000	- Single Pack, Assembled
FP2UZDB150K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	2700 3200 4100	117.4 110.3 107.9	5000	>80	50,000	



Luxterior
by TCP

2x4 LED WATTAGE SELECTABLE STANDARD FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL

FP4UZDB130K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29 39 46	3600 4600 5200	124.1 117.9 113	3000	>80	50,000	
FP4UZDB135K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29 39 46	3600 4600 5200	124.1 117.9 113	3500	>80	50,000	- Emergency Back-Up
FP4UZDB141K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29 39 46	3600 4600 5200	124.1 117.9 113	4100	>80	50,000	- Single Pack, Assembled
FP4UZDB150K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29 39 46	3600 4600 5200	124.1 117.9 113	5000	>80	50,000	



Luxterior
by TCP

1x4 LED WATTAGE SELECTABLE STANDARD FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL

FP1UZDB130K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	3000	>80	50,000	
FP1UZDB135K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	3500	>80	50,000	- Emergency Back-Up
FP1UZDB141K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	4100	>80	50,000	- Single Pack, Assembled
FP1UZDB150K	23, 29, 38 Wattage Selectable Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	5000	>80	50,000	



Luxterior
by TCP

AVAILABLE ACCESSORIES (ordered separately)

- YHANGER6PK – Y Fit Cable Hanger 6 Pack
- DRVEXTCABLE – 3 FT Driver Extension Cable

- FPSK1 – 1X4 Flat Panel Surface Mount Kit (White)
- FPSK2 – 2X2 Flat Panel Surface Mount Kit (White)
- FPSK4 – 2X4 Flat Panel Surface Mount Kit (White)

- DTFLK1 – 1X4 Recess Mount Flange Kit
- DTFLK2 – 2X2 Recess Mount Flange Kit
- DTFLK4 – 2X4 Recess Mount Flange Kit



Many items are DLC QPL. Visit www.designlights.org/qpl for a full listing.

¹ Actual wattage may vary by +/- 10%.
² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

For the most up-to-date specs and warranty information, please visit www.tcp.com

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

LUXTERIOR 50,000 HOUR LED STANDARD FLAT PANEL LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

2x2 LED STANDARD FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

FP2UZD2330K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	2700	117.4	3000	>80	50,000	
FP2UZD2335K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	2700	117.4	3500	>80	50,000	
FP2UZD2341K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	2700	117.4	4100	>80	50,000	
FP2UZD2350K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	2700	117.4	5000	>80	50,000	
FP2UZD2930K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3200	110.3	3000	>80	50,000	
FP2UZD2935K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3200	110.3	3500	>80	50,000	- Emergency
FP2UZD2941K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3200	110.3	4100	>80	50,000	Back-Up
FP2UZD2950K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3200	110.3	5000	>80	50,000	
FP2UZD3830K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	4100	107.9	3000	>80	50,000	
FP2UZD3835K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	4100	107.9	3500	>80	50,000	
FP2UZD3841K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	4100	107.9	4100	>80	50,000	
FP2UZD3850K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	4100	107.9	5000	>80	50,000	

2x4 LED STANDARD FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

FP4UZD2930K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3600	124.1	3000	>80	50,000	
FP4UZD2935K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3600	124.1	3500	>80	50,000	
FP4UZD2941K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3600	124.1	4100	>80	50,000	
FP4UZD2950K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3600	124.1	5000	>80	50,000	
FP4UZD3930K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	39	4600	117.9	3000	>80	50,000	
FP4UZD3935K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	39	4600	117.9	3500	>80	50,000	- Emergency
FP4UZD3941K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	39	4600	117.9	4100	>80	50,000	Back-Up
FP4UZD3950K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	39	4600	117.9	5000	>80	50,000	
FP4UZD4630K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	46	5200	113	3000	>80	50,000	
FP4UZD4635K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	46	5200	113	3500	>80	50,000	
FP4UZD4641K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	46	5200	113	4100	>80	50,000	
FP4UZD4650K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	46	5200	113	5000	>80	50,000	

1x4 LED STANDARD FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL



Luxterior
by TCP

FP1UZD2330K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	2600	113	3000	>80	50,000	
FP1UZD2335K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	2600	113	3500	>80	50,000	
FP1UZD2341K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	2600	113	4100	>80	50,000	
FP1UZD2350K	23W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	2600	113	5000	>80	50,000	
FP1UZD2930K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3200	110.3	3000	>80	50,000	
FP1UZD2935K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3200	110.3	3500	>80	50,000	- Emergency
FP1UZD2941K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3200	110.3	4100	>80	50,000	Back-Up
FP1UZD2950K	29W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3200	110.3	5000	>80	50,000	
FP1UZD3830K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	4200	110.5	3000	>80	50,000	
FP1UZD3835K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	4200	110.5	3500	>80	50,000	
FP1UZD3841K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	4200	110.5	4100	>80	50,000	
FP1UZD3850K	38W Flat Panel, 1x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	4200	110.5	5000	>80	50,000	

AVAILABLE ACCESSORIES (ordered separately)

YHANGER6PK – Y Fit Cable Hanger 6 Pack
DRVEXTCABLE – 3 FT Driver Extension Cable

FPSK1 – 1X4 Flat Panel Surface Mount Kit (White)
FPSK2 – 2X2 Flat Panel Surface Mount Kit (White)
FPSK4 – 2X4 Flat Panel Surface Mount Kit (White)

DTFLK1 – 1X4 Recess Mount Flange Kit
DTFLK2 – 2X2 Recess Mount Flange Kit
DTFLK4 – 2X4 Recess Mount Flange Kit

¹ Actual wattage may vary by +/- 10%.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.


For the most up-to-date specs and warranty information, please visit www.tcp.com

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

50,000 HOUR LED WATTAGE SELECTABLE BACK-LIT DIRECT TROFFER LUMINAIRE

2x2 LED WATTAGE SELECTABLE BACK-LIT DIRECT TROFFER FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL

DTF2UZDB130K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	3000	>80	50,000	- Emergency Back-Up
DTF2UZDB135K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	3500	>80	50,000	- Single Pack, Assembled
DTF2UZDB141K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	4100	>80	50,000	- Single Pack, Assembled
DTF2UZDB150K	23, 29, 38 Wattage Selectable Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23 29 38	2600 3200 4200	113 110.3 110.5	5000	>80	50,000	- Single Pack, Assembled



2x4 LED WATTAGE SELECTABLE BACK-LIT DIRECT TROFFER FLAT PANELS – KIT ITEMS; DRIVER SHIPS SEPARATE FROM PANEL


DTF4UZDB130K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29 39 46	3300 4400 5100	113.8 112.8 110.9	3000	>80	50,000	- Emergency Back-Up
DTF4UZDB135K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29 39 46	3300 4400 5100	113.8 112.8 110.9	3500	>80	50,000	- Single Pack, Assembled
DTF4UZDB141K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29 39 46	3300 4400 5100	113.8 112.8 110.9	4100	>80	50,000	- Single Pack, Assembled
DTF4UZDB150K	29, 39, 46 Wattage Selectable Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29 39 46	3300 4400 5100	113.8 112.8 110.9	5000	>80	50,000	- Single Pack, Assembled



50,000 HOUR LED DIRECT TROFFER LUMINAIRE (CONSULT SPEC SHEET FOR ORDERING MATRIX)


2x2 LED DIRECT TROFFER FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL

DTF2UZD2330K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	2600	113	3000	>80	50,000	
DTF2UZD2335K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	2600	113	3500	>80	50,000	
DTF2UZD2341K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	2600	113	4100	>80	50,000	
DTF2UZD2350K	23W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	2600	113	5000	>80	50,000	
DTF2UZD2930K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3200	110.3	3000	>80	50,000	
DTF2UZD2935K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3200	110.3	3500	>80	50,000	- Emergency Back-Up
DTF2UZD2941K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3200	110.3	4100	>80	50,000	- Emergency Back-Up
DTF2UZD2950K	29W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3200	110.3	5000	>80	50,000	- Emergency Back-Up
DTF2UZD3830K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	38	4200	110.5	3000	>80	50,000	
DTF2UZD3835K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	38	4200	110.5	3500	>80	50,000	
DTF2UZD3841K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	38	4200	110.5	4100	>80	50,000	
DTF2UZD3850K	38W Flat Panel, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	38	4200	110.5	5000	>80	50,000	



2x4 LED DIRECT TROFFER FLAT PANELS – FULLY ASSEMBLED; DRIVER ATTACHED TO PANEL

DTF4UZD2930K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	3300	113.8	3000	>80	50,000	
DTF4UZD2935K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	3300	113.8	3500	>80	50,000	
DTF4UZD2941K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	3300	113.8	4100	>80	50,000	
DTF4UZD2950K	29W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	3300	113.8	5000	>80	50,000	
DTF4UZD3930K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	39	4400	112.8	3000	>80	50,000	
DTF4UZD3935K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	39	4400	112.8	3500	>80	50,000	- Emergency Back-Up
DTF4UZD3941K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	39	4400	112.8	4100	>80	50,000	- Emergency Back-Up
DTF4UZD3950K	39W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	39	4400	112.8	5000	>80	50,000	- Emergency Back-Up
DTF4UZD4630K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	46	5100	110.9	3000	>80	50,000	
DTF4UZD4635K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	46	5100	110.9	3500	>80	50,000	
DTF4UZD4641K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	46	5100	110.9	4100	>80	50,000	
DTF4UZD4650K	46W Flat Panel, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	46	5100	110.9	5000	>80	50,000	



AVAILABLE ACCESSORIES (ordered separately)

YHANGER6PK – Y Fit Cable Hanger 6 Pack
DRVEXTCABLE – 3 FT Driver Extension Cable

DTSK1 – 1X4 Direct Troffer Surface Mount Kit (White)
DTSK2 – 2X2 Direct Troffer Surface Mount Kit (White)
DTSK4 – 2X4 Direct Troffer Surface Mount Kit (White)

DTFLK1 – 1X4 Recess Mount Flange Kit
DTFLK2 – 2X2 Recess Mount Flange Kit
DTFLK4 – 2X4 Recess Mount Flange Kit



Many items are DLC QPL
Visit www.designlights.org/qpl for a full listing.

¹ Actual wattage may vary by +/- 10%.
² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.



Item Number

Item Description

Voltage

Dimming

Wattage¹

Lumens²

LPW

CCT (K)

CRI

Rated Life (hrs)

Options

50,000 HOUR LED DESIGNER SERIES WATTAGE SELECTABLE VOLUMETRIC LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

2x2 DESIGNER SERIES WATTAGE SELECTABLE VOLUMETRIC LUMINAIRES DAMP LOCATION RATED, SHIPPED FULLY ASSEMBLED WITH DETACHABLE DRIVER



Luxterior
by TCP

TRV2UZDA130K	23, 29, 38 Wattage Selectable Volumetric Troffer, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	23	3100	134.8	3000	>80	50,000
				29	3800	131			
				38	4800	126.3			
TRV2UZDA135K	23, 29, 38 Wattage Selectable Volumetric Troffer, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	23	3100	134.8	3500	>80	50,000
				29	3800	131			
				38	4800	126.3			
TRV2UZDA141K	23, 29, 38 Wattage Selectable Volumetric Troffer, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	23	3100	134.8	4100	>80	50,000
				29	3800	131			
				38	4800	126.3			
TRV2UZDA150K	23, 29, 38 Wattage Selectable Volumetric Troffer, 2x2, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	23	3100	134.8	5000	>80	50,000
				29	3800	131			
				38	4800	126.3			

2x4 DESIGNER SERIES WATTAGE SELECTABLE VOLUMETRIC LUMINAIRES DAMP LOCATION RATED, SHIPPED FULLY ASSEMBLED WITH DETACHABLE DRIVER



Luxterior
by TCP

TRV4UZDA130K	29, 38, 46 Wattage Selectable Volumetric Troffer, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 30K	120-277V	0-10V	29	4000	137.9	3000	>80	50,000
				38	5200	136.8			
				46	6000	130.4			
TRV4UZDA135K	29, 38, 46 Wattage Selectable Volumetric Troffer, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 35K	120-277V	0-10V	29	4000	137.9	3500	>80	50,000
				38	5200	136.8			
				46	6000	130.4			
TRV4UZDA141K	29, 38, 46 Wattage Selectable Volumetric Troffer, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 41K	120-277V	0-10V	29	4000	137.9	4100	>80	50,000
				38	5200	136.8			
				46	6000	130.4			
TRV4UZDA150K	29, 38, 46 Wattage Selectable Volumetric Troffer, 2x4, Frosted Diffuser Lens, 0-10V Dimming, 50K	120-277V	0-10V	29	4000	137.9	5000	>80	50,000
				38	5200	136.8			
				46	6000	130.4			

75,000 HOUR LED LINEAR LOW BAY LUMINAIRES

LED LINEAR LOW BAY



LB
by TCP

LB5600135	LED Linear Low Bay, All metal frame, 120-277V, 56W, 35K	120-277V	0-10V	56	6,700	119.6	3500	82	50,000	MOTION SENSOR GYZJ0001- Quick Snap Motion Sensor (available pre-assembled or in box)
LB5600140	LED Linear Low Bay, All metal frame, 120-277V, 56W, 40K	120-277V	0-10V	56	6,700	119.6	4000	82	50,000	
LB5600150	LED Linear Low Bay, All metal frame, 120-277V, 56W, 50K	120-277V	0-10V	56	6,700	119.6	5000	82	50,000	

50,000 HOUR LED LINEAR HIGH BAY LUMINAIRES

HB BY TCP LED LINEAR HIGH BAY



HB
by TCP

HB9000140	LED Linear High Bay, 120-277V, 90W, 40K	120-277V	0-10V	90	11,700	130	4000	82	50,000	LS1 - Factory Installed Motion Sensor (120, 277, 347v)
HB9000150	LED Linear High Bay, 120-277V, 90W, 50K	120-277V	0-10V	90	11,700	130	5000	82	50,000	
HB9000240	LED Linear High Bay, 347-480V, 90W, 40K	347-480V	0-10V	90	11,700	130	4000	82	50,000	
HB9000250	LED Linear High Bay, 347-480V, 90W, 50K	347-480V	0-10V	90	11,700	130	5000	82	50,000	LS1D - Factory Installed Motion Sensor w/ Daylight Harvesting (120, 277, 347v)
HB10500140	LED Linear High Bay, 120-277V, 105W, 40K	120-277V	0-10V	105	13,650	130	4000	82	50,000	
HB10500150	LED Linear High Bay, 120-277V, 105W, 50K	120-277V	0-10V	105	13,650	130	5000	82	50,000	
HB10500240	LED Linear High Bay, 347-480V, 105W, 40K	347-480V	0-10V	105	13,650	130	4000	82	50,000	LS4 - Factory Installed Motion Sensor (480v)
HB10500250	LED Linear High Bay, 347-480V, 105W, 50K	347-480V	0-10V	105	13,650	130	5000	82	50,000	
HB15000140	LED Linear High Bay, 120-277V, 150W, 40K	120-277V	0-10V	150	19,500	130	4000	82	50,000	
HB15000150	LED Linear High Bay, 120-277V, 150W, 50K	120-277V	0-10V	150	19,500	130	5000	82	50,000	HB1WG - Wire Guard for HB105W and HB150W
HB15000240	LED Linear High Bay, 347-480V, 150W, 40K	347-480V	0-10V	150	19,500	130	4000	82	50,000	
HB15000250	LED Linear High Bay, 347-480V, 150W, 50K	347-480V	0-10V	150	19,500	130	5000	82	50,000	
HB17500140	LED Linear High Bay, 120-277V, 175W, 40K	120-277V	0-10V	175	22,750	130	4000	82	50,000	HB2WG - Wire Guard for HB210W
HB17500150	LED Linear High Bay, 120-277V, 175W, 50K	120-277V	0-10V	175	22,750	130	5000	82	50,000	
HB17500240	LED Linear High Bay, 347-480V, 175W, 40K	347-480V	0-10V	175	22,750	130	4000	82	50,000	
HB17500250	LED Linear High Bay, 347-480V, 175W, 50K	347-480V	0-10V	175	22,750	130	5000	82	50,000	OT00040 - Replacement Lens Panel for HB105W and HB150W
HB21000140	LED Linear High Bay, 120-277V, 210W, 40K	120-277V	0-10V	210	27,300	130	4000	82	50,000	
HB21000150	LED Linear High Bay, 120-277V, 210W, 50K	120-277V	0-10V	210	27,300	130	5000	82	50,000	
HB21000240	LED Linear High Bay, 347-480V, 210W, 40K	347-480V	0-10V	210	27,300	130	4000	82	50,000	OT00040A - Replacement Lens Panel for 210W
HB21000250	LED Linear High Bay, 347-480V, 210W, 50K	347-480V	0-10V	210	27,300	130	5000	82	50,000	



Many items are DLC QPL. Visit www.designlights.org/qpl for a full listing.

AVAILABLE ACCESSORIES (ordered separately)

YHANGER6PK - Y Fit Cable Hanger 6 Pack
DRVEXTCABLE - 3 FT Driver Extension Cable

FPSK1 - 1X4 Flat Panel Surface Mount Kit (White)
FPSK2 - 2X2 Flat Panel Surface Mount Kit (White)
FPSK4 - 2X4 Flat Panel Surface Mount Kit (White)

DTFLK1 - 1X4 Recess Mount Flange Kit
DTFLK2 - 2X2 Recess Mount Flange Kit
DTFLK4 - 2X4 Recess Mount Flange Kit

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

50,000 HOUR LED IB SERIES HIGH BAY LUMINAIRES

IB SERIES LED 2 FOOT LINEAR HIGH BAY

IB2UZDE140K	LED 2 Foot Linear High Bay, 120-277V, 90W, 40K	120-277V	0-10V	90	11,700	130	4000	82	50,000	
IB2UZDE150K	LED 2 Foot Linear High Bay, 120-277V, 90W, 50K	120-277V	0-10V	90	11,700	130	5000	82	50,000	
IB2UZDA140K	LED 2 Foot Linear High Bay, 120-277V, 105W, 40K	120-277V	0-10V	105	13,650	130	4000	82	50,000	
IB2UZDA150K	LED 2 Foot Linear High Bay, 120-277V, 105W, 50K	120-277V	0-10V	105	13,650	130	5000	82	50,000	
IB2UZDA240K	LED 2 Foot Linear High Bay, 120-277V, 150W, 40K	120-277V	0-10V	150	19,500	130	4000	82	50,000	LS1 - Factory Installed Motion Sensor
IB2UZDA250K	LED 2 Foot Linear High Bay, 120-277V, 150W, 50K	120-277V	0-10V	150	19,500	130	5000	82	50,000	LS1D - Factory Installed Motion Sensor w/ Daylight Harvesting 10C - 10' Cord, No Plug
IB2UZDE240K	LED 2 Foot Linear High Bay, 120-277V, 175W, 40K	120-277V	0-10V	175	22,750	130	4000	82	50,000	
IB2UZDE250K	LED 2 Foot Linear High Bay, 120-277V, 175W, 50K	120-277V	0-10V	175	22,750	130	5000	82	50,000	
IB2UZDA340K	LED 2 Foot Linear High Bay, 120-277V, 210W, 40K	120-277V	0-10V	210	27,300	130	4000	82	50,000	
IB2UZDA350K	LED 2 Foot Linear High Bay, 120-277V, 210W, 50K	120-277V	0-10V	210	27,300	130	5000	82	50,000	



IB SERIES LED 3 FOOT LINEAR HIGH BAY

IB3UZDA440K	LED 3 Foot Linear High Bay, 120-277V, 310W, 40K	120-277V	0-10V	310	40,300	130	4000	82	50,000	LS1 - Factory Installed Motion Sensor
IB3UZDA450K	LED 3 Foot Linear High Bay, 120-277V, 310W, 50K	120-277V	0-10V	310	40,300	130	5000	82	50,000	LS1D - Factory Installed Motion Sensor w/ Daylight Harvesting 10C - 10' Cord, No Plug



IB SERIES LED 4 FOOT LINEAR HIGH BAY

IB4UZDA540K	LED 4 Foot Linear High Bay, 120-277V, 410W, 40K	120-277V	0-10V	410	53,000	129.2	4000	82	50,000	LS1 - Factory Installed Motion Sensor
IB4UZDA550K	LED 4 Foot Linear High Bay, 120-277V, 410W, 50K	120-277V	0-10V	410	53,000	129.2	5000	82	50,000	LS1D - Factory Installed Motion Sensor w/ Daylight Harvesting 10C - 10' Cord, No Plug



Many items are DLC QPL
Visit www.designlights.org/qpl for a full listing.

¹ Actual wattage may vary by +/- 10%.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Options
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	---------

50,000 HOUR LED UFO HIGH BAY LUMINAIRES

LED UFO 11" High Bay LUMINAIRES



Industra
by TCP

UF0UZDB140K	LED UFO High Bay, 120-277V, 100W, 40K	120-277V	0-10V	100	14,000	140	4000	>80	50,000	
UF0UZDB150K	LED UFO High Bay, 120-277V, 100W, 50K	120-277V	0-10V	100	14,000	140	5000	>80	50,000	
UF0UZDB240K	LED UFO High Bay, 120-277V, 150W, 40K	120-277V	0-10V	150	21,000	140	4000	>80	50,000	
UF0UZDB250K	LED UFO High Bay, 120-277V, 150W, 50K	120-277V	0-10V	150	21,000	140	5000	>80	50,000	
UF0UZDB340K	LED UFO High Bay, 120-277V, 200W, 40K	120-277V	0-10V	200	29,000	145	4000	>80	50,000	
UF0UZDB350K	LED UFO High Bay, 120-277V, 200W, 50K	120-277V	0-10V	200	29,000	145	5000	>80	50,000	

LED UFO 14.25" High Bay LUMINAIRES



Industra
by TCP

UF0UZDB440K	LED UFO High Bay, 120-277V, 240W, 40K	120-277V	0-10V	240	34,800	145	4000	>80	50,000	
UF0UZDB450K	LED UFO High Bay, 120-277V, 240W, 50K	120-277V	0-10V	240	34,800	145	5000	>80	50,000	
UF0UZDB540K	LED UFO High Bay, 120-277V, 300W, 40K	120-277V	0-10V	300	43,500	145	4000	>80	50,000	
UF0UZDB550K	LED UFO High Bay, 120-277V, 300W, 50K	120-277V	0-10V	300	43,500	145	5000	>80	50,000	

50,000 HOUR LED ROUND HIGH BAY LUMINAIRES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED ROUND HIGH BAY GEN 2, WET LOCATION RATED, IP65



Industra
by TCP



HBRUZDA240K	Round High Bay, 120-277V, 15,000L, 100W, 0-10V Dimming, 40K	120-277V	0-10V	100	15,000	150	4000	80	50,000	
HBRUZDA250K	Round High Bay, 120-277V, 15,000L, 100W, 0-10V Dimming, 50K	120-277V	0-10V	100	15,000	150	5000	80	50,000	
HBRHZA240K	Round High Bay, 347-480V, 15,000L, 100W, 0-10V Dimming, 40K	347-480V	0-10V	100	15,000	150	4000	80	50,000	
HBRHZA250K	Round High Bay, 347-480V, 15,000L, 100W, 0-10V Dimming, 50K	347-480V	0-10V	100	15,000	150	5000	80	50,000	
HBRUZDA340K	Round High Bay, 120-277V, 22,500L, 150W, 0-10V Dimming, 40K	120-277V	0-10V	150	22,500	150	4000	80	50,000	
HBRUZDA350K	Round High Bay, 120-277V, 22,500L, 150W, 0-10V Dimming, 50K	120-277V	0-10V	150	22,500	150	5000	80	50,000	
HBRHZA340K	Round High Bay, 347-480V, 22,500L, 150W, 0-10V Dimming, 40K	347-480V	0-10V	150	22,500	150	4000	80	50,000	
HBRHZA350K	Round High Bay, 347-480V, 22,500L, 150W, 0-10V Dimming, 50K	347-480V	0-10V	150	22,500	150	5000	80	50,000	
HBRUZDA440K	Round High Bay, 120-277V, 30,000L, 200W, 0-10V Dimming, 40K	120-277V	0-10V	200	30,000	150	4000	80	50,000	
HBRUZDA450K	Round High Bay, 120-277V, 30,000L, 200W, 0-10V Dimming, 50K	120-277V	0-10V	200	30,000	150	5000	80	50,000	
HBRHZA440K	Round High Bay, 347-480V, 30,000L, 200W, 0-10V Dimming, 40K	347-480V	0-10V	200	30,000	150	4000	80	50,000	
HBRHZA450K	Round High Bay, 347-480V, 30,000L, 200W, 0-10V Dimming, 50K	347-480V	0-10V	200	30,000	150	5000	80	50,000	
HBRUZDA540K	Round High Bay, 120-277V, 36,000L, 240W, 0-10V Dimming, 40K	120-277V	0-10V	240	36,000	150	4000	80	50,000	
HBRUZDA550K	Round High Bay, 120-277V, 36,000L, 240W, 0-10V Dimming, 50K	120-277V	0-10V	240	36,000	150	5000	80	50,000	
HBRHZA540K	Round High Bay, 347-480V, 36,000L, 240W, 0-10V Dimming, 40K	347-480V	0-10V	240	36,000	150	4000	80	50,000	
HBRHZA550K	Round High Bay, 347-480V, 36,000L, 240W, 0-10V Dimming, 50K	347-480V	0-10V	240	36,000	150	5000	80	50,000	

AVAILABLE ACCESSORIES (ordered separately)

- HBRPMA34 – ¾" Pendant mount adapter (100W & 150W models)
- HBRPMA34B – ¾" Pendant mount adapter (200W & 240W models)
- HBRPMB34 – ¾" Pendant mount adapter w/junction
- HBRSENSOR3 – Wet location rated daylight harvesting occupancy sensor 120/277/347V

- HBRSENSOR1 – Wet location rated daylight harvesting occupancy sensor 120/277V
- HBRALUM90 – 90 degree aluminum reflector
- HBRACREFL – Acrylic refractor
- HBRACLENS – Acrylic lens for HBRACREFL



Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Power Factor
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	--------------

50,000 HOUR LED VAPOR TIGHT (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED 2 FOOT VAPOR TIGHT, cULus WET LOCATION RATED, FROSTED LENS

VTF2UZDA140K	2 Foot, 24W, LED Vapor Tight, 40K	120-277V	No	24	3100	130	4000	80+	50,000	≥0.9
VTF2UZDA150K	2 Foot, 24W, LED Vapor Tight, 50K	120-277V	No	24	3100	130	5000	80+	50,000	≥0.9



LED 4 FOOT VAPOR TIGHT, cULus WET LOCATION RATED, FROSTED LENS

VTF4UZDA140K	4 Foot, 20W, LED Vapor Tight, 40K	120-277V	No	20	2600	130	4000	80+	50,000	≥0.9
VTF4UZDA150K	4 Foot, 20W, LED Vapor Tight, 50K	120-277V	No	20	2600	130	5000	80+	50,000	≥0.9
VTF4UZDA240K	4 Foot, 40W, LED Vapor Tight, 40K	120-277V	No	40	5400	135	4000	80+	50,000	≥0.9
VTF4UZDA250K	4 Foot, 40W, LED Vapor Tight, 50K	120-277V	No	40	5400	135	5000	80+	50,000	≥0.9



LED 8 FOOT VAPOR TIGHT, cULus WET LOCATION RATED, FROSTED LENS

VTF8UZDA140K	8 Foot, 65W, LED Vapor Tight, 40K	120-277V	No	65	8775	135	4000	80+	50,000	≥0.9
VTF8UZDA150K	8 Foot, 65W, LED Vapor Tight, 50K	120-277V	No	65	8775	135	5000	80+	50,000	≥0.9



50,000 HOUR LED WRAP LIGHT (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED WRAP LIGHT, DAMP LOCATION RATED

LWR2300135	4 Foot, 24W, 0-10V Dimming, LED Wrap Light, 35K	120-277V	0-10V	24	3500	145.8	3500	80+	50,000	≥0.9
LWR2300140	4 Foot, 24W, 0-10V Dimming, LED Wrap Light, 40K	120-277V	0-10V	24	3500	145.8	4000	80+	50,000	≥0.9
LWR2300150	4 Foot, 24W, 0-10V Dimming, LED Wrap Light, 50K	120-277V	0-10V	24	3500	145.8	5000	80+	50,000	≥0.9
LWR4000135	4 Foot, 40W, 0-10V Dimming, LED Wrap Light, 35K	120-277V	0-10V	40	4700	117.5	3500	80+	50,000	≥0.9
LWR4000140	4 Foot, 40W, 0-10V Dimming, LED Wrap Light, 40K	120-277V	0-10V	40	4750	118.8	4000	80+	50,000	≥0.9
LWR4000150	4 Foot, 40W, 0-10V Dimming, LED Wrap Light, 50K	120-277V	0-10V	40	4850	121.3	5000	80+	50,000	≥0.9
LWR6300135	4 Foot, 63W, 0-10V Dimming, LED Wrap Light, 35K	120-277V	0-10V	63	7700	122.2	3500	80+	50,000	≥0.9
LWR6300140	4 Foot, 63W, 0-10V Dimming, LED Wrap Light, 40K	120-277V	0-10V	63	7900	125.4	4000	80+	50,000	≥0.9
LWR6300150	4 Foot, 63W, 0-10V Dimming, LED Wrap Light, 50K	120-277V	0-10V	63	8050	127.8	5000	80+	50,000	≥0.9



Many items are DLC GPL.
Visit www.designlights.org/qpl for a full listing.

¹ Actual wattage may vary by +/- 10%.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

For the most up-to-date specs and warranty information, please visit www.tcpi.com



5 YEAR
WARRANTY



Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT (K)	CRI	Rated Life (hrs)	Power Factor
-------------	------------------	---------	---------	----------------------	---------------------	-----	---------	-----	------------------	--------------

50,000 HOUR LED GENERAL PURPOSE STRIP/ LOW BAY LUMINAIRE (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED GENERAL PURPOSE STRIPS, DAMP LOCATION RATED



TCPGPS2UZDA835K	2 Foot, 18W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	20	2600	130	3500	80	50,000	≥0.9
TCPGPS2UZDA840K	2 Foot, 18W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	20	2600	130	4000	80	50,000	≥0.9
TCPGPS2UZDA850K	2 Foot, 18W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	20	2600	130	5000	80	50,000	≥0.9
TCPGPS4UZDC835K	4 Foot, 25W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	25	3250	130	3500	80	50,000	≥0.9
TCPGPS4UZDC840K	4 Foot, 25W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	25	3250	130	4000	80	50,000	≥0.9
TCPGPS4UZDC850K	4 Foot, 25W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	25	3250	130	5000	80	50,000	≥0.9
TCPGPS4UZDA835K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	32	4200	130	3500	80	50,000	≥0.9
TCPGPS4UZDA840K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	32	4200	130	4000	80	50,000	≥0.9
TCPGPS4UZDA850K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	32	4200	130	5000	80	50,000	≥0.9
TCPGPS4UZDB840K	4 Foot, 18W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	18	2300	130	4000	80	50,000	≥0.9
TCPGPS4UZDB850K	4 Foot, 18W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	18	2300	130	5000	80	50,000	≥0.9
TCPGPS4HZDA835K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 35K	347V	0-10V	32	4200	130	3500	80	50,000	≥0.9
TCPGPS4HZDA840K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 40K	347V	0-10V	32	4200	130	4000	80	50,000	≥0.9
TCPGPS4HZDA850K	4 Foot, 32W, 0-10V Dimming, General Purpose Strip, 50K	347V	0-10V	32	4200	130	5000	80	50,000	≥0.9
TCPGPS4UZDE835K	4 Foot, 40W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	40	5200	130	3500	80	50,000	≥0.9
TCPGPS4UZDE840K	4 Foot, 40W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	40	5200	130	4000	80	50,000	≥0.9
TCPGPS4UZDE850K	4 Foot, 40W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	40	5200	130	5000	80	50,000	≥0.9
TCPGPS8UZDA835K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	65	8500	130	3500	80	50,000	≥0.9
TCPGPS8UZDA840K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	65	8500	130	4000	80	50,000	≥0.9
TCPGPS8UZDA850K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	65	8500	130	5000	80	50,000	≥0.9
TCPGPS8UZDB840K	8 Foot, 38W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	38	4900	130	4000	80	50,000	≥0.9
TCPGPS8UZDB850K	8 Foot, 38W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	38	4900	130	5000	80	50,000	≥0.9
TCPGPS8HZDA835K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 35K	347V	0-10V	65	8500	130	3500	80	50,000	≥0.9
TCPGPS8HZDA840K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 40K	347V	0-10V	65	8500	130	4000	80	50,000	≥0.9
TCPGPS8HZDA850K	8 Foot, 65W, 0-10V Dimming, General Purpose Strip, 50K	347V	0-10V	65	8500	130	5000	80	50,000	≥0.9
TCPGPS8UZDE835K	8 Foot, 75W, 0-10V Dimming, General Purpose Strip, 35K	120-277V	0-10V	75	9750	130	3500	80	50,000	≥0.9
TCPGPS8UZDE840K	8 Foot, 75W, 0-10V Dimming, General Purpose Strip, 40K	120-277V	0-10V	75	9750	130	4000	80	50,000	≥0.9
TCPGPS8UZDE850K	8 Foot, 75W, 0-10V Dimming, General Purpose Strip, 50K	120-277V	0-10V	75	9750	130	5000	80	50,000	≥0.9

50,000 HOUR LED GENERAL PURPOSE STRIP RETROFIT KIT (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED GENERAL PURPOSE STRIP RETROFIT KITS, DAMP LOCATION RATED



TCPGPR4UZDA835K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 35K	120-277V	0-10V	32	4200	130	3500	80	50,000	≥0.9
TCPGPR4UZDA840K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	120-277V	0-10V	32	4200	130	4000	80	50,000	≥0.9
TCPGPR4UZDA850K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	120-277V	0-10V	32	4200	130	5000	80	50,000	≥0.9
TCPGPR4HZDA835K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 35K	347-480V	0-10V	32	4200	130	3500	80	50,000	≥0.9
TCPGPR4HZDA840K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	347-480V	0-10V	32	4200	130	4000	80	50,000	≥0.9
TCPGPR4HZDA850K	4 Foot, 32W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	347-480V	0-10V	32	4200	130	5000	80	50,000	≥0.9
TCPGPR8UZDA835K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 35K	120-277V	0-10V	65	8500	130	3500	80	50,000	≥0.9
TCPGPR8UZDA840K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	120-277V	0-10V	65	8500	130	4000	80	50,000	≥0.9
TCPGPR8UZDA850K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	120-277V	0-10V	65	8500	130	5000	80	50,000	≥0.9
TCPGPR8HZDA835K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 35K	347-480V	0-10V	65	8500	130	3500	80	50,000	≥0.9
TCPGPR8HZDA840K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	347-480V	0-10V	65	8500	130	4000	80	50,000	≥0.9
TCPGPR8HZDA850K	8 Foot, 65W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	347-480V	0-10V	65	8500	130	5000	80	50,000	≥0.9
TCPGPR4UZDB840K	4 Foot, 18W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	120-277V	0-10V	18	2300	130	4000	80	50,000	≥0.9
TCPGPR4UZDB850K	4 Foot, 18W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	120-277V	0-10V	18	2300	130	5000	80	50,000	≥0.9
TCPGPR8UZDB840K	8 Foot, 38W, 0-10V Dimming, GP Strip Retrofit Kit, 40K	120-277V	0-10V	38	4900	130	4000	80	50,000	≥0.9
TCPGPR8UZDB850K	8 Foot, 38W, 0-10V Dimming, GP Strip Retrofit Kit, 50K	120-277V	0-10V	38	4900	130	5000	80	50,000	≥0.9

10



Many items are DLC QPL.
Visit www.designlights.org/apl for a full listing.

¹ Actual wattage may vary by +/- 10%.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

For the most up-to-date specs and warranty information, please visit www.tcpinc.com

Item Number

Item Description

Voltage Dimming Wattage¹ Lumens² LPW CCT(K) CRI Rated Life (hrs)

50,000 HOUR LED COMMERCIAL DOWNLIGHTS
18W 6" LED COMMERCIAL DOWNLIGHT (100W REPLACEMENT)

DLC618UZD27K	Round Commercial Downlight, 120-277V, 1,800L, 18W, 0-10V Dimming, 27K	120-277V	0-10V	18W	1,800	100	2700K	80	50,000
DLC618UZD30K	Round Commercial Downlight, 120-277V, 1,800L, 18W, 0-10V Dimming, 30K	120-277V	0-10V	18W	1,800	100	3000K	80	50,000
DLC618UZD35K	Round Commercial Downlight, 120-277V, 1,800L, 18W, 0-10V Dimming, 35K	120-277V	0-10V	18W	1,800	100	3500K	80	50,000
DLC618UZD41K	Round Commercial Downlight, 120-277V, 1,800L, 18W, 0-10V Dimming, 41K	120-277V	0-10V	18W	1,800	100	4100K	80	50,000
DLC618UZD50K	Round Commercial Downlight, 120-277V, 1,800L, 18W, 0-10V Dimming, 50K	120-277V	0-10V	18W	1,800	100	5000K	80	50,000



Industra
by TCP

24W 8" LED COMMERCIAL DOWNLIGHT (125W REPLACEMENT)

DLC824UZD27K	Round Commercial Downlight, 120-277V, 2,400L, 24W, 0-10V Dimming, 27K	120-277V	0-10V	24W	2,400	100	2700K	80	50,000
DLC824UZD30K	Round Commercial Downlight, 120-277V, 2,400L, 24W, 0-10V Dimming, 30K	120-277V	0-10V	24W	2,400	100	3000K	80	50,000
DLC824UZD35K	Round Commercial Downlight, 120-277V, 2,400L, 24W, 0-10V Dimming, 35K	120-277V	0-10V	24W	2,400	100	3500K	80	50,000
DLC824UZD41K	Round Commercial Downlight, 120-277V, 2,400L, 24W, 0-10V Dimming, 41K	120-277V	0-10V	24W	2,400	100	4100K	80	50,000
DLC824UZD50K	Round Commercial Downlight, 120-277V, 2,400L, 24W, 0-10V Dimming, 50K	120-277V	0-10V	24W	2,400	100	5000K	80	50,000



Industra
by TCP

30W 10" LED COMMERCIAL DOWNLIGHT (150W REPLACEMENT)

DLC1030UZD27K	Round Commercial Downlight, 120-277V, 3,000L, 30W, 0-10V Dimming, 27K	120-277V	0-10V	30W	3,000	100	2700K	80	50,000
DLC1030UZD30K	Round Commercial Downlight, 120-277V, 3,000L, 30W, 0-10V Dimming, 30K	120-277V	0-10V	30W	3,000	100	3000K	80	50,000
DLC1030UZD35K	Round Commercial Downlight, 120-277V, 3,000L, 30W, 0-10V Dimming, 35K	120-277V	0-10V	30W	3,000	100	3500K	80	50,000
DLC1030UZD41K	Round Commercial Downlight, 120-277V, 3,000L, 30W, 0-10V Dimming, 41K	120-277V	0-10V	30W	3,000	100	4100K	80	50,000
DLC1030UZD50K	Round Commercial Downlight, 120-277V, 3,000L, 30W, 0-10V Dimming, 50K	120-277V	0-10V	30W	3,000	100	5000K	80	50,000



50W 10" LED COMMERCIAL DOWNLIGHT (175W REPLACEMENT)

DLC1050UZD27K	Round Commercial Downlight, 120-277V, 5,000L, 50W, 0-10V Dimming, 27K	120-277V	0-10V	50W	5,000	100	2700K	80	50,000
DLC1050UZD30K	Round Commercial Downlight, 120-277V, 5,000L, 50W, 0-10V Dimming, 30K	120-277V	0-10V	50W	5,000	100	3000K	80	50,000
DLC1050UZD35K	Round Commercial Downlight, 120-277V, 5,000L, 50W, 0-10V Dimming, 35K	120-277V	0-10V	50W	5,000	100	3500K	80	50,000
DLC1050UZD41K	Round Commercial Downlight, 120-277V, 5,000L, 50W, 0-10V Dimming, 41K	120-277V	0-10V	50W	5,000	100	4100K	80	50,000
DLC1050UZD50K	Round Commercial Downlight, 120-277V, 5,000L, 50W, 0-10V Dimming, 50K	120-277V	0-10V	50W	5,000	100	5000K	80	50,000



Industra
by TCP

45W 12" LED COMMERCIAL DOWNLIGHT (150W REPLACEMENT)

DLC1245UZD27K	Round Commercial Downlight, 120-277V, 4,500L, 45W, 0-10V Dimming, 27K	120-277V	0-10V	45W	4,500	100	2700K	80	50,000
DLC1245UZD30K	Round Commercial Downlight, 120-277V, 4,500L, 45W, 0-10V Dimming, 30K	120-277V	0-10V	45W	4,500	100	3000K	80	50,000
DLC1245UZD35K	Round Commercial Downlight, 120-277V, 4,500L, 45W, 0-10V Dimming, 35K	120-277V	0-10V	45W	4,500	100	3500K	80	50,000
DLC1245UZD41K	Round Commercial Downlight, 120-277V, 4,500L, 45W, 0-10V Dimming, 41K	120-277V	0-10V	45W	4,500	100	4100K	80	50,000
DLC1245UZD50K	Round Commercial Downlight, 120-277V, 4,500L, 45W, 0-10V Dimming, 50K	120-277V	0-10V	45W	4,500	100	5000K	80	50,000



60W 12" LED COMMERCIAL DOWNLIGHT (200W REPLACEMENT)

DLC1260UZD27K	Round Commercial Downlight, 120-277V, 6,000L, 60W, 0-10V Dimming, 27K	120-277V	0-10V	60W	6,000	100	2700K	80	50,000
DLC1260UZD30K	Round Commercial Downlight, 120-277V, 6,000L, 60W, 0-10V Dimming, 30K	120-277V	0-10V	60W	6,000	100	3000K	80	50,000
DLC1260UZD35K	Round Commercial Downlight, 120-277V, 6,000L, 60W, 0-10V Dimming, 35K	120-277V	0-10V	60W	6,000	100	3500K	80	50,000
DLC1260UZD41K	Round Commercial Downlight, 120-277V, 6,000L, 60W, 0-10V Dimming, 41K	120-277V	0-10V	60W	6,000	100	4100K	80	50,000
DLC1260UZD50K	Round Commercial Downlight, 120-277V, 6,000L, 60W, 0-10V Dimming, 50K	120-277V	0-10V	60W	6,000	100	5000K	80	50,000

Industra
by TCP

Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing

¹ Actual wattage may vary by +/- 10%.
² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

For the most up-to-date specs and warranty information, please visit www.tcpi.com



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	Beam Angle	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	-----	------------	-----	---------------

35,000 HOUR RECESSED LED DOWNLIGHTS

10W 4" RECESSED DOWNLIGHTS (75W REPLACEMENT)



LED10DR427K	LED 10W 4" Recessed Downlight - 2700K	120	10	75W	750	75.0	2700K	120	80	6
LED10DR430K	LED 10W 4" Recessed Downlight - 3000K	120	10	75W	750	75.0	3000K	120	80	6
LED10DR441K	LED 10W 4" Recessed Downlight - 4100K	120	10	75W	800	80.0	4100K	120	80	6
LED10DR450K	LED 10W 4" Recessed Downlight - 5000K	120	10	75W	800	80.0	5000K	120	80	6

12W 5/6" RECESSED DOWNLIGHTS (120W REPLACEMENT)



LED14DR5627K	LED 12W 5/6" Recessed Downlight - 2700K	120	12	120W	1250	104.2	2700K	120	80	6
LED14DR5630K	LED 12W 5/6" Recessed Downlight - 3000K	120	12	120W	1300	108.3	3000K	120	80	6
LED14DR5641K	LED 12W 5/6" Recessed Downlight - 4100K	120	12	120W	1300	108.3	4100K	120	80	6
LED14DR5650K	LED 12W 5/6" Recessed Downlight - 5000K	120	12	120W	1350	112.5	5000K	120	80	6

9.5W 5/6" RECESSED DOWNLIGHTS (85W REPLACEMENT)

LED11DR5627K	LED 9.5W 5/6" Recessed Downlight - 2700K	120	9.5	75W	850	89.5	2700K	100	80	6
LED11DR5630K	LED 9.5W 5/6" Recessed Downlight - 3000K	120	9.5	75W	850	89.5	3000K	100	80	6
LED11DR5641K	LED 9.5W 5/6" Recessed Downlight - 4100K	120	9.5	75W	875	92.1	4100K	100	80	6
LED11DR5650K	LED 9.5W 5/6" Recessed Downlight - 5000K	120	9.5	75W	900	94.7	5000K	100	80	6

35,000 HOUR LED HI CRI RECESSED DOWNLIGHTS

9W 4" LED HI CRI RECESSED DOWNLIGHTS (50W REPLACEMENT)



L9DR4D3527K95	LED 9W 4" Hi CRI Recessed Downlight - 2700K	120	9	50W	550	61.1	2700K	120	90	6
L9DR4D3530K95	LED 9W 4" Hi CRI Recessed Downlight - 3000K	120	9	50W	600	66.7	3000K	120	90	6

12W 5/6" LED HI CRI RECESSED DOWNLIGHTS (65W REPLACEMENT)



L11DR56D3527K95	LED 11W 5/6" Hi CRI Recessed Downlight - 2700K	120	11	65W	700	63.6	2700K	120	90	6
L11DR56D3530K95	LED 11W 5/6" Hi CRI Recessed Downlight - 3000K	120	11	65W	750	68.2	3000K	120	90	6

40,000 HOUR LED DIMMABLE EDGELIT DOWNLIGHTS

8.5W 4" DIMMABLE EDGELIT DOWNLIGHTS (60W REPLACEMENT)



L9EL4D4027K	LED 8.5W 4" EdgELIT Downlight - 2700K	120	8.5	40W	500	58.8	2700K	120	80	6
L9EL4D4030K	LED 8.5W 4" EdgELIT Downlight - 3000K	120	8.5	40W	525	61.8	3000K	120	80	6
L9EL4D4040K	LED 8.5W 4" EdgELIT Downlight - 4000K	120	8.5	40W	550	64.7	4000K	120	80	6

11.6W 6" DIMMABLE EDGELIT DOWNLIGHTS (40W REPLACEMENT)



L12EL6D4027K	LED 11W 6" EdgELIT Downlight - 2700K	120	11.6	60W	800	69	2700K	120	80	6
L12EL6D4030K	LED 11W 6" EdgELIT Downlight - 3000K	120	11.6	60W	825	71.1	3000K	120	80	6
L12EL6D4040K	LED 11W 6" EdgELIT Downlight - 4000K	120	11.6	60W	850	73.3	4000K	120	80	6

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	Beam Angle	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	-----	------------	-----	---------------

35,000 HOUR LED BEVELED DESIGNER LOOK RECESSED DOWNLIGHTS
11W 4" RECESSED DOWNLIGHTS (75W REPLACEMENT)

L75DR4D3527K	LED 11W 4" Dim Recessed Downlight - 2700K	120	11	75W	850	77.3	2700K	120	80	6
L75DR4D3530K	LED 11W 4" Dim Recessed Downlight - 3000K	120	11	75W	850	77.3	3000K	120	80	6
L75DR4D3541K	LED 11W 4" Dim Recessed Downlight - 4100K	120	11	75W	850	77.3	4100K	120	80	6
L75DR4D3550K	LED 11W 4" Dim Recessed Downlight - 5000K	120	11	75W	850	77.3	5000K	120	80	6



16.5W 5 1/6" LED BEVELED DESIGNER RECESSED DOWNLIGHTS (120W REPLACEMENT)

L120DR56D3527K	LED 16.5W 5 1/6" Dim Recessed Downlight - 2700K	120	16.5	120W	1400	84.8	2700K	120	80	6
L120DR56D3530K	LED 16.5W 5 1/6" Dim Recessed Downlight - 3000K	120	16.5	120W	1400	84.8	3000K	120	80	6
L120DR56D3541K	LED 16.5W 5 1/6" Dim Recessed Downlight - 4100K	120	16.5	120W	1400	84.8	4100K	120	80	6
L120DR56D3550K	LED 16.5W 5 1/6" Dim Recessed Downlight - 5000K	120	16.5	120W	1400	84.8	5000K	120	80	6



12W 5 1/6" RECESSED DOWNLIGHTS (75W REPLACEMENT)

L75DR56D3527K	LED 12W 5 1/6" Dim Recessed Downlight - 2700K	120	12	75W	850	70.8	2700K	120	80	6
L75DR56D3530K	LED 12W 5 1/6" Dim Recessed Downlight - 3000K	120	12	75W	850	70.8	3000K	120	80	6
L75DR56D3541K	LED 12W 5 1/6" Dim Recessed Downlight - 4100K	120	12	75W	850	70.8	4100K	120	80	6
L75DR56D3550K	LED 12W 5 1/6" Dim Recessed Downlight - 5000K	120	12	75W	850	70.8	5000K	120	80	6

50,000 HOUR LED DIMMABLE JUNCTION BOX DOWNLIGHTS
11W 5 1/6" LED DIMMABLE JUNCTION BOX DOWNLIGHTS (75W REPLACEMENT)

SDL61D27K	LED 11W 5 1/6" Junction Box Disc Downlight - 2700K	120	11	75W	1100	100	2700K	120	80	6
SDL61D30K	LED 11W 5 1/6" Junction Box Disc Downlight - 3000K	120	11	75W	1100	100	3000K	120	80	6
SDL61D41K	LED 11W 5 1/6" Junction Box Disc Downlight - 4100K	120	11	75W	1100	100	4100K	120	80	6
SDL61D50K	LED 11W 5 1/6" Junction Box Disc Downlight - 5000K	120	11	75W	1100	100	5000K	120	80	6



40,000 HOUR LED DELUX SERIES ROUND SNAP-IN DOWNLIGHTS
14W 6" LED DELUX SERIES ROUND SNAP-IN DOWNLIGHTS (85W REPLACEMENT)

DDC61D27K	LED 14W 6" Round Snap-In Downlight - 2700K	120	14	85W	1100	78	2700K	110	80	6
DDC61D30K	LED 14W 6" Round Snap-In Downlight - 3000K	120	14	85W	1100	78	3000K	110	80	6
DDC61D35K	LED 14W 6" Round Snap-In Downlight - 3500K	120	14	85W	1100	78	3500K	110	80	6
DDC61D41K	LED 14W 6" Round Snap-In Downlight - 4100K	120	14	85W	1100	78	4100K	110	80	6
DDC61D50K	LED 14W 6" Round Snap-In Downlight - 5000K	120	14	85W	1100	78	5000K	110	80	6



6" LED DELUX SERIES ROUND SNAP-IN DOWNLIGHT TRIM RINGS

TR6BLK	Black 6" Trim Ring	20
TR6WHT	White 6" Trim Ring	20
TR6AGD	Antique Gold 6" Trim Ring	20
TR6SLV	Silver 6" Trim Ring	20
TR6RGD	Rose Gold 6" Trim Ring	20



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



Consult www.tcp.com for warranty information.



Item Number

Item Description

Voltage

Lamp Watts

Wattage Equivalent

Lumens

Lumens Per Watt

CCT


Beam Angle

CRI

Case Quantity

40,000 HOUR LED SQUARE SNAP-IN DOWNLIGHTS

13W 4" LED SQUARE SNAP-IN DOWNLIGHTS (60W REPLACEMENT)



DDR40227	LED 13W 4" Square Snap-In Downlight - 2700K	120	13	75W	750	57.7	2700K	110	80	6
DDR40230	LED 13W 4" Square Snap-In Downlight - 3000K	120	13	75W	750	57.7	3000K	110	80	6
DDR40240	LED 13W 4" Square Snap-In Downlight - 4000K	120	13	75W	750	57.7	4000K	110	80	6
DDR40250	LED 13W 4" Square Snap-In Downlight - 5000K	120	13	75W	750	57.7	5000K	110	80	6

14W 6" LED SQUARE SNAP-IN DOWNLIGHTS (75W REPLACEMENT)



DDR60227	LED 14W 6" Square Snap-In Downlight - 2700K	120	14	85W	1000	71.4	2700K	110	80	6
DDR60230	LED 14W 6" Square Snap-In Downlight - 3000K	120	14	85W	1000	71.4	3000K	110	80	6
DDR60240	LED 14W 6" Square Snap-In Downlight - 4000K	120	14	85W	1000	71.4	4000K	110	80	6
DDR60250	LED 14W 6" Square Snap-In Downlight - 5000K	120	14	85W	1000	71.4	5000K	110	80	6

18W 8" LED SQUARE SNAP-IN DOWNLIGHTS (100W REPLACEMENT)



DDR80227	LED 18W 8" Square Snap-In Downlight - 2700K	120	18	125W	1400	77.8	2700K	110	80	6
DDR80230	LED 18W 8" Square Snap-In Downlight - 3000K	120	18	125W	1400	77.8	3000K	110	80	6
DDR80240	LED 18W 8" Square Snap-In Downlight - 4000K	120	18	125W	1400	77.8	4000K	110	80	6
DDR80250	LED 18W 8" Square Snap-In Downlight - 5000K	120	18	125W	1400	77.8	5000K	110	80	6

40,000 HOUR LED ROUND SNAP-IN DOWNLIGHTS

13W 4" LED ROUND SNAP-IN DOWNLIGHTS (60W REPLACEMENT)



DDR40127	LED 13W 4" Round Snap-In Downlight - 2700K	120	13	75W	850	65.4	2700K	110	80	6
DDR40130	LED 13W 4" Round Snap-In Downlight - 3000K	120	13	75W	850	65.4	3000K	110	80	6
DDR40140	LED 13W 4" Round Snap-In Downlight - 4000K	120	13	75W	850	65.4	4000K	110	80	6
DDR40150	LED 13W 4" Round Snap-In Downlight - 5000K	120	13	75W	850	65.4	5000K	110	80	6

14W 6" LED ROUND SNAP-IN DOWNLIGHTS (75W REPLACEMENT)



DDR60127	LED 14W 6" Round Snap-In Downlight - 2700K	120	14	85W	1100	78.6	2700K	110	80	6
DDR60130	LED 14W 6" Round Snap-In Downlight - 3000K	120	14	85W	1100	78.6	3000K	110	80	6
DDR60140	LED 14W 6" Round Snap-In Downlight - 4000K	120	14	85W	1100	78.6	4000K	110	80	6
DDR60150	LED 14W 6" Round Snap-In Downlight - 5000K	120	14	85W	1100	78.6	5000K	110	80	6

18W 8" LED ROUND SNAP-IN DOWNLIGHTS (100W REPLACEMENT)



DDR80127	LED 18W 8" Round Snap-In Downlight - 2700K	120	18	125W	1550	86.1	2700K	110	80	6
DDR80130	LED 18W 8" Round Snap-In Downlight - 3000K	120	18	125W	1550	86.1	3000K	110	80	6
DDR80140	LED 18W 8" Round Snap-In Downlight - 4000K	120	18	125W	1550	86.1	4000K	110	80	6
DDR80150	LED 18W 8" Round Snap-In Downlight - 5000K	120	18	125W	1550	86.1	5000K	110	80	6

25,000 HOUR ALLUSION LED 10W 5/6" RECESSED DOWNLIGHTS WITH SMOOTH WARM DIMMING

Allusion™



LED10DR56DA	10W 5 5/8" Recessed Downlight	120	11	65W	1100	100	3000K to 2000K	120	80	6
-------------	-------------------------------	-----	----	-----	------	-----	----------------	-----	----	---



OUTDOOR LED LUMINAIRES



Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Controls	Finish
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	----------	--------

ELEMENTS LED ADJUSTABLE WALL PACK

LED ADJUSTABLE WALL PACK WET LOCATION RATED

FCWUZDA1T340KBRPC	Wall Pack, 120-277V, 0-10V Dimmable, Photocell, 4000K	120-277V	0-10V	40	4500	112.5	4000K	70	50,000	Photocell	Bronze
FCWUZDA1T350KBRPC	Wall Pack, 120-277V, 0-10V Dimmable, Photocell, 5000K	120-277V	0-10V	40	4500	112.5	5000K	70	50,000	Photocell	Bronze
FCWUZDA2T340KBRPC	Wall Pack, 120-277V, 0-10V Dimmable, Photocell, 4000K	120-277V	0-10V	90	9500	105	4000K	70	50,000	Photocell	Bronze
FCWUZDA2T350KBRPC	Wall Pack, 120-277V, 0-10V Dimmable, Photocell, 5000K	120-277V	0-10V	90	9500	105	5000K	70	50,000	Photocell	Bronze



Elements
by TCP

ELEMENTS LED WALL PACK

LED FULL CUTOFF WALL PACK WP40 WET LOCATION RATED

WP40UNIT341KBLK	WP40 Full Cutoff Wall Pack, Universal, Non-Dimmable	120-277V	--	40	4035	103	4100K	83	50,000	--	Black
WP40UNIT350KBLK	WP40 Full Cutoff Wall Pack, Universal, Non-Dimmable	120-277V	--	40	4035	103	5000K	83	50,000	--	Black



Elements
by TCP

LED FULL CUTOFF WALL PACK WP80 WET LOCATION RATED

WP80UNIT341KBLK	WP80 Full Cutoff Wall Pack, Universal, Non-Dimmable	120-277V	--	80	8400	108	4100K	83	50,000	--	Black
WP80UNIT350KBLK	WP80 Full Cutoff Wall Pack, Universal, Non-Dimmable	120-277V	--	80	8400	108	5000K	83	50,000	--	Black



Elements
by TCP

LED NON-CUTOFF WALL PACKS, ACRYLIC LENS WET LOCATION RATED

WP5500140	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K	120-277V	--	55	6900	125.5	4000K	80	50,000	--	Bronze
WP5500150	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K	120-277V	--	55	6900	125.5	5000K	80	50,000	--	Bronze
WP5500140PC	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K, Photocell	120-277V	--	55	6900	125.5	4000K	80	50,000	Photocell	Bronze
WP5500150PC	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K, Photocell	120-277V	--	55	6900	125.5	5000K	80	50,000	Photocell	Bronze
WP5500140MS	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K, Motion Sensor	120-277V	--	55	6900	125.5	4000K	80	50,000	Motion Sensor	Bronze
WP5500150MS	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K, Motion Sensor	120-277V	--	55	6900	125.5	5000K	80	50,000	Motion Sensor	Bronze
WP12000140	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K	120-277V	--	120	14500	120.8	4000K	80	50,000	--	Bronze
WP12000150	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K	120-277V	--	120	14500	120.8	5000K	80	50,000	--	Bronze
WP12000140PC	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K, Photocell	120-277V	--	120	14500	120.8	4000K	80	50,000	Photocell	Bronze
WP12000150PC	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K, Photocell	120-277V	--	120	14500	120.8	5000K	80	50,000	Photocell	Bronze
WP12000140MS	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 4000K, Microwave Motion Sensor	120-277V	--	120	14500	120.8	4000K	80	50,000	Motion Sensor	Bronze
WP12000150MS	Non-Cutoff Wall Pack, Universal, Non-Dimmable, 5000K, Microwave Motion Sensor	120-277V	--	120	14500	120.8	5000K	80	50,000	Motion Sensor	Bronze



Elements
by TCP

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Controls	Finish
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	----------	--------

LED NON-CUTOFF COMPACT WALL PACKS WET LOCATION RATED




WP1700150	Non-Cutoff Compact Wall Pack, 17W Universal, Non-Dimmable, 5000K	120-277V	-	17	1700	100	5000K	80	50,000	-	Bronze
WP1700140S	Non-Cutoff Compact Wall Pack, 17W Universal, Non-Dim, 4000K W/PC	120-277V	-	17	1700	100	4000K	80	50,000	Photocell	Bronze
WP1700150S	Non-Cutoff Compact Wall Pack, 17W Universal, Non-Dim, 5000K W/PC	120-277V	-	17	1700	100	5000K	80	50,000	Photocell	Bronze
WP2500150	Non-Cutoff Compact Wall Pack, 25W Universal, Non-Dimmable, 5000K	120-277V	-	25	2250	90	5000K	80	50,000	-	Bronze
WP2500140S	Non-Cutoff Compact Wall Pack, 25W Universal, Non-Dimmable, 4000K W/PC	120-277V	-	25	2250	90	4000K	80	50,000	Photocell	Bronze
WP2500150S	Non-Cutoff Compact Wall Pack, 25W Universal, Non-Dimmable, 5000K W/PC	120-277V	-	25	2250	90	5000K	80	50,000	Photocell	Bronze



Elements
by TCP

NEW LED CANOPY LIGHT WET LOCATION RATED



CP4500140	Small Canopy, Square, Universal, Non-Dimmable, Photocell	120-277V	-	45	5350	118.9	4000K	>80	50,000	-	Bronze
CP4500150	Small Canopy, Square, Universal, Non-Dimmable, Photocell	120-277V	-	45	5350	118.9	5000K	>80	50,000	-	Bronze
CP7000140	Small Canopy, Square, Universal, Non-Dimmable, Photocell	120-277V	-	70	7600	108.6	4000K	>80	50,000	-	Bronze
CP7000150	Small Canopy, Square, Universal, Non-Dimmable, Photocell	120-277V	-	70	7600	108.6	5000K	>80	50,000	-	Bronze

Elements
by TCP

ELEMENTS LED FLOOD LIGHTS (CONSULT SPEC SHEET FOR ORDERING MATRIX)

LED FLOOD LIGHTS - SMALL WET LOCATION RATED



FLKUA3W40KBR	Flood Light, Small, 120-277V, Non-Dimmable, Knuckle, Wide Beam, 4000K	120-277V	-	50	6250	125	4000K	70	50,000	-	Bronze
FLKUA3W50KBR	Flood Light, Small, 120-277V, Non-Dimmable, Knuckle, Wide Beam, 5000K	120-277V	-	50	6250	125	5000K	70	50,000	-	Bronze
FLYUA3W40KBR	Flood Light, Small, 120-277V, Non-Dimmable, Yoke, Wide Beam, 4000K	120-277V	-	50	6250	125	4000K	70	50,000	-	Bronze
FLYUA3W50KBR	Flood Light, Small, 120-277V, Non-Dimmable, Yoke, Wide Beam, 5000K	120-277V	-	50	6250	125	5000K	70	50,000	-	Bronze

Elements
by TCP

Item Number	Item Description	Voltage	Dimming	Wattage ¹	Lumens ²	LPW	CCT(K)	CRI	Rated Life (hrs)	Controls	Finish
-------------	------------------	---------	---------	----------------------	---------------------	-----	--------	-----	------------------	----------	--------

ELEMENTS LED POST TOP

LED POST TOP WET LOCATION RATED

PTUZDA1T540KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 4000K	120-277V	0-10V	75	9000	117	4000K	70	50,000	NEMA 7-Pin Photocell	Bronze
PTUZDA1T550KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 5000K	120-277V	0-10V	75	9000	117	5000K	70	50,000	NEMA 7-Pin Photocell	Bronze
PTUZDA2T540KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 4000K	120-277V	0-10V	100	12500	125	4000K	70	50,000	NEMA 7-Pin Photocell	Bronze
PTUZDA2T550KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 5000K	120-277V	0-10V	100	12500	125	5000K	70	50,000	NEMA 7-Pin Photocell	Bronze
PTUZDA3T540KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 4000K	120-277V	0-10V	150	18750	125	4000K	70	50,000	NEMA 7-Pin Photocell	Bronze
PTUZDA3T550KN7BR	LED Post Top, Universal, 120-277V, 0-10V Dimming, NEMA 7-Pin Photocell, 5000K	120-277V	0-10V	150	18750	125	5000K	70	50,000	NEMA 7-Pin Photocell	Bronze



Elements
by TCP

ELEMENTS LED BARN LIGHT LUMINAIRE

LED BARN LIGHT cULUS WET LOCATION RATED

SLUA140KN3BRZ	LED Barn Light, Non Dim, 120-277V, 3-Pin PC Rec., 4000K	120-277V	-	45	6400	142	4000	70	50,000	NEMA 3-Pin Photocell	Bronze
SLUA150KN3BRZ	LED Barn Light, Non Dim, 120-277V, 3-Pin PC Rec., 5000K	120-277V	-	45	6500	144	5000	70	50,000	NEMA 3-Pin Photocell	Bronze
SLUA240KN3BRZ	LED Barn Light, Non Dim, 120-277V, 3-Pin PC Rec., 4000K	120-277V	-	70	9500	136	4000	70	50,000	NEMA 3-Pin Photocell	Bronze
SLUA250KN3BRZ	LED Barn Light, Non Dim, 120-277V, 3-Pin PC Rec., 5000K	120-277V	-	70	9700	139	5000	70	50,000	NEMA 3-Pin Photocell	Bronze
SLUZDA140KN7BR	LED Barn Light, 0-10 Dim, 120-277V, 7-Pin PC Rec., 4000K	120-277V	0-10V	45	6400	142	4000	70	50,000	NEMA 7-Pin Photocell	Bronze
SLUZDA150KN7BR	LED Barn Light, 0-10 Dim, 120-277V, 7-Pin PC Rec., 5000K	120-277V	0-10V	45	6500	144	5000	70	50,000	NEMA 7-Pin Photocell	Bronze
SLUZDA240KN7BR	LED Barn Light, 0-10 Dim, 120-277V, 7-Pin PC Rec., 4000K	120-277V	0-10V	70	9500	136	4000	70	50,000	NEMA 7-Pin Photocell	Bronze
SLUZDA250KN7BR	LED Barn Light, 0-10 Dim, 120-277V, 7-Pin PC Rec., 5000K	120-277V	0-10V	70	9700	139	5000	70	50,000	NEMA 7-Pin Photocell	Bronze



Elements
by TCP

ELEMENTS LED SECURITY LIGHT LUMINAIRE

LED SECURITY LIGHT cULUS WET LOCATION RATED

RSLUA140KPCSV	LED Security Light, Non Dim, 120-277V, Button PC, 4000K	120-277V	-	27	3800	141	4000	70	50,000	-	Silver
RSLUA150KPCSV	LED Security Light, Non Dim, 120-277V, Button PC, 5000K	120-277V	-	27	3900	144	5000	70	50,000	-	Silver
RSLUA240KPCSV	LED Security Light, Non Dim, 120-277V, Button PC, 4000K	120-277V	-	40	5500	138	4000	70	50,000	-	Silver
RSLUA250KPCSV	LED Security Light, Non Dim, 120-277V, Button PC, 5000K	120-277V	-	40	5700	143	5000	70	50,000	-	Silver



Elements
by TCP

Item Number	Item Description ⁵	Voltage ¹	Dimming	Wattage ³	Lumens ²	LPW	Distribution ⁴	CCT(K)	CRI	Rated Life (hrs)	Finish
-------------	-------------------------------	----------------------	---------	----------------------	---------------------	-----	---------------------------	--------	-----	------------------	--------

ELEMENTS LED AREA LIGHT LUMINAIRE

LED AREA LIGHT LUMINAIRE cULus WET LOCATION RATED



Elements
by TCP



ALUZDA1T340KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 40K	120-277V	0-10V	100	13500	135	III	4000	70	50,000	Bronze
ALUZDA1T350KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 50K	120-277V	0-10V	100	13500	135	III	5000	70	50,000	Bronze
ALUZDB1T340KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 40K	120-277V	0-10V	150	20000	133.3	III	4000	70	50,000	Bronze
ALUZDB1T350KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 50K	120-277V	0-10V	150	20000	133.3	III	5000	70	50,000	Bronze
ALHZDB1T340KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 40K	347-480V	0-10V	150	20000	133.3	III	4000	70	50,000	Bronze
ALHZDB1T350KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 50K	347-480V	0-10V	150	20000	133.3	III	5000	70	50,000	Bronze
ALUZDA2T340KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 40K	120-277V	0-10V	200	26500	132.5	III	4000	70	50,000	Bronze
ALUZDA2T350KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 50K	120-277V	0-10V	200	26500	132.5	III	5000	70	50,000	Bronze
ALHZDA2T340KN7BR	LED Area Light, 0-10V Dimming, 347-480V, Photocell, 40K	347-480V	0-10V	200	26500	132.5	III	4000	70	50,000	Bronze
ALHZDA2T350KN7BR	LED Area Light, 0-10V Dimming, 347-480V, Photocell, 50K	347-480V	0-10V	200	26500	132.5	III	5000	70	50,000	Bronze
ALUZDA3T340KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 40K	120-277V	0-10V	300	40000	133.3	III	4000	70	50,000	Bronze
ALUZDA3T350KN7BR	LED Area Light, 0-10V Dimming, 120-277V, Photocell, 50K	120-277V	0-10V	300	40000	133.3	III	5000	70	50,000	Bronze
ALHZDA3T340KN7BR	LED Area Light, 0-10V Dimming, 347-480V, Photocell, 40K	347-480V	0-10V	300	40000	133.3	III	4000	70	50,000	Bronze
ALHZDA3T350KN7BR	LED Area Light, 0-10V Dimming, 347-480V, Photocell, 50K	347-480V	0-10V	300	40000	133.3	III	5000	70	50,000	Bronze

FACTORY INSTALLED OPTIONS (add to catalog number)

Motion Sensor
MS - PIR Motion Sensor with Daylight Harvesting and Bi-Level Dimming.
Not available on A1 or 347/480V models.

ACCESSORIES (Field installed)

ALPIRREMOTE - Remote Control to program the Motion Sensor
(Only one needed per job)

¹ 347/480V is not available on A1 models.

² Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

³ Actual lumen output and input wattage may differ by +/-10%

⁴ Type III Standard. Types IV and V are made to order and require additional lead time. Consult factory for details.

⁵ Shorting Cap provided. Can be used with a standard 3-pin or 7-pin photocontrol or a wireless control node.

For the most up-to-date specs and warranty information, please visit www.tcp.com

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
25,000 HOUR HIGH OUTPUT DIMMABLE ELITE PARS											
18.5W DIMMABLE HIGH OUTPUT ELITE PAR38 (REPLACES 150W)											
LED17HOP38D27KFL	18.5W DIM High Output P38 - 2700K 40°	120	18.5	150W	1800	97.3	4346	40	2700K	80	12
LED17HOP38D27KNFL	18.5W DIM High Output P38 - 2700K 25°	120	18.5	150W	1800	97.3	9299	25	2700K	80	12
LED17HOP38D27KSP	18.5W DIM High Output P38 - 2700K 15°	120	18.5	150W	1800	97.3	21535	15	2700K	80	12
LED17HOP38D27KSPB	18.5W DIM High Output P38 - 2700K 15° - Black	120	18.5	150W	1800	97.3	21535	15	2700K	80	12
LED17HOP38D30KFL	18.5W DIM High Output P38 - 3000K 40°	120	18.5	150W	1825	98.6	4365	40	3000K	80	12
LED17HOP38D30KFLB	18.5W DIM High Output P38 - 3000K 25° - Black	120	18.5	150W	1825	98.6	4365	40	3000K	80	12
LED17HOP38D30KNFL	18.5W DIM High Output P38 - 3000K 15°	120	18.5	150W	1825	98.6	12782	25	3000K	80	12
LED17HOP38D30KNFLB	18.5W DIM High Output P38 - 3000K 40° - Black	120	18.5	150W	1825	98.6	12782	25	3000K	80	12
LED17HOP38D30KSP	18.5W DIM High Output P38 - 3000K 25°	120	18.5	150W	1825	98.6	23699	15	3000K	80	12
LED17HOP38D30KSPB	18.5W DIM High Output P38 - 3000K 15° - Black	120	18.5	150W	1825	98.6	23699	15	3000K	80	12
LED17HOP38D35KFL	18.5W DIM High Output P38 - 3500K 25°	120	18.5	150W	1850	100.0	4365	40	3500K	80	12
LED17HOP38D35KFLB	18.5W DIM High Output P38 - 3500K 15° - Black	120	18.5	150W	1850	100.0	4365	40	3500K	80	12
LED17HOP38D35KWFL	18.5W DIM High Output P38 - 3500K 60°	120	18.5	150W	1850	100.0	-	60	3500K	80	12
LED17HOP38D35KSP	18.5W DIM High Output P38 - 3500K 25°	120	18.5	150W	1850	100.0	23685	25	3500K	80	12
LED17HOP38D35KNFL	18.5W DIM High Output P38 - 3500K 15°	120	18.5	150W	1850	100.0	12782	15	3500K	80	12
LED17HOP38D41KFL	18.5W DIM High Output P38 - 4100K 40°	120	18.5	150W	1900	102.7	4604	40	4100K	80	12
LED17HOP38D41KNFL	18.5W DIM High Output P38 - 4100K 25°	120	18.5	150W	1900	102.7	11614	25	4100K	80	12
LED17HOP38D41KSP	18.5W DIM High Output P38 - 4100K 15°	120	18.5	150W	1900	102.7	22458	15	4100K	80	12
LED17HOP38D50KFL	18.5W DIM High Output P38 - 5000K 40°	120	18.5	150W	2000	108.1	4446	40	5000K	80	12
LED17HOP38D50KNFL	18.5W DIM High Output P38 - 5000K 25°	120	18.5	150W	2000	108.1	12467	25	3000K	80	12
LED17HOP38D50KSP	18.5W DIM High Output P38 - 5000K 15°	120	18.5	150W	2000	108.1	21535	15	3000K	80	12



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



Consult www.tcp.com for warranty information. Black Housing option available. Add "B" to the end of item #.



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

25,000 HOUR DIMMABLE ELITE PARS

15W DIMMABLE ELITE PAR38 (REPLACES 120W)



LED17P38D24KFL	15W PAR38 - 2400K 40°	120	15	120W	1050	70	2132	40	2400K	80	12
LED17P38D24KNFL	15W PAR38 - 2400K 25°	120	15	120W	1050	70	4750	25	2400K	80	12
LED17P38D24KSP	15W PAR38 - 2400K 15°	120	15	120W	1050	70	6937	15	2400K	80	12
LED17P38D27KFL	15W PAR38 - 2700K 40°	120	15	120W	1200	80	2563	40	2700K	80	12
LED17P38D27KFLB	15W PAR38 - 2700K 40° - Black	120	15	120W	1200	80	2563	40	2700K	80	12
LED17P38D27KNFL	15W PAR38 - 2700K 25°	120	15	120W	1200	80	5710	25	2700K	80	12
LED17P38D27KSP	15W PAR38 - 2700K 15°	120	15	120W	1200	80	8338	15	2700K	80	12
LED17P38D30KFL	15W PAR38 - 3000K 40°	120	15	120W	1200	80	3107	40	3000K	80	12
LED17P38D30KFLB	15W PAR38 - 3000K 40° - Black	120	15	120W	1200	80	3107	40	3000K	80	12
LED17P38D30KNFL	15W PAR38 - 3000K 25°	120	15	120W	1200	80	6130	25	3000K	80	12
LED17P38D30KNFLB	15W PAR38 - 3000K 25° - Black	120	15	120W	1200	80	6130	25	3000K	80	12
LED17P38D30KSP	15W PAR38 - 3000K 15°	120	15	120W	1200	80	8658	15	3000K	80	12
LED17P38D30KSPB	15W PAR38 - 3000K 15° - Black	120	15	120W	1200	80	8658	15	3000K	80	12
LED17P38D30KWFLB	15W PAR38 - 3000K 60° - Black	120	15	120W	1200	80	-	60	3000K	80	12
LED17P38D35KFL	15W PAR38 - 3500K 40°	120	15	120W	1200	80	3607	40	3500K	80	12
LED17P38D35KFLB	15W PAR38 - 3500K 40° - Black	120	15	120W	1200	80	3607	40	3500K	80	12
LED17P38D35KNFL	15W PAR38 - 3500K 25°	120	15	120W	1200	80	6130	25	3500K	80	12
LED17P38D35KNFLB	15W PAR38 - 3500K 25° - Black	120	15	120W	1200	80	6130	25	3500K	80	12
LED17P38D35KSP	15W PAR38 - 3500K 15°	120	15	120W	1200	80	8658	15	3500K	80	12
LED17P38D41KFL	15W PAR38 - 4100K 40°	120	15	120W	1200	80	2870	40	4100K	80	12
LED17P38D41KFLB	15W PAR38 - 4100K 40° - Black	120	15	120W	1200	80	2870	40	4100K	80	12
LED17P38D41KNFL	15W PAR38 - 4100K 25°	120	15	120W	1200	80	9288	25	4100K	80	12
LED17P38D41KNFLB	15W PAR38 - 4100K 25° - Black	120	15	120W	1200	80	9288	25	4100K	80	12
LED17P38D41KSP	15W PAR38 - 4100K 15°	120	15	120W	1200	80	18408	15	4100K	80	12
LED17P38D41KSPB	15W PAR38 - 4100K 15° - Black	120	15	120W	1200	80	18408	15	4100K	80	12
LED17P38D50KFL	15W PAR38 - 5000K 40°	120	15	120W	1200	80	2713	40	5000K	80	12
LED17P38D50KFLB	15W PAR38 - 5000K 40° - Black	120	15	120W	1200	80	2713	40	5000K	80	12
LED17P38D50KNFL	15W PAR38 - 5000K 25°	120	15	120W	1200	80	9387	25	5000K	80	12
LED17P38D50KSP	15W PAR38 - 5000K 15°	120	15	120W	1200	80	19721	15	5000K	80	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
13.5W DIMMABLE ELITE PAR38 (REPLACES 90W)											
LED14P38D24KFL	13.5W PAR38 - 2400K 40°	120	13.5	90W	1000	75.0	-	40	2400K	80	12
LED14P38D24KNFL	13.5W PAR38 - 2400K 25°	120	13.5	90W	1000	75.0	-	25	2400K	80	12
LED14P38D24KSP	13.5W PAR38 - 2400K 15°	120	13.5	90W	1000	75.0	-	15	2400K	80	12
LED14P38D27KFL	13.5W PAR38 - 2700K 40°	120	13.5	90W	1050	77.8	2858	40	2700K	80	12
LED14P38D27KNFL	13.5W PAR38 - 2700K 25°	120	13.5	90W	1050	77.8	5583	25	2700K	80	12
LED14P38D27KNFLB	13.5W PAR38 - 2700K 25° - Black	120	13.5	90W	1050	77.8	5583	25	2700K	80	12
LED14P38D27KSP	13.5W PAR38 - 2700K 15°	120	13.5	90W	1050	77.8	10949	15	2700K	80	12
LED14P38D27KSPB	13.5W PAR38 - 2700K 15° - Black	120	13.5	90W	1050	77.8	10949	15	2700K	80	12
LED14P38D30KFL	13.5W PAR38 - 3000K 40°	120	13.5	90W	1050	77.8	2846	40	3000K	80	12
LED14P38D30KNFL	13.5W PAR38 - 3000K 25°	120	13.5	90W	1050	77.8	6721	25	3000K	80	12
LED14P38D30KSP	13.5W PAR38 - 3000K 15°	120	13.5	90W	1050	77.8	11845	15	3000K	80	12
LED14P38D30KWFL	13.5W PAR38 - 3000K 60°	120	13.5	90W	1050	77.8	-	60	3000K	80	12
LED14P38D35KFL	13.5W PAR38 - 3500K 40°	120	13.5	90W	1050	77.8	2846	40	3500K	80	12
LED14P38D35KFLB	13.5W PAR38 - 3500K 40° - Black	120	13.5	90W	1050	77.8	2846	40	3500K	80	12
LED14P38D35KNFL	13.5W PAR38 - 3500K 25°	120	13.5	90W	1050	77.8	6271	25	3500K	80	12
LED14P38D35KSP	13.5W PAR38 - 3500K 15°	120	13.5	90W	1050	77.8	10949	15	3500K	80	12
LED14P38D41KFL	13.5W PAR38 - 4100K 40°	120	13.5	90W	1050	77.8	2678	40	4100K	80	12
LED14P38D41KFLB	13.5W PAR38 - 4100K 40° - Black	120	13.5	90W	1050	77.8	2678	40	4100K	80	12
LED14P38D41KNFL	13.5W PAR38 - 4100K 25°	120	13.5	90W	1050	77.8	8310	25	4100K	80	12
LED14P38D41KSP	13.5W PAR38 - 4100K 15°	120	13.5	90W	1050	77.8	13535	15	4100K	80	12
LED14P38D41KSPB	13.5W PAR38 - 4100K 15° - Black	120	13.5	90W	1050	77.8	13535	15	4100K	80	12
LED14P38D50KFL	13.5W PAR38 - 5000K 40°	120	13.5	90W	1050	77.8	2647	40	5000K	80	12
LED14P38D50KFLB	13.5W PAR38 - 5000K 40° - Black	120	13.5	90W	1050	77.8	2647	40	5000K	80	12
LED14P38D50KNFL	13.5W PAR38 - 5000K 25°	120	13.5	90W	1150	82.1	7611	25	5000K	80	12
LED14P38D50KSP	13.5W PAR38 - 5000K 15°	120	13.5	90W	1150	82.1	12147	15	5000K	80	12



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



5 YEAR WARRANTY

Consult www.tcp.com for warranty information.

Black Housing option available. Add "B" to the end of item #.



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

13.5W DIMMABLE ELITE PAR30 (REPLACES 75W)



LED14P30D24KFL	13.5W PAR30 - 2400K 40°	120	13.5	75W	1000	74.1	-	40	2400K	80	12
LED14P30D24KNFL	13.5W PAR30 - 2400K 25°	120	13.5	75W	1000	74.1	-	25	2400K	80	12
LED14P30D24KNFLB	13.5W PAR30 - 2400K 25° - Black	120	13.5	75W	1000	74.1	-	25	2400K	80	12
LED14P30D24KSP	13.5W PAR30 - 2400K 15°	120	13.5	75W	1000	74.1	-	15	2400K	80	12
LED14P30D27KFL	13.5W PAR30 - 2700K 40°	120	13.5	75W	1050	77.8	2693	40	2700K	80	12
LED14P30D27KFLB	13.5W PAR30 - 2700K 40° - Black	120	13.5	75W	1050	77.8	2693	40	2700K	80	12
LED14P30D27KNFL	13.5W PAR30 - 2700K 25°	120	13.5	75W	1050	77.8	5808	25	2700K	80	12
LED14P30D27KNFLB	13.5W PAR30 - 2700K 25° - Black	120	13.5	75W	1050	77.8	5808	25	2700K	80	12
LED14P30D27KSP	13.5W PAR30 - 2700K 15°	120	13.5	75W	1050	77.8	10563	15	2700K	80	12
LED14P30D27KSPB	13.5W PAR30 - 2700K 15° - Black	120	13.5	75W	1050	77.8	10563	15	2700K	80	12
LED14P30D30KFL	13.5W PAR30 - 3000K 40°	120	13.5	75W	1050	77.8	2849	40	3000K	80	12
LED14P30D30KFLB	13.5W PAR30 - 3000K 40° - Black	120	13.5	75W	1050	77.8	2849	40	3000K	80	12
LED14P30D30KNFL	13.5W PAR30 - 3000K 25°	120	13.5	75W	1050	77.8	6392	25	3000K	80	12
LED14P30D30KNFLB	13.5W PAR30 - 3000K 25° - Black	120	13.5	75W	1050	77.8	6392	25	3000K	80	12
LED14P30D30KSP	13.5W PAR30 - 3000K 15°	120	13.5	75W	1050	77.8	11181	15	3000K	80	12
LED14P30D30KSPB	13.5W PAR30 - 3000K 15° - Black	120	13.5	75W	1050	77.8	11181	15	3000K	80	12
LED14P30D35KFL	13.5W PAR30 - 3500K 40°	120	13.5	75W	1050	77.8	2849	40	3500K	80	12
LED14P30D35KFLB	13.5W PAR30 - 3500K 40° - Black	120	13.5	75W	1050	77.8	2849	40	3500K	80	12
LED14P30D35KNFL	13.5W PAR30 - 3500K 25°	120	13.5	75W	1050	77.8	6392	25	3500K	80	12
LED14P30D35KSP	13.5W PAR30 - 3500K 15°	120	13.5	75W	1050	77.8	11181	15	3500K	80	12
LED14P30D41KFL	13.5W PAR30 - 4100K 40°	120	13.5	75W	1050	77.8	2661	40	4100K	80	12
LED14P30D41KFLB	13.5W PAR30 - 4100K 40° - Black	120	13.5	75W	1050	77.8	2661	40	4100K	80	12
LED14P30D41KNFL	13.5W PAR30 - 4100K 25°	120	13.5	75W	1050	77.8	5781	25	4100K	80	12
LED14P30D41KNFLB	13.5W PAR30 - 4100K 25° - Black	120	13.5	75W	1050	77.8	5781	25	4100K	80	12
LED14P30D41KSP	13.5W PAR30 - 4100K 15°	120	13.5	75W	1050	77.8	12465	15	4100K	80	12
LED14P30D41KSPB	13.5W PAR30 - 4100K 15° - Black	120	13.5	75W	1050	77.8	12465	15	4100K	80	12
LED14P30D50KFL	13.5W PAR30 - 5000K 40°	120	13.5	75W	1050	77.8	2837	40	5000K	80	12
LED14P30D50KFLB	13.5W PAR30 - 5000K 40° - Black	120	13.5	75W	1050	77.8	2837	40	5000K	80	12
LED14P30D50KNFL	13.5W PAR30 - 5000K 25°	120	13.5	75W	1050	77.8	5875	25	5000K	80	12
LED14P30D50KSP	13.5W PAR30 - 5000K 15°	120	13.5	75W	1050	77.8	10043	15	5000K	80	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

10.5W DIMMABLE ELITE PAR30 (REPLACES 75W)

LED12P30D24KFL	10.5W PAR30 - 2400K 40°	120	10.5	75W	800	76.2	-	40	2400K	80	12
LED12P30D24KNFL	10.5W PAR30 - 2400K 25°	120	10.5	75W	800	76.2	-	25	2400K	80	12
LED12P30D24KSP	10.5W PAR30 - 2400K 15°	120	10.5	75W	800	76.2	-	15	2400K	80	12
LED12P30D27KFL	10.5W PAR30 - 2700K 40°	120	10.5	75W	850	81	2202	40	2700K	80	12
LED12P30D27KFLB	10.5W PAR30 - 2700K 40° - Black	120	10.5	75W	850	81	2202	40	2700K	80	12
LED12P30D27KNFL	10.5W PAR30 - 2700K 25°	120	10.5	75W	850	81	5031	25	2700K	80	12
LED12P30D27KNFLB	10.5W PAR30 - 2700K 25° - Black	120	10.5	75W	850	81	5031	25	2700K	80	12
LED12P30D27KSP	10.5W PAR30 - 2700K 15°	120	10.5	75W	850	81	9193	15	2700K	80	12
LED12P30D27KSPB	10.5W PAR30 - 2700K 15° - Black	120	10.5	75W	850	81	9193	15	2700K	80	12
LED12P30D30KFL	12W PAR30 - 3000K 40°	120	10.5	75W	850	81	2389	40	3000K	80	12
LED12P30D30KFLB	12W PAR30 - 3000K 40° - Black	120	10.5	75W	850	81	2389	40	3000K	80	12
LED12P30D30KNFL	12W PAR30 - 3000K 25°	120	10.5	75W	850	81	5528	25	3000K	80	12
LED12P30D30KNFLB	12W PAR30 - 3000K 25° - Black	120	10.5	75W	850	81	5528	25	3000K	80	12
LED12P30D30KSP	12W PAR30 - 3000K 15°	120	10.5	75W	850	81	9006	15	3000K	80	12
LED12P30D30KSPB	12W PAR30 - 3000K 15° - Black	120	10.5	75W	850	81	9006	15	3000K	80	12
LED12P30D35KFL	12W PAR30 - 3500K 40°	120	10.5	75W	850	81	2389	40	3500K	80	12
LED12P30D35KNFL	12W PAR30 - 3500K 25°	120	10.5	75W	850	81	5528	25	3500K	80	12
LED12P30D35KSP	12W PAR30 - 3500K 15°	120	10.5	75W	850	81	9006	15	3500K	80	12
LED12P30D41KFL	12W PAR30 - 4100K 40°	120	10.5	75W	850	81	2561	40	4100K	80	12
LED12P30D41KFLB	12W PAR30 - 4100K 40° - Black	120	10.5	75W	850	81	2561	40	4100K	80	12
LED12P30D41KNFL	12W PAR30 - 4100K 25°	120	10.5	75W	850	81	5781	25	4100K	80	12
LED12P30D41KNFLB	12W PAR30 - 4100K 25° - Black	120	10.5	75W	850	81	5781	25	4100K	80	12
LED12P30D41KSP	12W PAR30 - 4100K 15°	120	10.5	75W	850	81	9491	15	4100K	80	12
LED12P30D41KSPB	12W PAR30 - 4100K 15° - Black	120	10.5	75W	850	81	9491	15	4100K	80	12
LED12P30D50KFL	12W PAR30 - 5000K 40°	120	10.5	75W	850	81	2437	40	5000K	80	12
LED12P30D50KFLB	12W PAR30 - 5000K 40° - Black	120	10.5	75W	850	81	2437	40	5000K	80	12
LED12P30D50KNFL	12W PAR30 - 5000K 25°	120	10.5	75W	850	81	5575	25	5000K	80	12
LED12P30D50KSP	12W PAR30 - 5000K 15°	120	10.5	75W	850	81	9647	15	5000K	80	12



10W DIMMABLE ELITE PAR30 SHORT NECK (REPLACES 75W)

LED12P30SD24KFL	10W PAR30 Short Neck - 2400K 40°	120	10	75W	800	80	1619	40	2400K	80	12
LED12P30SD24KNFL	10W PAR30 Short Neck - 2400K 25°	120	10	75W	800	80	-	25	2400K	80	12
LED12P30SD24KSP	10W PAR30 Short Neck - 2400K 15°	120	10	75W	800	80	-	15	2400K	80	12
LED12P30SD27KFL	10W PAR30 Short Neck - 2700K 40°	120	10	75W	850	85	1817	40	2700K	80	12
LED12P30SD27KFLB	10W PAR30 Short Neck - 2700K 40° - Black	120	10	75W	850	85	1817	40	2700K	80	12
LED12P30SD27KNFL	10W PAR30 Short Neck - 2700K 40°	120	10	75W	850	85	4025	25	2700K	80	12
LED12P30SD27KNFLB	10W PAR30 Short Neck - 2700K 40° - Black	120	10	75W	850	85	4025	25	2700K	80	12
LED12P30SD27KSP	10W PAR30 Short Neck - 2700K 15°	120	10	75W	850	85	8042	15	2700K	80	12



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing

5 YEAR WARRANTY

Black Housing option available. Add "B" to the end of item #.

Consult www.tpci.com for warranty information.



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

10W DIMMABLE ELITE PAR30 SHORT NECK (REPLACES 75W) CONTINUED



LED12P30SD30KFL	10W PAR30 Short Neck - 3000K 40°	120	10	75W	850	85	1858	40	3000K	80	12
LED12P30SD30KFLB	10W PAR30 Short Neck - 3000K 40° - Black	120	10	75W	850	85	1858	40	3000K	80	12
LED12P30SD30KNFL	10W PAR30 Short Neck - 3000K 25°	120	10	75W	850	85	4968	25	3000K	80	12
LED12P30SD30KNFLB	10W PAR30 Short Neck - 3000K 25° - Black	120	10	75W	850	85	4968	25	3000K	80	12
LED12P30SD30KSP	10W PAR30 Short Neck - 3000K 15°	120	10	75W	850	85	8380	15	3000K	80	12
LED12P30SD30KSPB	10W PAR30 Short Neck - 3000K 15° - Black	120	10	75W	850	85	8380	15	3000K	80	12
LED12P30SD35KFL	10W PAR30 Short Neck - 3500K 40°	120	10	75W	850	85	2232	40	3500K	80	12
LED12P30SD35KFLB	10W PAR30 Short Neck - 3500K 40° - Black	120	10	75W	850	85	2232	40	3500K	80	12
LED12P30SD35KNFL	10W PAR30 Short Neck - 3500K 25°	120	10	75W	850	85	4402	25	3500K	80	12
LED12P30SD35KNFLB	10W PAR30 Short Neck - 3500K 25° - Black	120	10	75W	850	85	4402	25	3500K	80	12
LED12P30SD35KSP	10W PAR30 Short Neck - 3500K 15°	120	10	75W	850	85	8380	15	3500K	80	12
LED12P30SD41KFL	10W PAR30 Short Neck - 4100K 40°	120	10	75W	850	85	2247	40	4100K	80	12
LED12P30SD41KFLB	10W PAR30 Short Neck - 4100K 40° - Black	120	10	75W	850	85	2247	40	4100K	80	12
LED12P30SD41KNFL	10W PAR30 Short Neck - 4100K 25°	120	10	75W	850	85	4895	25	4100K	80	12
LED12P30SD41KSP	10W PAR30 Short Neck - 4100K 15°	120	10	75W	850	85	8710	15	4100K	80	12
LED12P30SD50KFL	10W PAR30 Short Neck - 5000K 40°	120	10	75W	850	85	2454	40	5000K	80	12
LED12P30SD50KNFL	10W PAR30 Short Neck - 5000K 25°	120	10	75W	850	85	5260	25	5000K	80	12
LED12P30SD50KSP	10W PAR30 Short Neck - 5000K 15°	120	10	75W	850	85	9292	15	5000K	80	12

7W DIMMABLE ELITE PAR20 (REPLACES 50W)



LED8P20D24KFL	7W PAR20 - 2400K 40°	120	7	50W	550	78.6	1058	40	2400K	80	12
LED8P20D24KNFL	7W PAR20 - 2400K 25°	120	7	50W	550	78.6	1894	25	2400K	80	12
LED8P20D27KFL	7W PAR20 - 2700K 40°	120	7	50W	600	85.7	1208	40	2700K	80	12
LED8P20D27KFLB	7W PAR20 - 2700K 40° - Black	120	7	50W	600	85.7	1208	40	2700K	80	12
LED8P20D27KNFL	7W PAR20 - 2700K 25°	120	7	50W	600	85.7	2030	25	2700K	80	12
LED8P20D27KSP	7W PAR20 - 2700K 15°	120	7	50W	600	85.7	4898	15	2700K	80	12
LED8P20D30KFL	7W PAR20 - 3000K 40°	120	7	50W	625	89.3	1187	40	3000K	80	12
LED8P20D30KFLB	7W PAR20 - 3000K 40° - Black	120	7	50W	625	89.3	1187	40	3000K	80	12
LED8P20D30KNFL	7W PAR20 - 3000K 25°	120	7	50W	625	89.3	2050	25	3000K	80	12
LED8P20D30KNFLB	7W PAR20 - 3000K 25° - Black	120	7	50W	625	89.3	2050	25	3000K	80	12
LED8P20D30KSP	7W PAR20 - 3000K 15°	120	7	50W	625	89.3	5391	15	3000K	80	12
LED8P20D35KFL	7W PAR20 - 3500K 40°	120	7	50W	675	96.4	1187	25	3500K	80	12
LED8P20D35KNFL	7W PAR20 - 3500K 25°	120	7	50W	675	96.4	2050	25	3500K	80	12
LED8P20D41KFL	7W PAR20 - 4100K 40°	120	7	50W	675	96.4	1383	40	4100K	80	12
LED8P20D41KFLB	7W PAR20 - 4100K 40° - Black	120	7	50W	675	96.4	1383	40	4100K	80	12
LED8P20D41KNFL	7W PAR20 - 4100K 25°	120	7	50W	675	96.4	2174	25	4100K	80	12
LED8P20D41KNFLB	7W PAR20 - 4100K 25° - Black	120	7	50W	675	96.4	2174	25	4100K	80	12
LED8P20D41KSP	7W PAR20 - 4100K 15°	120	7	50W	675	96.4	5411	15	4100K	80	12
LED8P20D50KFL	7W PAR20 - 5000K 40°	120	7	50W	700	100	1330	40	5000K	80	12
LED8P20D50KFLB	7W PAR20 - 5000K 40° - Black	120	7	50W	700	100	1330	40	5000K	80	12
LED8P20D50KNFL	7W PAR20 - 5000K 25°	120	7	50W	700	100	2172	25	5000K	80	12
LED8P20D50KSP	7W PAR20 - 5000K 15°	120	7	50W	700	100	5599	15	5000K	80	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

25,000 HOUR DIMMABLE SMD PARS

15W DIMMABLE SMD PAR38 (REPLACES 150W)

L150P38D2527KFL	15W PAR38 - 2700K 40°	120	15	150W	1450	96.7	3403	40	2700K	80	12
L150P38D2527KNFL	15W PAR38 - 2700K 25°	120	15	150W	1450	96.7	7563	25	2700K	80	12
L150P38D2530KFL	15W PAR38 - 3000K 40°	120	15	150W	1500	100	3470	40	3000K	80	12
L150P38D2530KNFL	15W PAR38 - 3000K 25°	120	15	150W	1500	100	7624	25	3000K	80	12
L150P38D2541KFL	15W PAR38 - 4100K 40°	120	15	150W	1550	103.3	3554	40	4100K	80	12
L150P38D2541KNFL	15W PAR38 - 4100K 25°	120	15	150W	1550	103.3	7800	25	4100K	80	12
L150P38D2550KFL	15W PAR38 - 5000K 40°	120	15	150W	1600	106.7	3880	40	5000K	80	12
L150P38D2550KNFL	15W PAR38 - 5000K 25°	120	15	150W	1600	106.7	8028	25	5000K	80	12



13W DIMMABLE SMD PAR38 (REPLACES 120W)

L120P38D2527KFL	13W PAR38 - 2700K 40°	120	13	120W	1100	84.6	2584	40	2700K	80	12
L120P38D2527KNFL	13W PAR38 - 2700K 25°	120	13	120W	1100	84.6	6235	25	2700K	80	12
L120P38D2530KFL	13W PAR38 - 3000K 40°	120	13	120W	1200	92.3	2508	40	3000K	80	12
L120P38D2530KNFL	13W PAR38 - 3000K 25°	120	13	120W	1200	92.3	6661	25	3000K	80	12
L120P38D2540KFL	13W PAR38 - 4000K 40°	120	13	120W	1250	96.2	2348	40	4000K	80	12
L120P38D2540KNFL	13W PAR38 - 4000K 25°	120	13	120W	1250	96.2	6482	25	4000K	80	12
L120P38D2550KFL	13W PAR38 - 5000K 40°	120	13	120W	1250	96.2	2562	40	5000K	80	12
L120P38D2550KNFL	13W PAR38 - 5000K 25°	120	13	120W	1250	96.2	6513	25	5000K	80	12

10W DIMMABLE SMD PAR38 (REPLACES 90W)

L90P38D2527KFL	10W PAR38 - 2700K 40°	120	10	90W	900	90	1872	40	2700K	80	12
L90P38D2527KNFL	10W PAR38 - 2700K 25°	120	10	90W	900	90	4199	25	2700K	80	12
L90P38D2530KFL	10W PAR38 - 3000K 40°	120	10	90W	900	90	1964	40	3000K	80	12
L90P38D2530KNFL	10W PAR38 - 3000K 25°	120	10	90W	900	90	4384	25	3000K	80	12
L90P38D2540KFL	10W PAR38 - 4000K 40°	120	10	90W	950	95	2017	40	4000K	80	12
L90P38D2540KNFL	10W PAR38 - 4000K 25°	120	10	90W	950	95	4413	25	4000K	80	12
L90P38D2550KFL	10W PAR38 - 5000K 40°	120	10	90W	950	95	2222	40	5000K	80	12
L90P38D2550KNFL	10W PAR38 - 5000K 25°	120	10	90W	950	95	4383	25	5000K	80	12

9W DIMMABLE SMD PAR30 (REPLACES 75W)

L75P30D2527KFL	9W PAR30 - 2700K 40°	120	9	75W	700	77.8	1640	40	2700K	80	12
L75P30D2527KNFL	9W PAR30 - 2700K 25°	120	9	75W	700	77.8	3419	25	2700K	80	12
L75P30D2530KFL	9W PAR30 - 3000K 40°	120	9	75W	720	80	1658	40	3000K	80	12
L75P30D2530KNFL	9W PAR30 - 3000K 25°	120	9	75W	720	80	3392	25	3000K	80	12
L75P30D2540KFL	9W PAR30 - 4000K 40°	120	9	75W	770	85.6	1759	40	4000K	80	12
L75P30D2540KNFL	9W PAR30 - 4000K 25°	120	9	75W	770	85.6	3701	25	4000K	80	12
L75P30D2550KFL	9W PAR30 - 5000K 40°	120	9	75W	770	85.6	1790	40	5000K	80	12
L75P30D2550KNFL	9W PAR30 - 5000K 25°	120	9	75W	770	85.6	3874	25	5000K	80	12



9.5W DIMMABLE SMD PAR30 SHORT NECK (REPLACES 75W)

L75P30SD2527KFL	9.5W PAR30 Short Neck - 2700K 40°	120	9.5	75W	720	75.8	1714	40	2700K	80	12
L75P30SD2527KNFL	9.5W PAR30 Short Neck - 2700K 25°	120	9.5	75W	720	75.8	3051	25	2700K	80	12
L75P30SD2530KFL	9.5W PAR30 Short Neck - 3000K 40°	120	9.5	75W	720	75.8	1621	40	3000K	80	12
L75P30SD2530KNFL	9.5W PAR30 Short Neck - 3000K 25°	120	9.5	75W	720	75.8	3064	25	3000K	80	12
L75P30SD2540KFL	9.5W PAR30 Short Neck - 4000K 40°	120	9.5	75W	770	81.1	1714	40	4000K	80	12
L75P30SD2540KNFL	9.5W PAR30 Short Neck - 4000K 25°	120	9.5	75W	770	81.1	2930	25	4000K	80	12
L75P30SD2550KFL	9.5W PAR30 Short Neck - 5000K 40°	120	9.5	75W	770	81.1	1847	40	5000K	80	12
L75P30SD2550KNFL	9.5W PAR30 Short Neck - 5000K 25°	120	9.5	75W	770	81.1	3274	25	5000K	80	12



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



Consult www.tpci.com for warranty information.

Black Housing option available. Add "B" to the end of item #.



Item Number Item Description Voltage Lamp Watts Wattage Equivalent Lumens Lumens Per Watt CBCP Beam Angle CCT CRI Case Quantity

7W DIMMABLE SMD PAR20 (REPLACES 50W)



L50P20D2527KFL	7W PAR20 - 2700K 40°	120	7	50W	525	75	1208	40	2700K	80	12
L50P20D2527KNFL	7W PAR20 - 2700K 25°	120	7	50W	525	75	2030	25	2700K	80	12
L50P20D2530KFL	7W PAR20 - 3000K 40°	120	7	50W	525	75	1187	40	3000K	80	12
L50P20D2530KNFL	7W PAR20 - 3000K 25°	120	7	50W	525	75	2050	25	3000K	80	12
L50P20D2540KFL	7W PAR20 - 4000K 40°	120	7	50W	575	82.1	1383	40	4000K	80	12
L50P20D2540KNFL	7W PAR20 - 4000K 25°	120	7	50W	575	82.1	2174	25	4000K	80	12
L50P20D2550KFL	7W PAR20 - 5000K 40°	120	7	50W	575	82.1	1330	40	5000K	80	12
L50P20D2550KNFL	7W PAR20 - 5000K 25°	120	7	50W	575	82.1	2172	25	5000K	80	12

25,000 HOUR DIMMABLE HIGH OUTPUT, HIGH CRI PARS

18.5W DIMMABLE DESIGNER ELITE HIGH OUTPUT HIGH CRI PAR38 (REPLACES 120W) CRI>90 R9>50



LED17HOP38D27KFL95	18.5W DIM High Output, High CRI P38 - 2700K 40°	120	18.5	150W	1300	70.3	2231	40	2700K	90	12
LED17HOP38D27KNFL95	18.5W DIM High Output, High CRI P38 - 2700K 25°	120	18.5	150W	1300	70.3	5382	25	2700K	90	12
LED17HOP38D27KSP95	18.5W DIM High Output, High CRI P38 - 2700K 15°	120	18.5	150W	1300	70.3	12059	15	2700K	90	12
LED17HOP38D30KFL95	18.5W DIM High Output, High CRI P38 - 3000K 40°	120	18.5	150W	1300	70.3	2231	40	3000K	90	12
LED17HOP38D30KNFL95	18.5W DIM High Output, High CRI P38 - 3000K 25°	120	18.5	150W	1300	70.3	5382	25	3000K	90	12
LED17HOP38D30KSP95	18.5W DIM High Output, High CRI P38 - 3000K 15°	120	18.5	150W	1300	70.3	12059	15	3000K	90	12

25,000 HOUR DIMMABLE HIGH CRI PARS

15W DIMMABLE DESIGNER ELITE HIGH CRI PAR38 (REPLACES 90W) CRI>90 R9>50

LED17P38D27KFL95	15W DIM High CRI P38 - 2700K 40°	120	15	90W	1050	70	1533	40	2700K	90	12
LED17P38D27KNFL95	15W DIM High CRI P38 - 2700K 25°	120	15	90W	1050	70	3698	25	2700K	90	12
LED17P38D27KSP95	15W DIM High CRI P38 - 2700K 15°	120	15	90W	1050	70	8285	15	2700K	90	12
LED17P38D30KFL95	15W DIM High CRI P38 - 3000K 40°	120	15	90W	1050	70	1533	40	3000K	90	12
LED17P38D30KNFL95	15W DIM High CRI P38 - 3000K 25°	120	15	90W	1050	70	3698	25	3000K	90	12

13.5W DIMMABLE DESIGNER ELITE HIGH CRI PAR38 (REPLACES 75W)

LED14P38D27KNFL95	13.5W DIM High CRI P38 - 2700K 25°	120	13.5	75W	1000	74.1	3698	25	2700K	90	12
-------------------	------------------------------------	-----	------	-----	------	------	------	----	-------	----	----

13.5W DIMMABLE DESIGNER ELITE HIGH CRI PAR30 (REPLACES 75W)



LED14P30D27KNFL95	13.5W DIM High CRI P30 - 2700K 25°	120	13.5	75W	1000	74.1	2910	25	2700K	90	12
LED14P30D30KNFL95	13.5W DIM High CRI P30 - 3000K 25°	120	13.5	75W	1000	74.1	2910	25	3000K	90	12

10.5W DIMMABLE DESIGNER ELITE HIGH CRI PAR30 (REPLACES 65W)

LED12P30D30KNFL95	10.5W DIM High CRI P30 - 3000K 25°	120	10.5	65W	750	71.4	2118	25	3000K	90	12
-------------------	------------------------------------	-----	------	-----	-----	------	------	----	-------	----	----

10W DIMMABLE DESIGNER ELITE HIGH CRI PAR30 SHORT NECK (REPLACES 65W)



LED12P30SD27KFL95	10W DIM High CRI P30 Short Neck - 2700K 40°	120	10	65W	750	75	957	40	2700K	90	12
LED12P30SD27KNFL95	10W DIM High CRI P30 Short Neck - 2700K 25°	120	10	65W	750	75	2118	25	2700K	90	12
LED12P30SD30KFL95	10W DIM High CRI P30 Short Neck - 3000K 40°	120	10	65W	750	75	957	40	3000K	90	12
LED12P30SD30KNFL95	10W DIM High CRI P30 Short Neck - 3000K 25°	120	10	65W	750	75	2118	25	3000K	90	12
LED12P30SD30KSP95	10W DIM High CRI P30 Short Neck - 3000K 15°	120	10	65W	750	75	4481	15	3000K	90	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	Beam Angle	CCT	CRI	Case Quantity
25,000 HOUR DIMMABLE ELITE BR5										
17W DIMMABLE ELITE BR40 (REPLACES 90W)										
LED17BR40D24K	17W Dim BR40 - 2400K	120	17	90W	1250	73.5	110	2400K	80	12
LED17BR40D27K	17W Dim BR40 - 2700K	120	17	90W	1400	82.4	110	2700K	80	12
LED17BR40D30K	17W Dim BR40 - 3000K	120	17	90W	1400	82.4	110	3000K	80	12
LED17BR40D41K	17W Dim BR40 - 4100K	120	17	90W	1400	82.4	110	4100K	80	12
LED17BR40D50K	17W Dim BR40 - 5000K	120	17	90W	1400	82.4	110	5000K	80	12
14W DIMMABLE ELITE BR40 (REPLACES 75W)										
L85BR40D24K	14W Dim BR40 - 2400K	120	14	75W	1050	75	110	2400K	80	12
L85BR40D27K	14W Dim BR40 - 2700K	120	14	75W	1100	78.6	110	2700K	80	12
L85BR40D30K	14W Dim BR40 - 3000K	120	14	75W	1150	82.1	110	3000K	80	12
L85BR40D41K	14W Dim BR40 - 4100K	120	14	75W	1200	85.7	110	4100K	80	12
L85BR40D50K	14W Dim BR40 - 5000K	120	14	75W	1200	85.7	110	5000K	80	12
10.5W DIMMABLE ELITE BR30 (REPLACES 65W)										
LED12BR30D24K	10.5W Dim BR30 - 2400K	120	10.5	65W	680	64.8	110	2400K	80	12
LED12BR30D27K	10.5W Dim BR30 - 2700K	120	10.5	65W	850	81.0	110	2700K	80	12
LED12BR30D30K	10.5W Dim BR30 - 3000K	120	10.5	65W	850	81.0	110	3000K	80	12
LED12BR30D41K	10.5W Dim BR30 - 4100K	120	10.5	65W	850	81.0	110	4100K	80	12
LED12BR30D50K	10.5W Dim BR30 - 5000K	120	10.5	65W	850	81.0	110	5000K	80	12
9.5W DIMMABLE ELITE BR30 (REPLACES 65W)										
LED9BR30D24K	9.5W Dim BR30 - 2400K	120	9.5	65W	600	63.2	110	2400K	80	12
LED9BR30D27K	9.5W Dim BR30 - 2700K	120	9.5	65W	700	73.7	110	2700K	80	12
LED9BR30D30K	9.5W Dim BR30 - 3000K	120	9.5	65W	700	73.7	110	3000K	80	12
LED9BR30D41K	9.5W Dim BR30 - 4100K	120	9.5	65W	750	78.9	110	4100K	80	12
LED9BR30D50K	9.5W Dim BR30 - 5000K	120	9.5	65W	750	78.9	110	5000K	80	12
9W DIMMABLE ELITE R20 (REPLACES 60W)										
LED10R20D24K	9W Dim R20 - 2400K	120	9	60W	520	57.8	110	2400K	80	12
LED10R20D27K	9W Dim R20 - 2700K	120	9	60W	660	73.3	110	2700K	80	12
LED10R20D30K	9W Dim R20 - 3000K	120	9	60W	700	77.8	110	3000K	80	12
LED10R20D41K	9W Dim R20 - 4100K	120	9	60W	725	80.6	110	4100K	80	12
LED10R20D50K	9W Dim R20 - 5000K	120	9	60W	750	83.3	110	5000K	80	12
7.5W DIMMABLE ELITE R20 (REPLACES 50W)										
LED7R20D2524K	7.5W Dim R20 - 2400K	120	7.5	50W	400	53.3	110	2400K	80	12
LED7R20D2527K	7.5W Dim R20 - 2700K	120	7.5	50W	525	70	110	2700K	80	12
LED7R20D2530K	7.5W Dim R20 - 3000K	120	7.5	50W	525	70	110	3000K	80	12
LED7R20D2541K	7.5W Dim R20 - 4100K	120	7.5	50W	525	70	110	4100K	80	12
LED7R20D2550K	7.5W Dim R20 - 5000K	120	7.5	50W	525	70	110	5000K	80	12





Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------------	-----	-----	---------------

15,000 HOUR DIMMABLE ELITE BRS 2 Pack

9W DIMMABLE ELITE BR30 (REPLACES 65W)



L8BR30D1527K2	9W Dim BR30 - 2700K 2 Pack	120	9	65W	650	72.2	110	2700K	80	12
---------------	----------------------------	-----	---	-----	-----	------	-----	-------	----	----

25,000 HOUR NON DIMMABLE ELITE BRS

17W NON DIMMABLE ELITE BR40 (REPLACES 90W)



LED17BR4027K	14W Non Dim BR40 - 2700K	120	17	90W	1400	82.4	110	2700K	80	12
LED17BR4030K	14W Non Dim BR40 - 3000K	120	17	90W	1400	82.4	110	3000K	80	12
LED17BR4041K	14W Non Dim BR40 - 4100K	120	17	90W	1400	82.4	110	4100K	80	12

10.5W NON DIMMABLE ELITE BR30 (REPLACES 65W)



LED12BR3027K	10.5W Non Dim BR30 - 2700K	120	10.5	65W	850	81.0	110	2700K	80	12
LED12BR3030K	10.5W Non Dim BR30 - 3000K	120	10.5	65W	850	81.0	110	3000K	80	12
LED12BR3041K	10.5W Non Dim BR30 - 4100K	120	10.5	65W	850	81.0	110	4100K	80	12

8.5W NON DIMMABLE ELITE BR30 (REPLACES 65W)



LED10BR3027K	8.5W Non Dim BR30 - 2700K	120	8.5	65W	650	76.5	110	2700K	80	12
LED10BR3030K	8.5W Non Dim BR30 - 3000K	120	8.5	65W	650	76.5	110	3000K	80	12
LED10BR3041K	8.5W Non Dim BR30 - 4100K	120	8.5	65W	650	76.5	110	4100K	80	12
LED10BR3050K	8.5W Non Dim BR30 - 5000K	120	8.5	65W	650	76.5	110	5000K	80	12

25,000 HOUR DIMMABLE ELITE COLORED BRS

12W DIMMABLE ELITE BR30 - COLORED LENS



LED12BR30DAMB	12W Elite BR30 Amber Lens	120	9.5	65W	NA	-	110	Amber	-	12
---------------	---------------------------	-----	-----	-----	----	---	-----	-------	---	----

Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



Consult www.tpci.com for warranty information.

Other housing colors are available by special request.

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	-----	-----	---------------

25,000 HOUR ELITE OMNIDIRECTIONAL A-LAMPS (REPLACES 100W)

15W DIMMABLE A19 - ELITE OMNIDIRECTIONAL A-LAMP (REPLACES 100W)

L15A19D2527K	Dimmable 15W Omnidirectional A19 - 2700K	120	15	100W	1600	106.7	2700K	80	12
L15A19D2530K	Dimmable 15W Omnidirectional A19 - 3000K	120	15	100W	1600	106.7	3000K	80	12
L15A19D2541K	Dimmable 15W Omnidirectional A19 - 4100K	120	15	100W	1600	106.7	4100K	80	12
L15A19D2550K	Dimmable 15W Omnidirectional A19 - 5000K	120	15	100W	1600	106.7	5000K	80	12



15,000 HOUR OMNIDIRECTIONAL A-LAMPS (REPLACES 100W)

15W DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 100W)

L15A19D1527K	Dimmable 15W Omnidirectional A19 - 2700K	120	15	100W	1600	106.7	2700K	80	12
L15A19D1530K	Dimmable 15W Omnidirectional A19 - 3000K	120	15	100W	1650	110	3000K	80	12
L15A19D1541K	Dimmable 15W Omnidirectional A19 - 4100K	120	15	100W	1700	113.3	4100K	80	12
L15A19D1550K	Dimmable 15W Omnidirectional A19 - 5000K	120	15	100W	1750	116.7	5000K	80	12



15W NON-DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 100W)

L16A19N1527K	Non-Dimmable 15W Omnidirectional A19 - 2700K	120	15	100W	1600	106.7	2700K	80	12
L16A19N1530K	Non-Dimmable 15W Omnidirectional A19 - 3000K	120	15	100W	1650	110	3000K	80	12
L16A19N1541K	Non-Dimmable 15W Omnidirectional A19 - 4100K	120	15	100W	1700	113.3	4100K	80	12
L16A19N1550K	Non-Dimmable 15W Omnidirectional A19 - 5000K	120	15	100W	1750	116.7	5000K	80	12



10,000 HOUR GENERAL PURPOSE A-LAMPS (REPLACES 100W)

14W NON-DIMMABLE A19 - GENERAL PURPOSE A-LAMP (REPLACES 100W) 4 PACK

L16A19N1027K4	Non-Dimmable 14W General Purpose A19 - 2700K 4 Pack	120	14	100W	1500	107.1	2700K	80	12
L16A19N1041K4	Non-Dimmable 14W General Purpose A19 - 4100K 4 Pack	120	14	100W	1500	107.1	4100K	80	12



25,000 HOUR ELITE OMNIDIRECTIONAL A-LAMPS (REPLACES 75W)

11.5W DIMMABLE A19 - ELITE OMNIDIRECTIONAL A-LAMP (REPLACES 75W)

L11A19D2527K	Dimmable 11.5W Omnidirectional A19 - 2700K	120	11.5	75W	1100	95.7	2700K	80	12
L11A19D2530K	Dimmable 11.5W Omnidirectional A19 - 3000K	120	11.5	75W	1100	95.7	3000K	80	12
L11A19D2541K	Dimmable 11.5W Omnidirectional A19 - 4100K	120	11.5	75W	1100	95.7	4100K	80	12
L11A19D2550K	Dimmable 11.5W Omnidirectional A19 - 5000K	120	11.5	75W	1100	95.7	5000K	80	12



15,000 HOUR OMNIDIRECTIONAL A-LAMPS (REPLACES 75W)

11W NON-DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 75W)

L11A19N1527K	Non-Dimmable 11W Omnidirectional A19 - 2700K	120	11	75W	1100	100	2700K	80	12
L11A19N1530K	Non-Dimmable 11W Omnidirectional A19 - 3000K	120	11	75W	1100	100	3000K	80	12
L11A19N1541K	Non-Dimmable 11W Omnidirectional A19 - 4100K	120	11	75W	1100	100	4100K	80	12
L11A19N1550K	Non-Dimmable 11W Omnidirectional A19 - 5000K	120	11	75W	1100	100	5000K	80	12



Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing

5 YEAR WARRANTY
 25,000 HOUR LAMPS

3 YEAR WARRANTY
 15,000 HOUR LAMPS

1 YEAR WARRANTY
 10,000 HOUR LAMPS

Consult www.tpci.com for warranty information.



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	-----	-----	---------------

25,000 HOUR ELITE OMNIDIRECTIONAL A-LAMPS (REPLACES 60W)

9W DIMMABLE A19 - ELITE OMNIDIRECTIONAL A-LAMP (REPLACES 60W)



L9A19D2524K	Dimmable 9W Omnidirectional A19 - 2400K	120	9	60W	700	77.7	2400K	80	12
L9A19D2527K	Dimmable 9W Omnidirectional A19 - 2700K	120	9	60W	800	88.9	2700K	80	12
L9A19D2530K	Dimmable 9W Omnidirectional A19 - 3000K	120	9	60W	800	88.9	3000K	80	12
L9A19D2541K	Dimmable 9W Omnidirectional A19 - 4100K	120	9	60W	825	91.7	4100K	80	12
L9A19D2550K	Dimmable 9W Omnidirectional A19 - 5000K	120	9	60W	825	91.7	5000K	80	12

15,000 HOUR ELITE OMNIDIRECTIONAL A-LAMPS (REPLACES 60W)

9W DIMMABLE A19 - OMNIDIRECTIONAL A-LAMP (REPLACES 60W)



L9A19D1527K	Dimmable 9W Omnidirectional A19 - 2700K	120	9	60W	800	88.9	2700K	80	12
L9A19D1530K	Dimmable 9W Omnidirectional A19 - 3000K	120	9	60W	800	88.9	3000K	80	12
L9A19D1541K	Dimmable 9W Omnidirectional A19 - 4100K	120	9	60W	825	91.7	4100K	80	12
L9A19D1550K	Dimmable 9W Omnidirectional A19 - 5000K	120	9	60W	825	91.7	5000K	80	12

9W NON-DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 60W)



L60A19N1527K	Non-Dimmable 9W Omnidirectional A19 - 2700K	120	9	60W	800	88.9	2700K	80	12
L60A19N1530K	Non-Dimmable 9W Omnidirectional A19 - 3000K	120	9	60W	800	88.9	3000K	80	12
L60A19N1541K	Non-Dimmable 9W Omnidirectional A19 - 4100K	120	9	60W	850	94.4	4100K	80	12
L60A19N1550K	Non-Dimmable 9W Omnidirectional A19 - 5000K	120	9	60W	850	94.4	5000K	80	12

10,000 HOUR GENERAL PURPOSE A-LAMPS (REPLACES 60W)

9.5W NON-DIMMABLE A19 - GENERAL PURPOSE A-LAMP (REPLACES 60W) 4 PACK



L9A19N1027K4	Non-Dimmable 9.5W General Purpose A19 - 2700K 4 Pack	120	9.5	60W	800	84.2	2700K	80	12
L9A19N1030K4	Non-Dimmable 9.5W General Purpose A19 - 3000K 4 Pack	120	9.5	60W	800	84.2	3000K	80	12
L9A19N1041K4	Non-Dimmable 9.5W General Purpose A19 - 4100K 4 Pack	120	9.5	60W	800	84.2	4100K	80	12

25,000 HOUR ELITE OMNIDIRECTIONAL A-LAMPS (REPLACES 40W)

6W DIMMABLE A19 - ELITE OMNIDIRECTIONAL A-LAMP (REPLACES 40W)



L40A19D2524K	Dimmable 6W Omnidirectional A19 - 2400K	120	6	40W	375	62.5	2400K	80	12
L40A19D2527K	Dimmable 6W Omnidirectional A19 - 2700K	120	6	40W	480	80.0	2700K	80	12
L40A19D2530K	Dimmable 6W Omnidirectional A19 - 3000K	120	6	40W	480	80.0	3000K	80	12
L40A19D2541K	Dimmable 6W Omnidirectional A19 - 4100K	120	6	40W	500	83.3	4100K	80	12
L40A19D2550K	Dimmable 6W Omnidirectional A19 - 5000K	120	6	40W	525	87.2	5000K	80	12

15,000 HOUR OMNIDIRECTIONAL A-LAMPS (REPLACES 40W)

6W NON-DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 40W)



L6A19N1527K	Non-Dimmable 6W Omnidirectional A19 - 2700K	120	6	40W	480	80.0	2700K	80	12
L6A19N1530K	Non-Dimmable 6W Omnidirectional A19 - 3000K	120	6	40W	480	80.0	3000K	80	12
L6A19N1541K	Non-Dimmable 6W Omnidirectional A19 - 4100K	120	6	40W	480	80.0	4100K	80	12
L6A19N1550K	Non-Dimmable 6W Omnidirectional A19 - 5000K	120	6	40W	480	80.0	5000K	80	12

30

Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



5 YEAR WARRANTY
25,000 HOUR LAMPS

3 YEAR WARRANTY
15,000 HOUR LAMPS

1 YEAR WARRANTY
10,000 HOUR LAMPS

Consult www.tcp.com for warranty information.

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	-----	-----	---------------

25,000 HOUR ELITE GU24 BASED A-LAMPS (REPLACES 60W)
10W GU24 BASED DIMMABLE A19 - OMNIDIRECTIONAL (REPLACES 60W)

LED10A19GUDOD27K	Dimmable 10W GU24 OmniDirectional A19 - 2700K	120	10	60W	850	85	2700K	80	12
LED10A19GUDOD30K	Dimmable 10W GU24 OmniDirectional A19 - 3000K	120	10	60W	850	85	3000K	80	12
LED10A19GUDOD41K	Dimmable 10W GU24 OmniDirectional A19 - 4100K	120	10	60W	850	85	4100K	80	12



25,000 HOUR ELITE GU24 BASED A-LAMPS (REPLACES 100W)
14W GU24 BASED DIMMABLE A21 - OMNIDIRECTIONAL (REPLACES 100W)

L14A21GUD2527K	Dimmable 14W GU24 OmniDirectional A21 - 2700K	120	14	100W	1600	114.3	2700K	80	12
L14A21GUD2530K	Dimmable 14W GU24 OmniDirectional A21 - 3000K	120	14	100W	1600	114.3	3000K	80	12
L14A21GUD2541K	Dimmable 14W GU24 OmniDirectional A21 - 4100K	120	14	100W	1700	121.4	4100K	80	12
L14A21GUD2550K	Dimmable 14W GU24 OmniDirectional A21 - 5000K	120	14	100W	1700	121.4	5000K	80	12



25,000 HOUR ELITE 60W WET LOCATION A-LAMPS (REPLACES 60W)
9.5W WET LOCATION A19 OMNIDIRECTIONAL A-LAMP (REPLACES 60W)

LED10A19DOD27KW	Dimmable 9.5W Omnidirectional Wet Location A19 - 2700K	120	9.5	60W	800	84.2	2700K	80	12
LED10A19DOD30KW	Dimmable 9.5W Omnidirectional Wet Location A19 - 3000K	120	9.5	60W	825	86.8	3000K	80	12
LED10A19DOD41KW	Dimmable 9.5W Omnidirectional Wet Location A19 - 4100K	120	9.5	60W	850	89.5	4100K	80	12
LED10A19DOD50KW	Dimmable 9.5W Omnidirectional Wet Location A19 - 5000K	120	9.5	60W	850	89.5	5000K	80	12



Item Number	Item Description	Voltage	Wattage/Lumens			Wattage/LPW			CCT	CRI	Case Quantity
			16W	8W	4W	16W	8W	4W			

25,000 HOUR ELITE 100W LED THREE WAY A-LAMPS (REPLACES 100W/60W/40W)
16W/8W/4W A21 - THREE WAY A-LAMPS (REPLACES 100W/60W/40W)

LED16A21D3WAY27K	16W/8W/4W A21 - 2700K	120	1600	800	480	100	100	120	2700K	80	12
LED16A21D3WAY30K	16W/8W/4W A21 - 3000K	120	1600	800	480	100	100	120	3000K	80	12
LED16A21D3WAY41K	16W/8W/4W A21 - 4100K	120	1600	800	480	100	100	120	4100K	80	12
LED16A21D3WAY50K	16W/8W/4W A21 - 5000K	120	1600	800	480	100	100	120	5000K	80	12





Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------------	-----	-----	---------------

25,000 HOUR ELITE GU5.3 50W DIMMABLE LED MR16

7W DIMMABLE ELITE VALUE GU5.3 12V MR16 (50W EQUIVALENT)



LED712VVMR16V24KNFL	7W 12V MR16 - 2400K 20°	12	7	50W	450	64.3	20	2400K	80	12
LED712VVMR16V24KFL	7W 12V MR16 - 2400K 40°	12	6.5	50W	450	69.2	40	2400K	80	12
LED712VVMR16V27KNFL	7W 12V MR16 - 2700K 20°	12	7	50W	500	71.4	20	2700K	80	12
LED712VVMR16V27KFL	7W 12V MR16 - 2700K 40°	12	6.5	50W	500	76.9	40	2700K	80	12
LED712VVMR16V30KNFL	7W 12V MR16 - 3000K 20°	12	7	50W	500	71.4	20	3000K	80	12
LED712VVMR16V30KFL	7W 12V MR16 - 3000K 40°	12	6.5	50W	500	76.9	40	3000K	80	12
LED712VVMR16V41KNFL	7W 12V MR16 - 4100K 20°	12	7	50W	500	71.4	20	4100K	80	12
LED712VVMR16V41KFL	7W 12V MR16 - 4100K 40°	12	6.5	50W	500	76.9	40	4100K	80	12
LED712VVMR16V50KFL	7W 12V MR16 - 5000K 40°	12	7	50W	500	71.4	40	5000K	80	12

7W DIMMABLE ELITE GU5.3 12V MR16 (50W EQUIVALENT) HIGH CRI CRI>90 R9>50



LED712VVMR16927KNFL	7W 12V MR16 - 2700K 20°	12	7	50W	425	60.7	20	2700K	90	12
LED712VVMR16927KNFLB	7W 12V MR16 - 2700K 20° - Black	12	7	50W	425	60.7	20	2700K	90	12
LED712VVMR16927KFL	7W 12V MR16 - 2700K 40°	12	6.5	50W	425	65.4	40	2700K	90	12
LED712VVMR16927KFLB	7W 12V MR16 - 2700K 40° - Black	12	6.5	50W	425	65.4	40	2700K	90	12
LED712VVMR16930KNFL	7W 12V MR16 - 3000K 20°	12	7	50W	425	60.7	20	3000K	90	12
LED712VVMR16930KFL	7W 12V MR16 - 3000K 40°	12	6.5	50W	425	65.4	40	3000K	90	12
LED712VVMR16941KNFL	7W 12V MR16 - 4100K 20°	12	7	50W	425	60.7	20	4100K	90	12
LED712VVMR16941KFL	7W 12V MR16 - 4100K 40°	12	6.5	50W	425	65.4	40	4100K	80	12

5W DIMMABLE ELITE VALUE GU5.3 12V MR16 (35W EQUIVALENT)



LED512VVMR1627KNFL	5W 12V MR16 - 2700K 20°	12	5	35W	400	80	20	2700K	80	12
LED512VVMR1627KFL	5W 12V MR16 - 2700K 40°	12	5	35W	400	80	40	2700K	80	12
LED512VVMR1630KNFL	5W 12V MR16 - 3000K 20°	12	5	35W	400	80	20	3000K	80	12
LED512VVMR1630KFL	5W 12V MR16 - 3000K 40°	12	5	35W	400	80	40	3000K	80	12
LED512VVMR1641KFL	5W 12V MR16 - 4100K 40°	12	5	35W	400	80	40	4100K	80	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per-Watt	CBCP	Beam Angle	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	---------------

25,000 HOUR ELITE DIMMABLE LED GU10

7W DIMMABLE ELITE GU10 (50W EQUIVALENT)

LED7GU10MR1627KFL	5W GU10 MR16 - 2700K 40°	120	5.5	35W	380	69.1	-	40	2700K	80	12
LED7GU10MR1630KFL	5W GU10 MR16 - 3000K 40°	120	5.5	35W	380	69.1	-	40	3000K	80	12
LED7GU10MR1641KFL	5W GU10 MR16 - 4100K 40°	120	5.5	35W	420	76.4	-	40	4100K	80	12



7W DIMMABLE DESIGNER ELITE GU10 (50W EQUIVALENT)

LED7MR16GU1024KFL	6W GU10 MR16 - 2400K 40°	120	6	50W	450	75	-	40	2400K	80	12
LED7MR16GU1027KNFL	5.5W GU10 MR16 - 2700K 40°	120	5.5	50W	500	90.9	-	20	2700K	80	12
LED7MR16GU1027KFL	6W GU10 MR16 - 2700K 40°	120	6	50W	500	83.3	-	40	2700K	80	12
LED7MR16GU1030KNFL	5.5W GU10 MR16 - 3000K 20°	120	5.5	50W	500	90.9	-	20	3000K	80	12
LED7MR16GU1030KFL	6W GU10 MR16 - 3000K 40°	120	6	50W	500	83.3	-	40	3000K	80	12
LED7MR16GU1041KNFL	7W GU10 MR16 - 4100K 20°	120	5.5	50W	500	90.9	-	20	4100K	80	12
LED7MR16GU1041KFL	7W GU10 MR16 - 4100K 40°	120	6	50W	500	83.3	-	40	4100K	80	12



25,000 HOUR ELITE DIMMABLE LED PAR16

7W DIMMABLE PAR16 (50W EQUIVALENT)

LED7P1624KFL	7W PAR16 - 2400K 40°	120	7	50W	500	71.4	1052	40	2400K	80	12
LED7P1627KNFL	7W PAR16 - 2700K 20°	120	7	50W	500	71.4	3296	20	2700K	80	12
LED7P1627KFL	7W PAR16 - 2700K 40°	120	7	50W	500	71.4	1057	40	2700K	80	12
LED7P1630KNFL	7W PAR16 - 3000K 20°	120	7	50W	500	71.4	3296	20	3000K	80	12
LED7P1630KFL	7W PAR16 - 3000K 40°	120	7	50W	500	71.4	1057	40	3000K	80	12
LED7P1641KNFL	7W PAR16 - 4100K 20°	120	7	50W	500	71.4	3296	20	4100K	80	12
LED7P1641KFL	7W PAR16 - 4100K 40°	120	7	50W	500	71.4	1057	40	4100K	80	12





Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	CCT	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----	-----	-----	---------------

25,000 HOUR DIMMABLE LED G25

DIMMABLE 4W AND 6W G25 FROSTED



LED5G25D27KF	Dimmable 4W G25 - 2700K Frosted	120	4	40W	350	87.5	2700K	80	12
LED5G25D30KF	Dimmable 4W G25 - 3000K Frosted	120	4	40W	350	87.5	3000K	80	12
L6G25D2527KF	Dimmable 6W G25 - 2700K Frosted	120	6	60W	525	87.5	2700K	80	12
L6G25D2530KF	Dimmable 6W G25 - 3000K Frosted	120	6	60W	525	87.5	3000K	80	12

25,000 HOUR NON DIMMABLE LED WET LOCATION S14

NON DIMMABLE 5W WET LOCATION S14



LED5E26S1427K	LED 4W Wet Location S14 - 2700K Clear	120	4	40W	300	75	2700K	80	12
LED5E26S1430K	LED 4W Wet Location S14 - 3000K Clear	120	4	40W	300	75	3000K	80	12
LED5E26S1441K	LED 4W Wet Location S14 - 4100K Clear	120	4	40W	300	75	4100K	80	12
LED5E26S1427KF	LED 4W Wet Location S14 - 2700K Frosted	120	4	40W	300	75	2700K	80	12
LED5E26S1430KF	LED 4W Wet Location S14 - 3000K Frosted	120	4	40W	300	75	3000K	80	12
LED5E26S1441KF	LED 4W Wet Location S14 - 4100K Frosted	120	4	40W	300	75	4100K	80	12

Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



Consult www.tpci.com for warranty information.

Item Number Item Description Voltage Lamp Watts Wattage Equivalent Lumens LPW CCT (Kelvin) CRI Case Quantity

25,000 HOUR DIMMABLE LED DECO LAMPS

DIMMABLE 5W DECO LAMPS

LED5E12G1627K	LED 5W Dim Candelabra G16 Globe - 2700K	120	5	40W	350	70	2700K	80	12
LED5E26G1627K	LED 5W Dim G16 Globe - 2700K	120	5	40W	350	70	2700K	80	12
LED5E12G1627KF	LED 5W Dim Candelabra Frost G16 Globe - 2700K	120	5	40W	350	70	2700K	80	12
LED5E26G1627KF	LED 5W Dim Frost G16 Globe - 2700K	120	5	40W	350	70	2700K	80	12
LED5E12B1127K	LED 5W Dim Candelabra Blunt Tip - 2700K	120	5	40W	350	70	2700K	80	12
LED5E12B1130K	LED 5W Dim Candelabra Blunt Tip - 3000K	120	5	40W	375	75	3000K	80	12
LED5E12B1150K	LED 5W Dim Candelabra Blunt Tip - 5000K	120	5	40W	375	75	5000K	80	12
LED5E26B1127K	LED 5W Dim Blunt Tip - 2700K	120	5	40W	350	70	2700K	80	12
LED5E26B1130K	LED 5W Dim Blunt Tip - 3000K	120	5	40W	375	75	3000K	80	12
LED5E12B1124KF	LED 5W Dim Candelabra Frost Blunt Tip - 2400K	120	5	40W	300	60	2400K	80	12
LED5E12B1127KF	LED 5W Dim Candelabra Frost Blunt Tip - 2700K	120	5	40W	350	70	2700K	80	12
LED5E12B1150KF	LED 5W Dim Candelabra Frost Blunt Tip - 5000K	120	5	40W	375	75	5000K	80	12
LED5E26B1127KF	LED 5W Dim Frost Blunt Tip - 2700K	120	5	40W	350	70	2700K	80	12
LED5E12F1127K	LED 5W Dim Candelabra F11 Flame Tip - 2700K	120	5	40W	350	70	2700K	80	12
LED5E26F1127K	LED 5W Dim F11 Flame Tip - 2700K	120	5	40W	350	70	2700K	80	12



25,000 HOUR DIMMABLE LED DECO LAMPS CONTINUED

DIMMABLE 4W DECO LAMPS

LED4E12G1627K	LED 4W Dim Candelabra G16 Globe - 2700K	120	4	25W	280	70	2700K	80	12
LED4E26G1627K	LED 4W Dim G16 Globe - 2700K	120	4	25W	280	70	2700K	80	12
LED4E12G1627KF	LED 4W Dim Candelabra Frost G16 Globe - 2700K	120	4	25W	280	70	2700K	80	12
LED4E26G1627KF	LED 4W Dim Frost G16 Globe - 2700K	120	4	25W	280	70	2700K	80	12
LED4E12B1124K	LED 4W Dim Candelabra Blunt Tip - 2400K	120	4	25W	250	62.5	2400K	80	12
LED4E12B1127K	LED 4W Dim Candelabra Blunt Tip - 2700K	120	4	25W	280	70	2700K	80	12
LED4E12B1150K	LED 4W Dim Candelabra Blunt Tip - 5000K	120	4	25W	280	70	5000K	80	12
LED4E26B1124K	LED 4W Dim Blunt Tip - 2400K	120	4	25W	250	62.5	2400K	80	12
LED4E26B1127K	LED 4W Dim Blunt Tip - 2700K	120	4	25W	280	70	2700K	80	12
LED4E12B1127KF	LED 4W Dim Candelabra Frosted Blunt Tip - 2700K	120	4	25W	280	70	2700K	80	12
LED4E26B1127KF	LED 4W Dim Frosted Blunt Tip - 2700K	120	4	25W	280	70	2700K	80	12
LED4E12F1127K	LED 4W Dim Candelabra F11 Flame - 2700K	120	4	25W	280	70	2700K	80	12
LED4E26F1127K	LED 4W Dim F11 Flame Tip - 2700K	120	4	25W	280	70	2700K	80	12





Item Number Item Description Voltage Lamp Watts Wattage Equivalent Lumens LPW CCT (Kelvin) CRI Base Type Case Quantity

25,000 HOUR LED ELEVATOR LAMPS (NON-DIMMABLE)



LED2W1383V2	LED 2W 1383 Frosted Elevator Lamp - 2700K	12	2	20W	150	75	2700K	80	BA15S	12
LED2WGBFV2	LED 2W GBF Frosted Elevator Lamp - 2700K	12	2	20W	150	75	2700K	80	BA15D	12

Item Number Lamp Type Item Description Voltage Lamp Watts Wattage Equivalent Lumens LPW Base CRI Color Temperature Glass Type Case Quantity

15,000 HOUR LED FILAMENT LAMPS, DIMMABLE

DIMMABLE LED 4.5W A19 FILAMENT, CLEAR, E26 BASE



FA19D4022KC	A19 Dim LED 4.5w A19, 22K Clear	120	4.5	40W	425	94	E26	80	2200	Clear	12
FA19D4027EC	A19 Dim LED 4.5w A19, 27K Clear	120	4.5	40W	450	100	E26	80	2700	Clear	12

DIMMABLE LED 4.5W A19 FILAMENT, FROSTED, E26 BASE

FA19D4027EW	A19 Dim LED 4.5w A19, 27K Frost	120	4.5	40W	450	100	E26	80	2700	Frost	12
FA19D4050EW	A19 Dim LED 4.5w A19, 50K Frost	120	4.5	40W	450	100	E26	80	5000	Frost	12

DIMMABLE LED 4.5W A19 FILAMENT, COLORED GLASS, E26 BASE

FA19D40BC	A19 Dim LED 4.5w A19, Clear Blue	120	4.5	40W	Blue	-	E26	80	Blue	Blue	12
FA19D40YC	A19 Dim LED 4.5w A19, Clear Yellow	120	4.5	40W	Yellow	-	E26	80	Yellow	Yellow	12

DIMMABLE LED 8W A19 FILAMENT, CLEAR, E26 BASE

FA19D6022KC	A19 Dim LED 8w A19, 22K Clear	120	8	60W	775	97	E26	80	2200	Clear	12
FA19D6027EC	A19 Dim LED 8w A19, 27K Clear	120	8	60W	800	100	E26	80	2700	Clear	12
FA19D6050EC	A19 Dim LED 8w A19, 50K Clear	120	8	60W	800	100	E26	80	5000	Clear	12

DIMMABLE LED 8W A19 FILAMENT, FROST, E26 BASE

FA19D6022KW	A19 Dim LED 8w A19, 22K Frost	120	8	60W	775	97	E26	80	2200	Frost	12
FA19D6027EW	A19 Dim LED 8w A19, 27K Frost	120	8	60W	800	100	E26	80	2700	Frost	12
FA19D6030EW	A19 Dim LED 8w A19, 30K Frost	120	8	60W	800	100	E26	80	3000	Frost	12
FA19D6040EW	A19 Dim LED 8w A19, 40K Frost	120	8	60W	800	100	E26	80	4000	Frost	12
FA19D6050EW	A19 Dim LED 8w A19, 50K Frost	120	8	60W	800	100	E26	80	5000	Frost	12

DIMMABLE LED 8W A19 FILAMENT, COLORED GLASS, E26 BASE

FA19D60BC	A19 Dim LED 8w A19, Clear Blue	120	8	40W	Blue	-	E26	80	Blue	Blue	12
FA19D60YC	A19 Dim LED 8w A19, Clear Yellow	120	8	40W	Yellow	-	E26	80	Yellow	Yellow	12

DIMMABLE LED 4W ST19 FILAMENT, E26 BASE



FST19D4022KC	ST19 Dim LED 4w ST19, 22K Clear	120	4	40W	425	106	E26	80	2200	Clear	12
FST19D4022KG	ST19 Dim LED 4w ST19, 22K Amber	120	4	40W	425	106	E26	80	2200	Amber	12

Item Number	Lamp Type	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	Base	CRI	Color Temperature	Glass Type	Case Quantity
-------------	-----------	------------------	---------	------------	--------------------	--------	-----	------	-----	-------------------	------------	---------------

15,000 HOUR LED FILAMENT LAMPS, DIMMABLE CONTINUED

DIMMABLE LED 3W B11 Deco, E12 Base

FB11D2522KE12C	B11	Dim LED 3w B11, 22K Clear	120	3	25W	225	75	E12	80	2200	Clear	12
FB11D2527EE12C	B11	Dim LED 3w B11, 27K Clear	120	3	25W	250	83	E12	80	2700	Clear	12
FB11D2527KE12G	B11	Dim LED 3w B11, 27K Amber	120	3	25W	250	83	E12	80	2700	Amber	12
FB11D2527EE12W	B11	Dim LED 3w B11, 27K Frost	120	3	25W	250	83	E12	80	2700	Frost	12
FB11D2550EE12C	B11	Dim LED 3w B11, 50K Clear	120	3	25W	250	83	E12	80	5000	Clear	12

DIMMABLE LED 4W B11 Deco, E12 Base

FB11D4022KE12C	B11	Dim LED 4w B11, 22K Clear	120	4	40W	300	75	E12	80	2200	Clear	12
FB11D4022KE12W	B11	Dim LED 4w B11, 22K Frost	120	4	40W	300	75	E12	80	2200	Frost	12
FB11D4027EE12C	B11	Dim LED 4w B11, 27K Clear	120	4	40W	300	75	E12	80	2700	Clear	12
FB11D4027EE12W	B11	Dim LED 4w B11, 27K Frost	120	4	40W	300	75	E12	80	2700	Frost	12
FB11D4050EE12C	B11	Dim LED 4w B11, 50K Clear	120	4	40W	300	75	E12	80	5000	Clear	12
FB11D4050EE12W	B11	Dim LED 4w B11, 50K Frost	120	4	40W	300	75	E12	80	5000	Frost	12

DIMMABLE LED 5.5W B11 Deco, E12 Base

FB11D6027EE12CS	B11	Dim LED 5.5w B11, 27K Clear	120	5.5	60W	500	91	E12	80	2700	Clear	12
FB11D6050EE12CS	B11	Dim LED 5.5w B11, 50K Clear	120	5.5	60W	500	91	E12	80	5000	Clear	12

DIMMABLE LED 3W B11 Deco, E26 Base

FB11D2527EC	B11	Dim LED 3w B11, 27K Clear	120	3	25W	250	83	E26	80	2700	Clear	12
FB11D2527EW	B11	Dim LED 3w B11, 27K Frost	120	3	25W	250	83	E26	80	2700	Frost	12

DIMMABLE LED 4W B11 Deco, E26 Base

FB11D4022KC	B11	Dim LED 4w B11, 22K Clear	120	4	40W	300	75	E26	80	2200	Clear	12
FB11D4022KW	B11	Dim LED 4w B11, 22K Frost	120	4	40W	300	75	E26	80	2200	Frost	12
FB11D4027EC	B11	Dim LED 4w B11, 27K Clear	120	4	40W	300	75	E26	80	2700	Clear	12
FB11D4027EW	B11	Dim LED 4w B11, 27K Frost	120	4	40W	300	75	E26	80	2700	Frost	12
FB11D4050EC	B11	Dim LED 4w B11, 50K Clear	120	4	40W	300	75	E26	80	5000	Clear	12
FB11D4050EW	B11	Dim LED 4w B11, 50K Frost	120	4	40W	300	75	E26	80	5000	Frost	12

DIMMABLE LED 5W B11 Deco, E26 Base

FB11D6022KC	B11	Dim LED 5w B11, 22K Clear	120	5	60W	475	95	E26	80	2200	Clear	12
FB11D6022KW	B11	Dim LED 5w B11, 22K Frost	120	5	60W	475	95	E26	80	2200	Frost	12
FB11D6027EC	B11	Dim LED 5w B11, 27K Clear	120	5	60W	500	100	E26	80	2700	Clear	12
FB11D6027EW	B11	Dim LED 5w B11, 27K Frost	120	5	60W	500	100	E26	80	2700	Frost	12
FB11D6050EC	B11	Dim LED 5w B11, 50K Clear	120	5	60W	500	100	E26	80	5000	Clear	12
FB11D6050EW	B11	Dim LED 5w B11, 50K Frost	120	5	60W	500	100	E26	80	5000	Frost	12



Item Number	Lamp Type	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	Base	CRI	Color Temperature	Glass Type	Case Quantity
-------------	-----------	------------------	---------	------------	--------------------	--------	-----	------	-----	-------------------	------------	---------------

DIMMABLE LED 3W F11 FILAMENT, E12 BASE



FF11D2522KE12W	F11	Dim LED 3w F11, 22K Frost	120	3	25W	225	75	E12	80	2200	Frost	12
FF11D2527EE12C	F11	Dim LED 3w F11, 27K Clear	120	3	25W	250	83	E12	80	2700	Clear	12
FF11D2527KE12G	F11	Dim LED 3w F11, 27K Amber	120	3	25W	225	75	E12	80	2700	Amber	12
FF11D2527EE12W	F11	Dim LED 3w F11, 27K Frost	120	3	25W	250	83	E12	80	2700	Frost	12
FF11D2550EE12C	F11	Dim LED 3w F11, 50K Clear	120	3	25W	250	83	E12	80	5000	Clear	12

DIMMABLE LED 4W F11 FILAMENT, E12 BASE

FF11D4022KE12C	F11	Dim LED 4w F11, 22K Clear	120	4	40W	300	75	E12	80	2200	Clear	12
FF11D4022KE12W	F11	Dim LED 4w F11, 22K Frost	120	4	40W	300	75	E12	80	2200	Frost	12
FF11D4027EE12C	F11	Dim LED 4w F11, 27K Clear	120	4	40W	300	75	E12	80	2700	Clear	12
FF11D4027KE12G	F11	Dim LED 4w F11, 27K Amber	120	4	40W	300	75	E12	80	2700	Amber	12
FF11D4027EE12W	F11	Dim LED 4w F11, 27K Frost	120	4	40W	300	75	E12	80	2700	Frost	12
FF11D4050EE12C	F11	Dim LED 4w F11, 50K Clear	120	4	40W	300	75	E12	80	5000	Clear	12

DIMMABLE LED 3W F11 Deco, E26 BASE



FF11D2522KC	F11	Dim LED 3w F11, 22K Clear	120	3	25W	225	75	E26	80	2200	Clear	12
FF11D2522KW	F11	Dim LED 3w F11, 22K Frost	120	3	25W	225	75	E26	80	2200	Frost	12
FF11D2527EC	F11	Dim LED 3w F11, 27K Clear	120	3	25W	250	83	E26	80	2700	Clear	12
FF11D2527EW	F11	Dim LED 3w F11, 27K Frost	120	3	25W	250	83	E26	80	2700	Frost	12
FF11D2550EC	F11	Dim LED 3w F11, 50K Clear	120	3	25W	250	83	E26	80	5000	Clear	12

DIMMABLE LED 4W F11 Deco, E26 BASE

FF11D4027EC	F11	Dim LED 4w F11, 27K Clear	120	4	40W	300	75	E26	80	2700	Clear	12
FF11D4050EW	F11	Dim LED 4w F11, 50K Frost	120	4	40W	300	75	E26	80	2700	Frost	12

DIMMABLE LED 5W F11 Deco, E26 BASE

FF11D6022KC	F11	Dim LED 5w F11, 22K Clear	120	5	60W	475	95	E26	80	2200	Clear	12
FF11D6022KW	F11	Dim LED 5w F11, 22K Frost	120	5	60W	475	95	E26	80	2200	Frost	12
FF11D6027EW	F11	Dim LED 5w F11, 27K Frost	120	5	60W	500	100	E26	80	2700	Frost	12
FF11D6050EC	F11	Dim LED 5w F11, 50K Clear	120	5	60W	500	100	E26	80	5000	Clear	12
FF11D6050EW	F11	Dim LED 5w F11, 50K Frost	120	5	60W	500	100	E26	80	5000	Frost	12

Item Number	Lamp Type	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	Base	CRI	Color Temperature	Glass Type	Case Quantity
-------------	-----------	------------------	---------	------------	--------------------	--------	-----	------	-----	-------------------	------------	---------------

DIMMABLE LED 4W G25 FILAMENT DECO, E26 BASE

FG25D4022KC	G25	Dim LED 4w G25, 22K Clear	120	4	40W	295	74	E26	80	2200	Clear	12
FG25D4022KW	G25	Dim LED 4w G25, 22K Frost	120	4	40W	295	74	E26	80	2200	Frost	12
FG25D4027EC	G25	Dim LED 4w G25, 27K Clear	120	4	40W	350	88	E26	80	2700	Clear	12
FG25D4027EW	G25	Dim LED 4w G25, 27K Frost	120	4	40W	350	88	E26	80	2700	Frost	12
FG25D4050EC	G25	Dim LED 4w G25, 50K Clear	120	4	40W	350	88	E26	80	5000	Clear	12
FG25D4050EW	G25	Dim LED 4w G25, 50K Frost	120	4	40W	350	88	E26	80	5000	Frost	12



DIMMABLE LED 4.5W G25 FILAMENT DECO, E26 BASE

FG25D6027EC	G25	Dim LED 4.5w G25, 27K Clear	120	4.5	60W	500	111	E26	80	2700	Clear	12
FG25D6027EW	G25	Dim LED 4.5w G25, 27K Frost	120	4.5	60W	500	111	E26	80	2700	Frost	12
FG25D6050EC	G25	Dim LED 4.5w G25, 50K Clear	120	4.5	60W	500	111	E26	80	2700	Clear	12
FG25D6050EW	G25	Dim LED 4.5w G25, 50K Frost	120	4.5	60W	500	111	E26	80	2700	Frost	12

DIMMABLE LED 3W G16 FILAMENT, E12 BASE

FG16D2522KE12C	G16	Dim LED 3w G16, 22K Clear	120	3	25W	225	75	E12	80	2200	Clear	12
FG16D2527EE12C	G16	Dim LED 3w G16, 27K Clear	120	3	25W	250	83	E12	80	2700	Clear	12
FG16D2550EE12C	G16	Dim LED 3w G16, 50K Clear	120	3	25W	250	83	E12	80	5000	Clear	12



DIMMABLE LED 4W G16 FILAMENT, E12 BASE

FG16D4022KE12C	G16	Dim LED 4w G16, 22K Clear	120	4	40W	325	81	E12	80	2200	Clear	12
FG16D4022KE12W	G16	Dim LED 4w G16, 22K Frost	120	4	40W	325	81	E12	80	2200	Frost	12
FG16D4027EE12W	G16	Dim LED 4w G16, 27K Frost	120	4	40W	350	88	E12	80	2700	Frost	12
FG16D4050EE12C	G16	Dim LED 4w G16, 50K Clear	120	4	40W	350	88	E12	80	5000	Clear	12
FG16D4050EE12W	G16	Dim LED 4w G16, 50K Frost	120	4	40W	350	88	E12	80	5000	Frost	12



DIMMABLE LED 3W G16 DECO, E26 BASE

FG16D2522KW	G16	Dim LED 3w G16, 22K Frost	120	3	25W	225	75	E26	80	2200	Frost	12
FG16D2527EC	G16	Dim LED 3w G16, 27K Clear	120	3	25W	250	83	E26	80	2700	Clear	12
FG16D2527EW	G16	Dim LED 3w G16, 27K Frost	120	3	25W	250	83	E26	80	2700	Frost	12
FG16D2550EC	G16	Dim LED 3w G16, 50K Clear	120	3	25W	250	83	E26	80	5000	Clear	12
FG16D2550EW	G16	Dim LED 3w G16, 50K Frost	120	3	25W	250	83	E26	80	5000	Frost	12



DIMMABLE LED 3W G16 DECO, E26 BASE

FG16D4022KW	G16	Dim LED 4w G16, 22K Frost	120	4	40W	325	81	E26	80	2200	Frost	12
FG16D4027EC	G16	Dim LED 4w G16, 27K Clear	120	4	40W	350	88	E26	80	2700	Clear	12
FG16D4027EW	G16	Dim LED 4w G16, 27K Frost	120	4	40W	350	88	E26	80	2700	Frost	12
FG16D4050EC	G16	Dim LED 4w G16, 50K Clear	120	4	40W	350	88	E26	80	5000	Clear	12
FG16D4050EW	G16	Dim LED 4w G16, 50K Frost	120	4	40W	350	88	E26	80	5000	Frost	12





Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Base	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----------------	------	------------	-----	-----	------	---------------

15,000 HOUR PRO DIMMABLE LED PARS

13W DIMMABLE PRO LINE PAR38 (REPLACES 90W)



L90P38D15V30KFL	13W Dimmable PAR38 - 3000K 40° Pro	120	13	90W	1100	84.6	-	40	3000K	80	E26	12
-----------------	------------------------------------	-----	----	-----	------	------	---	----	-------	----	-----	----

9W DIMMABLE PRO LINE PAR30 (REPLACES 75W)



L75P30D15V30KFL	LED 9W Dimmable PAR30 - 3000K 40° Pro	120	9	75W	720	80	-	40	3000K	80	E26	12
-----------------	---------------------------------------	-----	---	-----	-----	----	---	----	-------	----	-----	----

7W DIMMABLE PRO LINE PAR20 (REPLACES 50W)



L50P20D15V30KFL	LED 7W Dimmable PAR20 - 3000K 40° Pro	120	7	50W	525	75	-	40	3000K	80	E26	12
-----------------	---------------------------------------	-----	---	-----	-----	----	---	----	-------	----	-----	----

15,000 HOUR PRO DIMMABLE LED BR5

14W DIMMABLE PRO LINE BR40 (REPLACES 75W)



L75BR40D15V27K	LED 14W Dimmable BR40 - 2700K Pro	120	14	75W	1065	76.1	110	-	2700K	80	E26	12
----------------	-----------------------------------	-----	----	-----	------	------	-----	---	-------	----	-----	----

9W DIMMABLE PRO LINE BR30 (REPLACES 65W)



L65BR30D15V27K	LED 9W Dimmable BR30 - 2700K Pro	120	9	65W	650	72.2	110	-	2700K	80	E26	12
----------------	----------------------------------	-----	---	-----	-----	------	-----	---	-------	----	-----	----

7.5W DIMMABLE PRO LINE R20 (REPLACES 50W)



L50R20D15V27K	LED 7W Dimmable R20 - 2700K Pro	120	7.5	50W	500	66.7	110	-	2700K	80	E26	12
---------------	---------------------------------	-----	-----	-----	-----	------	-----	---	-------	----	-----	----

15,000 HOUR PRO DIMMABLE LED ALL GLASS DECORATIVE

4W DIMMABLE PRO LINE G25 (REPLACES 40W)



FG25D40V27W	LED 4W Dimmable G25 - 2700K Frosted Pro	120	4	40W	350	87.5	-	-	2700K	80	E26	12
-------------	---	-----	---	-----	-----	------	---	---	-------	----	-----	----

4W DIMMABLE PRO LINE B11 (REPLACES 40W)



FB11D40V27E12C	LED 4W Dimmable B11 - 2700K Frosted Pro	120	4	40W	350	87.5	-	-	2700K	80	E12	12
FB11D40V50E12C	LED 4W Dimmable B11 - 5000K Frosted Pro	120	4	40W	350	87.5	-	-	5000K	80	E12	12

40

Many items are ENERGY STAR® qualified. Visit energystar.gov for a full listing



5 YEAR WARRANTY

Consult www.tcp.com for warranty information.



Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CBCP	Beam Angle	CCT	CRI	Base	Case Quantity
15,000 HOUR LED ALL GLASS A19 – PROLINE												
DIMMABLE 8W ALL GLASS A19 – PROLINE												
LFF60A19D1527K	LED 8W Dimmable A19 - 2700K Frosted Pro	120	8	60W	725	90.6	-	-	2700K	80	E26	12
LFF60A19D1550K	LED 8W Dimmable A19 - 5000K Frosted Pro	120	8	60W	725	90.6	-	-	5000K	80	E26	12
LFC60A19D1527K	LED 8W Dimmable A19 - 2700K Clear Pro	120	8	60W	725	90.6	-	-	2700K	80	E26	12
NON DIMMABLE 8W ALL GLASS A19 – PROLINE												
LFF60A19N1527K	LED 8W Non Dimmable A19 - 2700K Frosted Pro	120	8	60W	725	90.6	-	-	2700K	80	E26	12
LFF60A19N1550K	LED 8W Non Dimmable A19 - 5000K Frosted Pro	120	8	60W	725	90.6	-	-	5000K	80	E26	12
LFC60A19N1527K	LED 8W Non Dimmable A19 - 2700K Clear Pro	120	8	60W	725	90.6	-	-	2700K	80	E26	12
LFC60A19N1550K	LED 8W Non Dimmable A19 - 5000K Clear Pro	120	8	60W	725	90.6	-	-	5000K	80	E26	12
DIMMABLE 4.5W ALL GLASS A19 – PROLINE												
LFF40A19D1527K	LED 4.5W Dimmable A19 - 2700K Frosted Pro	120	4.5	40W	425	94.4	-	-	2700K	80	E26	12
LFC40A19D1527K	LED 4.5W Dimmable A19 - 2700K Clear Pro	120	4.5	40W	425	94.4	-	-	2700K	80	E26	12
NON DIMMABLE 5W ALL GLASS A19 – PROLINE												
LFF40A19N1527K	LED 4.5W Non Dimmable A19 - 2700K Frosted Pro	120	5	40W	425	94.4	-	-	2700K	80	E26	12
LFF40A19N1550K	LED 4.5W Non Dimmable A19 - 5000K Frosted Pro	120	5	40W	425	94.4	-	-	5000K	80	E26	12
LFC40A19N1527K	LED 4.5W Non Dimmable A19 - 2700K Clear Pro	120	5	40W	425	94.4	-	-	2700K	80	E26	12
LFC40A19N1550K	LED 4.5W Non Dimmable A19 - 5000K Clear Pro	120	5	40W	425	94.4	-	-	5000K	80	E26	12
15,000 HOUR PRO LINE A-LAMPS												
15W A19 PROLINE DIMMABLE A-LAMP (REPLACES 100W)												
L100A19D15V27K	Dimmable 15W A19 - 2700K Pro	120	15	100W	1500	100	-	-	2700K	80	E26	12
14W A19 PROLINE NON DIMMABLE A-LAMP (REPLACES 100W)												
L100A19N15V27K	Non Dimmable 15W A19 - 2700K Pro	120	14	100W	1500	107.1	-	-	2700K	80	E26	12
9W A19 PROLINE DIMMABLE A-LAMP (REPLACES 60W)												
L60A19D15V27K	Dimmable 9W A19 - 2700K Pro	120	9	60W	800	88.9	-	-	2700K	80	E26	12
9W A19 PROLINE NON DIMMABLE A-LAMP (REPLACES 60W)												
L60A19N15V27K	Non Dimmable 9W A19 - 2700K Pro	120	9	60W	800	88.9	-	-	2700K	80	E26	12



Item Number	Lamp Type	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	Base	CRI	Color Temperature	Case Quantity
-------------	-----------	------------------	---------	------------	--------------------	--------	-----	------	-----	-------------------	---------------

15,000 HOUR GOOD LIFE WARM DIMMING LED FILAMENT LAMPS

DIMMABLE LED 8W A19 LAMP, E26 BASE



FA19D60GL1	A19	Dim LED 8w FIL A19,32K-18K	120	8	60W	800	100	E26	80	3200-1800	12
------------	-----	----------------------------	-----	---	-----	-----	-----	-----	----	-----------	----

DIMMABLE LED 8W BR30 LAMP, E26 BASE



FBR30D65GL1	BR30	Dim LED 8w FIL BR30,32K-18K	120	8	65W	650	81.3	E26	80	3200-1800	12
-------------	------	-----------------------------	-----	---	-----	-----	------	-----	----	-----------	----

DIMMABLE LED 5W CANDELABRA LAMP, E12 BASE



FB11D60FRGL1	B11	Dim LED 5w FIL B11,32K-18K	120	5	60W	500	100	E12	80	3200-1800	12
--------------	-----	----------------------------	-----	---	-----	-----	-----	-----	----	-----------	----



FF11D60FRGL1	F11	Dim LED 5w FIL F11,32K-18K	120	5	60W	500	100	E12	80	3200-1800	12
--------------	-----	----------------------------	-----	---	-----	-----	-----	-----	----	-----------	----

DIMMABLE LED 5W G25 LAMP, E26 BASE



FG25D60GL1	F11	Dim LED 5w FIL G25,32K-18K	120	5	40W	500	100	E26	80	3200-1800	12
------------	-----	----------------------------	-----	---	-----	-----	-----	-----	----	-----------	----

DIMMABLE LED 8W ST19 LAMP, E26 BASE



FST19D60GL1	ST19	Dim LED 8w FIL ST19,32K-18K	120	8	60W	500	62.5	E26	80	3200-1800	12
-------------	------	-----------------------------	-----	---	-----	-----	------	-----	----	-----------	----

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	CCT	CRI	Base	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----	-----	-----	------	---------------

10,000 HOUR NON DIMMABLE LED G4

NON DIMMABLE 1.5W G4 BASE



L1T3N1030K2	Non Dimmable 1.5W G4 - 3000K - 2 Pack	12	1.5	10W	120	80	3000K	80	G4	25
-------------	---------------------------------------	----	-----	-----	-----	----	-------	----	----	----

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lumens	LPW	CCT	Beam Angle	CRI	Case Quantity
-------------	------------------	---------	------------	--------------------	--------	-----	-----	------------	-----	---------------

NEW 25,000 HOUR ALLUSION LED 15W PAR38 WITH SMOOTH WARM DIMMING (REPLACES 90W)

L15P38DNFLA	15W PAR38 Narrow Flood	120	12.5	90W	975	78.0	3000K to 2000K	25	80	12
L15P38DFLA	15W PAR38 Flood	120	12.5	90W	975	78.0	3000K to 2000K	40	80	12



NEW 25,000 HOUR ALLUSION LED 15W PAR30 WITH SMOOTH WARM DIMMING (REPLACES 90W)

L15P30DNFLA	15W PAR30 Narrow Flood	120	12.5	90W	975	78.0	3000K to 2000K	25	80	12
L15P30DFLA	15W PAR30 Flood	120	12.5	90W	975	78.0	3000K to 2000K	40	80	12



NEW 25,000 HOUR ALLUSION LED 7W PAR20 WITH SMOOTH WARM DIMMING (REPLACES 50W)

L7P20DNFLA	7W PAR20 Narrow Flood	120	6.5	50W	525	80.8	3000K to 2000K	25	80	12
L7P20DFLA	7W PAR20 Flood	120	6.5	50W	525	80.8	3000K to 2000K	40	80	12



NEW 25,000 HOUR ALLUSION LED 7W MR16 WITH SMOOTH WARM DIMMING (REPLACES 50W)

L712VMR16DNFLA	7W MR16 Narrow Flood	120	6	50W	350	58.3	3000K to 1800K	20	80	12
----------------	----------------------	-----	---	-----	-----	------	----------------	----	----	----



NEW 30,000 HOUR ALLUSION LED 13W SL16 WITH SMOOTH WARM DIMMING

L15SL16D30A	13W SL16	120	13	-	1200	92.3	3000K to 2000K	110	80	6
-------------	----------	-----	----	---	------	------	----------------	-----	----	---



25,000 HOUR ALLUSION LED 10W 5/6" RECESSED DOWNLIGHTS WITH SMOOTH WARM DIMMING

LED10DR56DA	10W 5 5/8" Recessed Downlight	120	11	65W	1100	100	3000K to 2000K	120	80	6
-------------	-------------------------------	-----	----	-----	------	-----	----------------	-----	----	---



25,000 HOUR ALLUSION LED 10W BR30 WITH SMOOTH WARM DIMMING (REPLACES 65W)

LED10BR30DA	10W BR30	120	10	65W	675	67.5	3000K to 2000K	110	80	12
-------------	----------	-----	----	-----	-----	------	----------------	-----	----	----



25,000 HOUR ALLUSION LED 9W A LAMPS WITH SMOOTH WARM DIMMING

LED9A19DA	9W A19 A-Lamp	120	9	60W	650	72.2	2700K to 2000K	-	80	12
-----------	---------------	-----	---	-----	-----	------	----------------	---	----	----



25,000 HOUR ALLUSION LED 5W B11 DECO WITH SMOOTH WARM DIMMING

LED5E12B11DA	5W B11 Candelabra Blunt Tip	120	5	25W	300	60.0	2400K to 1900K	-	82	12
LED5E12B11DAF	5W B11 Candelabra Blunt Tip, Frosted	120	5	25W	300	60.0	2400K to 1900K	-	82	12



Item Number	Item Description	Voltage	Lamp Watts	Avg. System Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	CRI	Base Type	Case Quantity
-------------	------------------	---------	------------	-------------------	--------------------	--------	-----------------	-----	-----	-----------	---------------

50,000 HOUR DIMMABLE LED PL LAMPS

9W DIMMABLE VERTICAL BR30 PL LAMP



L9PLVD5027K	9W Dimmable Vertical BR30 PL - 2700K	120-277v, 347v	9	13.1	13-18	1050	116.7	2700K	80	G24q / GX24q	12
L9PLVD5030K	9W Dimmable Vertical BR30 PL - 3000K	120-277v, 347v	9	13.1	13-18	1100	122.2	3000K	80	G24q / GX24q	12
L9PLVD5041K	9W Dimmable Vertical BR30 PL - 4100K	120-277v, 347v	9	13.1	13-18	1150	127.8	4100K	80	G24q / GX24q	12
L9PLVD5050K	9W Dimmable Vertical BR30 PL - 5000K	120-277v, 347v	9	13.1	13-18	1175	130.6	5000K	80	G24q / GX24q	12

17W DIMMABLE VERTICAL BR30 PL LAMP



L17PLVD5027K	17W Dimmable Vertical BR30 PL - 2700K	120-277v, 347v	17	21.4	26	1700	100.0	2700K	80	G24q / GX24q	12
L17PLVD5030K	17W Dimmable Vertical BR30 PL - 3000K	120-277v, 347v	17	21.4	26	1800	105.8	3000K	80	G24q / GX24q	12
L17PLVD5041K	17W Dimmable Vertical BR30 PL - 4100K	120-277v, 347v	17	21.4	26	1900	111.7	4100K	80	G24q / GX24q	12
L17PLVD5050K	17W Dimmable Vertical BR30 PL - 5000K	120-277v, 347v	17	21.4	26	1950	114.7	5000K	80	G24q / GX24q	12

19W DIMMABLE VERTICAL BR40 PL LAMP



L19PLVD5027K	19W Dimmable Vertical BR40 PL - 2700K	120-277v, 347v	19	25.6	26-42	2350	123.7	2700K	80	G24q / GX24q	12
L19PLVD5030K	19W Dimmable Vertical BR40 PL - 4000K	120-277v, 347v	19	25.6	26-42	2400	126.3	3000K	80	G24q / GX24q	12
L19PLVD5041K	19W Dimmable Vertical BR40 PL - 4100K	120-277v, 347v	19	25.6	26-42	2450	128.9	4100K	80	G24q / GX24q	12
L19PLVD5050K	19W Dimmable Vertical BR40 PL - 5000K	120-277v, 347v	19	25.6	26-42	2480	130.5	5000K	80	G24q / GX24q	12

Item Number	Item Description	Voltage	Lamp Watts	Avg. System Watts	Wattage Equivalent	Lumens	Lumens Per Watt	CCT	CRI	Base Type	Case Quantity
-------------	------------------	---------	------------	-------------------	--------------------	--------	-----------------	-----	-----	-----------	---------------

20,000 HOUR NON DIMMABLE LED PL LAMPS
10.5W Non Dimmable Quad PL Lamp



LPLUD2027K	10.5W Non Dimmable Universal Quad PL - 2700K	120-277V	10.5	13.7	13-18	950	90.5	2700K	80	G24q / GX24q	12
LPLUD2030K	10.5W Non Dimmable Universal Quad PL - 3000K	120-277V	10.5	13.7	13-18	950	90.5	3000K	80	G24q / GX24q	12
LPLUD2035K	10.5W Non Dimmable Universal Quad PL - 3500K	120-277V	10.5	13.7	13-18	950	90.5	3500K	80	G24q / GX24q	12
LPLUD2041K	10.5W Non Dimmable Universal Quad PL - 4100K	120-277V	10.5	13.7	13-18	950	90.5	4100K	80	G24q / GX24q	12
LPLUD2050K	10.5W Non Dimmable Universal Quad PL - 5000K	120-277V	10.5	13.7	13-18	950	90.5	5000K	80	G24q / GX24q	12

20,000 HOUR NON DIMMABLE LED PL 3U LAMPS
15W Non Dimmable PL 3U Lamp



LPLU26A2527K	15W Non Dimmable Universal 3U PL - 2700K	120-277V	15	-	18-26	1350	90	2700K	80	G24q / GX24q	12
LPLU26A2530K	15W Non Dimmable Universal 3U PL - 3000K	120-277V	15	-	18-26	1350	90	3000K	80	G24q / GX24q	12
LPLU26A2535K	15W Non Dimmable Universal 3U PL - 3500K	120-277V	15	-	18-26	1350	90	3500K	80	G24q / GX24q	12
LPLU26A2541K	15W Non Dimmable Universal 3U PL - 4100K	120-277V	15	-	18-26	1350	90	4100K	80	G24q / GX24q	12
LPLU26A2550K	15W Non Dimmable Universal 3U PL - 5000K	120-277V	15	-	18-26	1350	90	5000K	80	G24q / GX24q	12

16W Non Dimmable PL 3U Lamp

LPLU42A2527K	16W Non Dimmable Universal 3U PL - 2700K	120-277V	16	-	32-42	1500	93.8	2700K	80	G24q / GX24q	12
LPLU42A2530K	16W Non Dimmable Universal 3U PL - 3000K	120-277V	16	-	32-42	1500	93.8	3000K	80	G24q / GX24q	12
LPLU42A2535K	16W Non Dimmable Universal 3U PL - 3500K	120-277V	16	-	32-42	1500	93.8	3500K	80	G24q / GX24q	12
LPLU42A2541K	16W Non Dimmable Universal 3U PL - 4100K	120-277V	16	-	32-42	1500	93.8	4100K	80	G24q / GX24q	12
LPLU42A2550K	16W Non Dimmable Universal 3U PL - 5000K	120-277V	16	-	32-42	1500	93.8	5000K	80	G24q / GX24q	12

20,000 HOUR NON DIMMABLE LED PL 2U LAMPS
10W Non Dimmable PL 2U Lamp



LPL218B2527K	10W Non Dimmable Universal 2U PL - 2700K	120-277V	8	-	13-18-26	975	121.9	2700K	80	G24d / GX24d G24q / GX24q	12
LPL218B2530K	10W Non Dimmable Universal 2U PL - 3000K	120-277V	8	-	13-18-26	1000	125	3000K	80	G24d / GX24d G24q / GX24q	12
LPL218B2535K	10W Non Dimmable Universal 2U PL - 3500K	120-277V	8	-	13-18-26	1025	128.1	3500K	80	G24d / GX24d G24q / GX24q	12
LPL218B2541K	10W Non Dimmable Universal 2U PL - 4100K	120-277V	8	-	13-18-26	1050	131.3	4100K	80	G24d / GX24d G24q / GX24q	12
LPL218B2550K	10W Non Dimmable Universal 2U PL - 5000K	120-277V	8	-	13-18-26	1050	131.3	5000K	80	G24d / GX24d G24q / GX24q	12



Item Number

Item Description

Voltage

Lamp Watts

Wattage Equivalent

Lamp Lumens

LPW

Color Temperature

Base

CRI

Beam Angle

Power Factor

Case Quantity

25,000 HOUR LED 120-277V LAMPS

LED 18W LED NON DIMMABLE A23 125W EQUIVALENT



L125A23N25UNV27K	LED 125W A23 UNV, E26 Base - 2700K	120-277v	18	125	2000	111.1	2700	E26	80	-	≥0.9	48
L125A23N25UNV30K	LED 125W A23 UNV, E26 Base - 3000K	120-277v	18	125	2000	111.1	3000	E26	80	-	≥0.9	48
L125A23N25UNV40K	LED 125W A23 UNV, E26 Base - 4000K	120-277v	18	125	2100	116.7	4000	E26	80	-	≥0.9	48
L125A23N25UNV50K	LED 125W A23 UNV, E26 Base - 5000K	120-277v	18	125	2200	122.2	2700	E26	80	-	≥0.9	48

LED 14W LED NON DIMMABLE A21 100W EQUIVALENT



L100A21N25UNV27K	LED 100W A21 UNV, E26 Base - 2700K	120-277v	14	100	1600	114.3	2700	E26	80	-	≥0.7	48
L100A21N25UNV30K	LED 100W A21 UNV, E26 Base - 3000K	120-277v	14	100	1625	116.1	3000	E26	80	-	≥0.7	48
L100A21N25UNV40K	LED 100W A21 UNV, E26 Base - 4000K	120-277v	14	100	1650	117.9	4000	E26	80	-	≥0.7	48
L100A21N25UNV50K	LED 100W A21 UNV, E26 Base - 5000K	120-277v	14	100	1650	117.9	5000	E26	80	-	≥0.7	48

LED 7.5W LED NON DIMMABLE A19 60W EQUIVALENT



L60A19N25UNV27K	LED 60W A19 UNV, E26 Base - 2700K	120-277v	7.5	60	800	106.7	2700	E26	80	-	≥0.5	48
L60A19N25UNV30K	LED 60W A19 UNV, E26 Base - 3000K	120-277v	7.5	60	800	106.7	3000	E26	80	-	≥0.5	48
L60A19N25UNV40K	LED 60W A19 UNV, E26 Base - 4000K	120-277v	7.5	60	850	113.3	4000	E26	80	-	≥0.5	48
L60A19N25UNV50K	LED 60W A19 UNV, E26 Base - 5000K	120-277v	7.5	60	875	116.7	5000	E26	80	-	≥0.5	48

LED 9.5W LED NON DIMMABLE BR30 65W EQUIVALENT



L65BR30N25UNV27K	LED 65W BR30 UNV, E26 Base - 2700K	120-277v	9.5	65	900	94.7	2700	E26	80	-	≥0.7	12
L65BR30N25UNV30K	LED 65W BR30 UNV, E26 Base - 3000K	120-277v	9.5	65	900	94.7	3000	E26	80	-	≥0.7	12
L65BR30N25UNV40K	LED 65W BR30 UNV, E26 Base - 4000K	120-277v	9.5	65	950	100	4000	E26	80	-	≥0.7	12
L65BR30N25UNV50K	LED 65W BR30 UNV, E26 Base - 5000K	120-277v	9.5	65	1000	105.3	5000	E26	80	-	≥0.7	12

LED 13W LED NON DIMMABLE BR30 100W EQUIVALENT



L100BR30N25UNV27K	LED 100W BR30 UNV, E26 Base - 2700K	120-277v	13	100	1400	107.7	2700	E26	80	-	≥0.7	12
L100BR30N25UNV30K	LED 100W BR30 UNV, E26 Base - 3000K	120-277v	13	100	1450	111.5	3000	E26	80	-	≥0.7	12
L100BR30N25UNV40K	LED 100W BR30 UNV, E26 Base - 4000K	120-277v	13	100	1500	115.4	4000	E26	80	-	≥0.7	12
L100BR30N25UNV50K	LED 100W BR30 UNV, E26 Base - 5000K	120-277v	13	100	1550	119.2	5000	E26	80	-	≥0.7	12

LED 12.5W LED NON DIMMABLE PAR38 120W EQUIVALENT



L100P38N25UNV27KFL	LED 100W PAR38 UNV, E26 Base - 2700K Flood	120-277v	12.5	120	1100	88	2700	E26	80	-	≥0.7	12
L100P38N25UNV30KFL	LED 100W PAR38 UNV, E26 Base - 3000K Flood	120-277v	12.5	120	1100	88	3000	E26	80	-	≥0.7	12
L100P38N25UNV40KFL	LED 100W PAR38 UNV, E26 Base - 4000K Flood	120-277v	12.5	120	1150	92	4000	E26	80	-	≥0.7	12
L100P38N25UNV50KFL	LED 100W PAR38 UNV, E26 Base - 5000K Flood	120-277v	12.5	120	1200	96	5000	E26	80	-	≥0.7	12
L100P38N25UNV27KNFL	LED 100W PAR38 UNV, E26 Base - 2700K Narrow Flood	120-277v	12.5	120	1100	88	2700	E26	80	-	≥0.7	12
L100P38N25UNV30KNFL	LED 100W PAR38 UNV, E26 Base - 3000K Narrow Flood	120-277v	12.5	120	1100	88	3000	E26	80	-	≥0.7	12
L100P38N25UNV40KNFL	LED 100W PAR38 UNV, E26 Base - 4000K Narrow Flood	120-277v	12.5	120	1150	92	4000	E26	80	-	≥0.7	12
L100P38N25UNV50KNFL	LED 100W PAR38 UNV, E26 Base - 5000K Narrow Flood	120-277v	12.5	120	1200	96	5000	E26	80	-	≥0.7	12

Item Number	Item Description	Voltage	Lamp Watts	Wattage Equivalent	Lamp Lumens	LPW	Color Temperature	CRI	Beam Angle	Base	Case Quantity
-------------	------------------	---------	------------	--------------------	-------------	-----	-------------------	-----	------------	------	---------------

30,000 HOUR STARLIGHT SERIES LED LAMPS
9W SL13 STARLIGHT, 65W EQUIVALENT

L9SL13D3030K	LED 9W Dimmable - 30K	120V	9	65	950	105.6	3000	80	110°	E26	12	
L9SL13D3040K	LED 9W Dimmable - 40K	120V	9	65	1000	111.1	4000	80	110°	E26	12	
L9SL13D3050K	LED 9W Dimmable - 50K	120V	9	65	1000	111.1	5000	80	110°	E26	12	

15W SL16 STARLIGHT, 100W EQUIVALENT

L15SL16D3030K	LED 15W Dimmable - 30K	120V	15	100	1625	108.3	3000	80	110°	E26	12	
L15SL16D3040K	LED 15W Dimmable - 40K	120V	15	100	1625	108.3	4000	80	110°	E26	12	
L15SL16D3050K	LED 15W Dimmable - 50K	120V	15	100	1625	108.3	5000	80	110°	E26	12	

19W SL19 STARLIGHT, 140W EQUIVALENT

L19SL19D3030K	LED 19W Dimmable - 30K	120V	19	140	2100	110.5	3000	80	110°	E26	12	
L19SL19D3040K	LED 19W Dimmable - 40K	120V	19	140	2250	118.4	4000	80	110°	E26	12	
L19SL19D3050K	LED 19W Dimmable - 50K	120V	19	140	2250	118.4	5000	80	110°	E26	12	

22W SL22 STARLIGHT, 140W EQUIVALENT

L22SL22D3030K	LED 22W Dimmable - 30K	120V	22	160	2350	106.8	3000	80	110°	E26	12	
L22SL22D3040K	LED 22W Dimmable - 40K	120V	22	160	2450	111.4	4000	80	110°	E26	12	
L22SL22D3050K	LED 22W Dimmable - 50K	120V	22	160	2450	111.4	5000	80	110°	E26	12	

25W SL122 STARLIGHT, 200W EQUIVALENT

L25SL22HD3030K	LED 25W Dimmable - 30K HL	120V	25	200	3100	124	3000	80	110°	E26	12	
L25SL22HD3040K	LED 25W Dimmable - 40K HL	120V	25	200	3100	124	4000	80	110°	E26	12	

Black, silver and custom colors are available by special order. All models are available in the following colors. To order, add the color code to the end of the model number (i.e., L15SL16D3030KRED)

B	Black
RED	Red
GRN	Green
BLU	Blue

Matching Pendant Mounts are also available:

555PMB	Pendant Mount Black
555PMWHT	Pendant Mount White
555PMRED	Pendant Mount Red
555PMGRN	Pendant Mount Green
555PMBLU	Pendant Mount Blue





Item Number	Item Description	Voltage	Lamp Watts	Metal Halide Comparison	Lamp Lumens	LPW	Color Temperature	Base	CRI	Case Quantity
-------------	------------------	---------	------------	-------------------------	-------------	-----	-------------------	------	-----	---------------

50,000 HOUR LED HID REPLACEMENT LAMPS

LED 20W METAL HALIDE REPLACEMENT LAMP, E26 BASE NEW



LHID07040	LED 20W 40K HID Replacement Lamp, E26 Base	120-277v	20	100	3000	150	4000	E26	80	6

LHID07050	LED 20W 50K HID Replacement Lamp, E26 Base	120-277v	20	100	3000	150	5000	E26	80	6

LED 25W METAL HALIDE REPLACEMENT LAMP, E26 BASE NEW



LHID10040	LED 25W 40K HID Replacement Lamp, E26 Base	120-277v	25	150	3750	150	4000	E26	80	6

LHID10050	LED 25W 50K HID Replacement Lamp, E26 Base	120-277v	25	150	3750	150	5000	E26	80	6

LED 40W METAL HALIDE REPLACEMENT LAMP, E26 BASE NEW



LHID15040	LED 40W 40K HID Replacement Lamp, E26 Base	120-277v	40	175	5850	146.3	4000	E26	80	6

LHID15050	LED 40W 50K HID Replacement Lamp, E26 Base	120-277v	40	175	5850	146.3	5000	E26	80	6

LED 65W METAL HALIDE REPLACEMENT LAMP, EX39 BASE NEW



LHID17540	LED 65W 40K HID Replacement Lamp, EX39 Base	120-277v	65	250	9900	152.3	4000	EX39	80	6

LHID17550	LED 65W 50K HID Replacement Lamp, EX39 Base	120-277v	65	250	9900	152.3	5000	EX39	80	6

LED 90W METAL HALIDE REPLACEMENT LAMP, EX39 BASE NEW



LHID25040	LED 90W 40K HID Replacement Lamp, EX39 Base	120-277v	90	400	13600	151.1	4000	EX39	80	6

LHID25050	LED 90W 50K HID Replacement Lamp, EX39 Base	120-277v	90	400	13600	151.1	5000	EX39	80	6

Item Number	Item Description	Voltage	Lamp Watts	Metal Halide Comparison	Lamp Lumens	LPW	Color Temperature	Base	CRI	Case Quantity
-------------	------------------	---------	------------	-------------------------	-------------	-----	-------------------	------	-----	---------------

50,000 HOUR LED HID REPLACEMENT LAMPS(CONTINUED)
LED 19W METAL HALIDE REPLACEMENT LAMP, E26 BASE

L19MHE265040K	LED 19W 40K HID Replacement Lamp, E26 Base	120-277v	19	70	2470	130	4000	E26	80	16
L19MHE265050K	LED 19W 50K HID Replacement Lamp, E26 Base	120-277v	19	70	2565	135	5000	E26	80	16



LED 24W METAL HALIDE REPLACEMENT LAMP, E26 BASE

L24MHE265040K	LED 24W 40K HID Replacement Lamp, E26 Base	120-277v	24	100	3120	130	4000	E26	80	16
L24MHE265050K	LED 24W 50K HID Replacement Lamp, E26 Base	120-277v	24	100	3240	135	5000	E26	80	16



LED 45W METAL HALIDE REPLACEMENT LAMP, E26 BASE

L45MHE265040K	LED 45W 40K HID Replacement Lamp, E26 Base	120-277v	45	175	5850	130	4000	E26	80	16
L45MHE265050K	LED 45W 50K HID Replacement Lamp, E26 Base	120-277v	45	175	6075	135	5000	E26	80	16



LED 45W METAL HALIDE REPLACEMENT LAMP, EX39 BASE

L45MHX395040K	LED 45W 40K HID Replacement Lamp, EX39 Base	120-277v	45	175	5850	130	4000	EX39	80	6
L45MHX395050K	LED 45W 50K HID Replacement Lamp, EX39 Base	120-277v	45	175	6075	135	5000	EX39	80	6



LED 80W METAL HALIDE REPLACEMENT LAMP, EX39 BASE

L80MHX395040K	LED 80W 40K HID Replacement Lamp, EX39 Base	120-277v	80	250	10400	130	4000	EX39	80	16
L80MHX395050K	LED 80W 50K HID Replacement Lamp, EX39 Base	120-277v	80	250	10800	135	5000	EX39	80	16



LED 100W METAL HALIDE REPLACEMENT LAMP, EX39 BASE

L100MHX395040K	LED 100W 40K HID Replacement Lamp, EX39 Base	120-277v	100	400	13500	135	4000	EX39	80	6
L100MHX395050K	LED 100W 50K HID Replacement Lamp, EX39 Base	120-277v	100	400	14000	140	5000	EX39	80	6



Item Number

Item Description

Lamp Wattage

Voltage

Fluorescent Equivalency

Lumens

Lumens Per Watt

Base

CCT

CRI

Master Pack

50,000 HOUR LED LIBERAT8™ BALLAST BYPASS TUBES
15W T8 BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G13 BASE


LT813B230K	LED 15W Ballast Bypass 4 Foot T8 - 30K	13.5	120-277v	32	1700	125.9	G13	3000	80	25
LT813B235K	LED 15W Ballast Bypass 4 Foot T8 - 35K	13.5	120-277v	32	1700	125.9	G13	3500	80	25
LT813B241K	LED 15W Ballast Bypass 4 Foot T8 - 41K	13.5	120-277v	32	1800	133.3	G13	4100	80	25
LT813B250K	LED 15W Ballast Bypass 4 Foot T8 - 50K	13.5	120-277v	32	1800	133.3	G13	5000	80	25

13.5W T8 BALLAST BYPASS - 4 FOOT SHATTERPROOF PET COATED GLASS TUBES, G13 BASE


L13T8BY5030K	LED 13.5W Ballast Bypass 4 Foot T8 - 30K	13.5	120-277v	32	1700	133.3	G13	3000	80	25
L13T8BY5035K	LED 13.5W Ballast Bypass 4 Foot T8 - 35K	13.5	120-277v	32	1700	133.3	G13	3500	80	25
L13T8BY5041K	LED 13.5W Ballast Bypass 4 Foot T8 - 41K	13.5	120-277v	32	1800	140.7	G13	4100	80	25
L13T8BY5050K	LED 13.5W Ballast Bypass 4 Foot T8 - 50K	13.5	120-277v	32	1800	148.1	G13	5000	80	25

12W T8 BALLAST BYPASS - 3 FOOT SHATTERPROOF PET COATED GLASS TUBES, G13 BASE

L12T8BY5030K	LED 12W Ballast Bypass 3 Foot T8 - 30K	12	120-277v	25	1400	100	G13	3000	80	25
L12T8BY5035K	LED 12W Ballast Bypass 3 Foot T8 - 35K	12	120-277v	25	1400	100	G13	3500	80	25
L12T8BY5041K	LED 12W Ballast Bypass 3 Foot T8 - 41K	12	120-277v	25	1450	100	G13	4100	80	25
L12T8BY5050K	LED 12W Ballast Bypass 3 Foot T8 - 50K	12	120-277v	25	1450	100	G13	5000	80	25

9W T8 BALLAST BYPASS - 2 FOOT SHATTERPROOF PET COATED GLASS TUBES, G13 BASE

L9T8BY5030K	LED 9W Ballast Bypass 2 Foot T8 - 30K	9	120-277v	17	1100	125	G13	3000	80	25
L9T8BY5035K	LED 9W Ballast Bypass 2 Foot T8 - 35K	9	120-277v	17	1100	125	G13	3500	80	25
L9T8BY5041K	LED 9W Ballast Bypass 2 Foot T8 - 41K	9	120-277v	17	1150	133.3	G13	4100	80	25
L9T8BY5050K	LED 9W Ballast Bypass 2 Foot T8 - 50K	9	120-277v	17	1150	138.8	G13	5000	80	25

43W T8 BALLAST BYPASS - 8 FOOT GLASS TUBES, R17D BASE


LT8R43B230KBP	LED 43W Ballast Bypass 8 Foot T8, R17d Base - 30K	43	120-277v	75	5100	118.6	R17d	3000	80	10
LT8R43B235KBP	LED 43W Ballast Bypass 8 Foot T8, R17d Base - 35K	43	120-277v	75	5500	127.9	R17d	3500	80	10
LT8R43B240KBP	LED 43W Ballast Bypass 8 Foot T8, R17d Base - 40K	43	120-277v	75	5500	127.9	R17d	4100	80	10
LT8R43B250KBP	LED 43W Ballast Bypass 8 Foot T8, R17d Base - 50K	43	120-277v	75	5500	127.9	R17d	5000	80	10

43W T8 BALLAST BYPASS - 8 FOOT GLASS TUBES, FA8 BASE


LT8F43B230KBP	LED 43W Ballast Bypass 8 Foot T8, Fa8 Base - 30K	43	120-277v	75	5100	118.6	Fa8	3000	80	10
LT8F43B235KBP	LED 43W Ballast Bypass 8 Foot T8, Fa8 Base - 35K	43	120-277v	75	5500	127.9	Fa8	3500	80	10
LT8F43B240KBP	LED 43W Ballast Bypass 8 Foot T8, Fa8 Base - 40K	43	120-277v	75	5500	127.9	Fa8	4000	80	10
LT8F43B250KBP	LED 43W Ballast Bypass 8 Foot T8, Fa8 Base - 50K	43	120-277v	75	5500	127.9	Fa8	5000	80	10

15.5W T8 BALLAST BYPASS - 2 FOOT SHATTERPROOF U-BEND PLASTIC TUBES, G13 BASE


LPT8U615B230K	LED 15.5W Ballast Bypass 2 Foot U-Bend T8 - 30K	15.5	120-277v	32	2000	129	G13	3000	80	25
LPT8U615B235K	LED 15.5W Ballast Bypass 2 Foot U-Bend T8 - 35K	15.5	120-277v	32	2000	129	G13	3500	80	25
LPT8U615B241K	LED 15.5W Ballast Bypass 2 Foot U-Bend T8 - 41K	15.5	120-277v	32	2100	135.5	G13	4100	80	25
LPT8U615B250K	LED 15.5W Ballast Bypass 2 Foot U-Bend T8 - 50K	15.5	120-277v	32	2100	135.5	G13	5000	80	25

50

LiberT8 T8 lamps are double ended for safety.


5 YEAR WARRANTY

 Consult www.tcpi.com for warranty information.

Item Number	Item Description	Lamp Wattage	Voltage	Fluorescent Equivalency	Lumens	Lumens Per Watt	Base	CCT	CRI	Master Pack
-------------	------------------	--------------	---------	-------------------------	--------	-----------------	------	-----	-----	-------------

50,000 HOUR LED LIBERAT8™ BALLAST BYPASS TUBES
24.5W T8 HIGH OUTPUT BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G13 BASE

LPT824B230K	LED 24.5W High Output Ballast Bypass 4 Foot T8 - 30K	24.5	120-277v	32	2850	116.3	G13	3000	80	25
LPT824B235K	LED 24.5W High Output Ballast Bypass 4 Foot T8 - 35K	24.5	120-277v	32	2850	116.3	G13	3500	80	25
LPT824B241K	LED 24.5W High Output Ballast Bypass 4 Foot T8 - 41K	24.5	120-277v	32	3000	122.4	G13	4100	80	25
LPT824B250K	LED 24.5W High Output Ballast Bypass 4 Foot T8 - 50K	24.5	120-277v	32	3000	122.4	G13	5000	80	25

18.5W T8 HIGH OUTPUT BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G13 BASE

LPT818B230K	LED 18.5W Ballast Bypass 4 Foot T8 - 30K	18.5	120-277v	32	2450	132.4	G13	3000	80	25
LPT818B235K	LED 18.5W Ballast Bypass 4 Foot T8 - 35K	18.5	120-277v	32	2450	132.4	G13	3500	80	25
LPT818B241K	LED 18.5W Ballast Bypass 4 Foot T8 - 41K	18.5	120-277v	32	2600	140.5	G13	4100	80	25
LPT818B250K	LED 18.5W Ballast Bypass 4 Foot T8 - 50K	18.5	120-277v	32	2600	140.5	G13	5000	80	25

15W T8 HIGH OUTPUT BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G13 BASE COMING SOON

LPT815B230K	LED 15W High Output Ballast Bypass 4 Foot T8 - 30K	15	120-277v	32	2100	140	G13	3000	80	25
LPT815B235K	LED 15W High Output Ballast Bypass 4 Foot T8 - 35K	15	120-277v	32	2100	140	G13	3500	80	25
LPT815B241K	LED 15W High Output Ballast Bypass 4 Foot T8 - 41K	15	120-277v	32	2200	146.7	G13	4100	80	25
LPT815B250K	LED 15W High Output Ballast Bypass 4 Foot T8 - 50K	15	120-277v	32	2200	146.7	G13	5000	80	25

50,000 HOUR LED LIBERAT5™ BALLAST BYPASS TUBES
12W T5 HIGH OUTPUT BALLAST BYPASS - 2 FOOT ALL GLASS TUBES, G5 BASE

LT5H012B130K	LED 12W High Output Ballast Bypass 2 Foot T5 - 30K	12	120-277v	24	1450	120.8	G5	3000	80	25
LT5H012B135K	LED 12W High Output Ballast Bypass 2 Foot T5 - 35K	12	120-277v	24	1450	120.8	G5	3500	80	25
LT5H012B141K	LED 12W High Output Ballast Bypass 2 Foot T5 - 41K	12	120-277v	24	1450	120.8	G5	4100	80	25
LT5H012B150K	LED 12W High Output Ballast Bypass 2 Foot T5 - 50K	12	120-277v	24	1450	120.8	G5	5000	80	25

16W T5 HIGH OUTPUT BALLAST BYPASS - 3 FOOT ALL GLASS TUBES, G5 BASE

LT5H016B130K	LED 16W High Output Ballast Bypass 3 Foot T5 - 30K	16	120-277v	39	1850	115.6	G5	3000	80	25
LT5H016B135K	LED 16W High Output Ballast Bypass 3 Foot T5 - 35K	16	120-277v	39	1850	115.6	G5	3500	80	25
LT5H016B141K	LED 16W High Output Ballast Bypass 3 Foot T5 - 41K	16	120-277v	39	1850	115.6	G5	4100	80	25
LT5H016B150K	LED 16W High Output Ballast Bypass 3 Foot T5 - 50K	16	120-277v	39	1850	115.6	G5	5000	80	25

25W T5 HIGH OUTPUT BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G5 BASE (DLC SEARCH "LT5H025B1XXK")

LT5H025B130K	LED 25W High Output Ballast Bypass 4 Foot T5 - 30K	25	120-277v	54	3200	128	G5	3000	80	25
LT5H025B135K	LED 25W High Output Ballast Bypass 4 Foot T5 - 35K	25	120-277v	54	3200	128	G5	3500	80	25
LT5H025B141K	LED 25W High Output Ballast Bypass 4 Foot T5 - 41K	25	120-277v	54	3200	128	G5	4100	80	25
LT5H025B150K	LED 25W High Output Ballast Bypass 4 Foot T5 - 50K	25	120-277v	54	3200	128	G5	5000	80	25





Item Number	Item Description	Lamp Wattage	Voltage	Fluorescent Equivalency	Lumens	Lumens Per Watt	Base	CCT	CRI	Master Pack
-------------	------------------	--------------	---------	-------------------------	--------	-----------------	------	-----	-----	-------------

50,000 HOUR LED LIBERAT5™ BALLAST BYPASS TUBES (CONTINUED)

9W T5 BALLAST BYPASS - 2 FOOT ALL GLASS TUBES, G5 BASE



LT5HE09B130K	LED 9W Ballast Bypass 2 Foot T8 - 30K	9	120-277v	14	1150	127.7	G5	3000	80	25
LT5HE09B135K	LED 9W Ballast Bypass 2 Foot T8 - 35K	9	120-277v	14	1150	127.7	G5	3500	80	25
LT5HE09B141K	LED 9W Ballast Bypass 2 Foot T8 - 41K	9	120-277v	14	1150	127.7	G5	4100	80	25
LT5HE09B150K	LED 9W Ballast Bypass 2 Foot T8 - 50K	9	120-277v	14	1150	127.7	G5	5000	80	25

12W T5 BALLAST BYPASS - 3 FOOT ALL GLASS TUBES, G5 BASE

LT5HE12B130K	LED 12W Ballast Bypass 3 Foot T8 - 30K	12	120-277v	21	1350	112.5	G5	3000	80	25
LT5HE12B135K	LED 12W Ballast Bypass 3 Foot T8 - 35K	12	120-277v	21	1350	112.5	G5	3500	80	25
LT5HE12B141K	LED 12W Ballast Bypass 3 Foot T8 - 41K	12	120-277v	21	1350	112.5	G5	4100	80	25
LT5HE12B150K	LED 12W Ballast Bypass 3 Foot T8 - 50K	12	120-277v	21	1350	112.5	G5	5000	80	25

13W T5 BALLAST BYPASS - 4 FOOT ALL GLASS TUBES, G5 BASE (DLC SEARCH "LT5HE13B1XXK")

LT5HE13B130K	LED 13W Ballast Bypass 4 Foot T8 - 30K	13	120-277v	28	1650	126.9	G5	3000	80	25
LT5HE13B135K	LED 13W Ballast Bypass 4 Foot T8 - 35K	13	120-277v	28	1650	126.9	G5	3500	80	25
LT5HE13B141K	LED 13W Ballast Bypass 4 Foot T8 - 41K	13	120-277v	28	1650	126.9	G5	4100	80	25
LT5HE13B150K	LED 13W Ballast Bypass 4 Foot T8 - 50K	13	120-277v	28	1650	126.9	G5	5000	80	25



Item Number	Item Description	Bare Lamp Wattage	Equivalent Wattage	LBF System Wattage	NBF System Wattage	HBF System Wattage	LBF Lamp Lumens	NBF Lamp Lumens	HBF Lamp Lumens	Base	CCT	CRI
-------------	------------------	-------------------	--------------------	--------------------	--------------------	--------------------	-----------------	-----------------	-----------------	------	-----	-----

50,000 HOUR LED DIRECT8™ INSTANT START COMPATIBLE

12W LED T8 INSTANT START - 4 FOOT GLASS TUBES (DLC SEARCH "L12T8D50")

L12T8D5030K	LED 12W IS/RS 4 Ft T8 - 30K	12	32	13	14.9	21.5	1260	1700	2280	G13	3000	80
L12T8D5035K	LED 12W IS/RS 4 Ft T8 - 35K	12	32	13	14.9	21.5	1300	1750	2340	G13	3500	80
L12T8D5041K	LED 12W IS/RS 4 Ft T8 - 41K	12	32	13	14.9	21.5	1340	1800	2400	G13	4100	80
L12T8D5050K	LED 12W IS/RS 4 Ft T8 - 50K	12	32	13	14.9	21.5	1380	1850	2480	G13	5000	80

18W LED T8 INSTANT START - 4 FOOT GLASS TUBES (DLC SEARCH "T80433")

LT818A30K	LED 18W IS/RS 4 Foot T8 - 30K	15	32	15.4	17.5	25.7	2000	2300	3380	G13	3000	80
LT818A35K	LED 18W IS/RS 4 Foot T8 - 35K	15	32	15.4	17.5	25.7	2050	2350	3450	G13	3500	80
LT818A41K	LED 18W IS/RS 4 Foot T8 - 41K	15	32	15.4	17.5	25.7	2050	2350	3450	G13	4100	80
LT818A50K	LED 18W IS/RS 4 Foot T8 - 50K	15	32	15.4	17.5	25.7	2100	2400	3525	G13	5000	80

12W LED HIGH CRI T8 INSTANT START - 4 FOOT GLASS TUBES

L12T8D5027K95	LED 12W IS/RS 4 Ft T8 - 27K 95	12	32	13	14.9	21.5	1300	1750	2340	G13	2700	90
L12T8D5030K95	LED 12W IS/RS 4 Ft T8 - 30K 95	12	32	13	14.9	21.5	1340	1800	2400	G13	3000	90
L12T8D5035K95	LED 12W IS/RS 4 Ft T8 - 35K 95	12	32	13	14.9	21.5	1340	1800	2400	G13	3500	90
L12T8D5041K95	LED 12W IS/RS 4 Ft T8 - 41K 95	12	32	13	14.9	21.5	1360	1825	2425	G13	4100	90
L12T8D5050K95	LED 12W IS/RS 4 Ft T8 - 50K 95	12	32	13	14.9	21.5	1380	1850	2480	G13	5000	90
T80414095P	LED 12W IS/RS 4 Ft T8 - 41K95	12	32	12.5	15	21.5	1050	1400	1860	G13	4100	90

Item Number	Item Description	Bare Lamp Wattage	Equivalent Wattage	LBF System Wattage	NBF System Wattage	HBF System Wattage	LBF Lamp Lumens	NBF Lamp Lumens	HBF Lamp Lumens	Base	CCT	CRI
-------------	------------------	-------------------	--------------------	--------------------	--------------------	--------------------	-----------------	-----------------	-----------------	------	-----	-----

50,000 HOUR LED DIRECT8™ INSTANT START COMPATIBLE CONTINUED

11W T8 HIGH EFFICACY INSTANT START - 4 FOOT GLASS TUBES

L11T8D5030K	LED 11W High Efficacy IS/RS 4 Ft T8 - 30K	11	32	11.3	13.6	18.5	1340	1800	2410	G13	3000	80
L11T8D5035K	LED 11W High Efficacy IS/RS 4 Ft T8 - 35K	11	32	11.3	13.6	18.5	1380	1850	2480	G13	3500	80
L11T8D5041K	LED 11W High Efficacy IS/RS 4 Ft T8 - 41K	11	32	11.3	13.6	18.5	1410	1900	2540	G13	4100	80
L11T8D5050K	LED 11W High Efficacy IS/RS 4 Ft T8 - 50K	11	32	11.3	13.6	18.5	1450	1950	2610	G13	5000	80

10W T8 HIGH EFFICACY INSTANT START - 4 FOOT GLASS TUBES BULK PACKS (DLC SEARCH "T80430")

T804304EBP	LED 13W IS/RS 4 Ft T8 - 41K Bulk Pack	10	32	11.6	13.2	19.4	1625	1850	2700	G13	4100	80
------------	---------------------------------------	----	----	------	------	------	------	------	------	-----	------	----

11W T8 HIGH EFFICACY INSTANT START - 3 FOOT GLASS TUBES

L11T83D5030K	LED 11W IS/RS 3 Ft T8 - 30K	11	25	11.6	13.5	19.2	1040	1400	1870	G13	3000	80
L11T83D5035K	LED 11W IS/RS 3 Ft T8 - 35K	11	25	11.6	13.5	19.2	1080	1450	1940	G13	3500	80
L11T83D5041K	LED 11W IS/RS 3 Ft T8 - 41K	11	25	11.6	13.5	19.2	1110	1500	2000	G13	4100	80
L11T83D5050K	LED 11W IS/RS 3 Ft T8 - 50K	11	25	11.6	13.5	19.2	1150	1550	2070	G13	5000	80

9W T8 HIGH EFFICACY INSTANT START - 2 FOOT GLASS TUBES

L9T8D5030K	LED 9W IS/RS 2 Ft T8 - 30K	9	17	8.5	9.5	14.2	850	1150	1540	G13	3000	80
L9T8D5035K	LED 9W IS/RS 2 Ft T8 - 35K	9	17	8.5	9.5	14.2	870	1175	1575	G13	3500	80
L9T8D5041K	LED 9W IS/RS 2 Ft T8 - 41K	9	17	8.5	9.5	14.2	890	1200	1600	G13	4100	80
L9T8D5050K	LED 9W IS/RS 2 Ft T8 - 50K	9	17	8.5	9.5	14.2	910	1225	1640	G13	5000	80

15W LED T8 INSTANT START BALLAST COMPATIBLE - 4 FOOT SHATTER PROOF TUBES BULK PACK (DLC SEARCH "LPT815A")

LPT815A41KBP	LED 15W IS/RS SC 4 Foot T8 - 41K Bulk Pack	15	32	15	18	21.5	1650	2100	2450	G13	4100	80
--------------	--	----	----	----	----	------	------	------	------	-----	------	----

15W LED T8 INSTANT START/RAPID START BALLAST COMPATIBLE - 4 FOOT SHATTER PROOF GLASS TUBES

L15T8D5030KSC	LED 15W IS/RS SC 4 Ft T8 - 30K	15	32	14.5	18	21.5	1600	2000	2350	G13	3000	80
L15T8D5035KSC	LED 15W IS/RS SC 4 Ft T8 - 35K	15	32	14.5	18	21.5	1600	2000	2350	G13	3500	80
L15T8D5041KSC	LED 15W IS/RS SC 4 Ft T8 - 41K	15	32	14.5	18	21.5	1650	2100	2450	G13	4100	80
L15T8D5050KSC	LED 15W IS/RS SC 4 Ft T8 - 50K	15	32	14.5	18	21.5	1700	2200	2500	G13	5000	80

13W LED U-BEND T8 INSTANT START/RAPID START BALLAST COMPATIBLE - 6 INCH PLASTIC

L13T8UD5030K	LED 13W U6 IS/RS 4 Ft T8 - 30K	13	32	13	16	22	1400	1800	2500	2G13	3000	83
L13T8UD5035K	LED 13W U6 IS/RS 4 Ft T8 - 35K	13	32	13	16	22	1400	1800	2500	2G13	3500	83
L13T8UD5041K	LED 13W U6 IS/RS 4 Ft T8 - 41K	13	32	13	16	22	1450	1850	2550	2G13	4100	83
L13T8UD5050K	LED 13W U6 IS/RS 4 Ft T8 - 50K	13	32	13	16	22	1500	1900	2600	2G13	5000	83



Item Number	Item Description	Lamp Wattage	Equivalent Wattage	System Wattage	Lamp Lumens	Lumens Per Watt	Base	CCT	CRI
-------------	------------------	--------------	--------------------	----------------	-------------	-----------------	------	-----	-----

50,000 HOUR LED DIRECT5™ ELECTRONIC BALLAST COMPATIBLE

25.5W LED T5 ELECTRONIC BALLAST COMPATIBLE - 4 FOOT SHATTERPROOF GLASS TUBES



L25TD5030K	LED 25W IS/RS SC 4 Ft T5 - 30K	25.5	54	28	3150	123.5	G5	3000	83
L25TD5035K	LED 25W IS/RS SC 4 Ft T5 - 35K	25.5	54	28	3150	123.5	G5	3500	83
L25TD5041K	LED 25W IS/RS SC 4 Ft T5 - 41K	25.5	54	28	3190	125.1	G5	4100	83
L25TD5050K	LED 25W IS/RS SC 4 Ft T5 - 50K	25.5	54	28	3280	128.6	G5	5000	83

13W LED T5 ELECTRONIC BALLAST COMPATIBLE - 4 FOOT SHATTERPROOF GLASS TUBES

L13TD5030K	LED 25W IS/RS SC 4 Ft T5 - 30K	13	28	16	1800	138.5	G5	3000	83
L13TD5035K	LED 25W IS/RS SC 4 Ft T5 - 35K	13	28	16	1800	138.5	G5	3500	83
L13TD5041K	LED 25W IS/RS SC 4 Ft T5 - 41K	13	28	16	1850	142.3	G5	4100	83
L13TD5050K	LED 25W IS/RS SC 4 Ft T5 - 50K	13	28	16	1900	146.2	G5	5000	83

Item Number	DLC Model #	Item Description	Line Voltage Wattage	Line Voltage Lumens	Line Voltage L/PW	LBF System Wattage	NBF System Wattage	LBF Lamp Lumens	NBF Lamp Lumens	NBF System L/PW	PF	CCT	CRI
-------------	-------------	------------------	----------------------	---------------------	-------------------	--------------------	--------------------	-----------------	-----------------	-----------------	----	-----	-----

50,000 HOUR LED T8 TYPE AB TUBES - BALLAST AND LINE VOLTAGE COMPATIBLE

15W LED T8 - 4 FOOT GLASS TUBES



LT815AB30K	T80407030E	LED 15W 4Ft T8 AB - 30K	16	1750	109.4	13.6	15.3	1550	1760	115	>.9	3000	>80
LT815AB35K	T80407035E	LED 15W 4Ft T8 AB - 35K	16	1800	112.5	13.6	15.3	1550	1760	115	>.9	3500	>80
LT815AB41K	T80407040E	LED 15W 4Ft T8 AB - 41K	16	1800	112.5	13.6	15.3	1590	1800	117.6	>.9	4100	>80
LT815AB50K	T80407050E	LED 15W 4Ft T8 AB - 50K	16	1800	112.5	13.6	15.3	1590	1800	117.6	>.9	5000	>80

15.5W LED T8 - 4 FOOT SHATTERPROOF COATED TUBES

LPT815AB30K	T8041430E	LED 15.5W 4Ft T8 AB PL -30K	16	1750	109.4	13.6	15.3	1550	1760	115	>.9	3000	>80
LPT815AB35K	T8041435E	LED 15.5W 4Ft T8 AB PL -35K	16	1750	109.4	13.6	15.3	1550	1760	115	>.9	3500	>80
LPT815AB41K	T8041440E	LED 15.5W 4Ft T8 AB PL -41K	16	1800	112.5	13.6	15.3	1590	1800	117.6	>.9	4100	>80
LPT815AB50K	T8041450E	LED 15.5W 4Ft T8 AB PL -50K	16	1850	115.6	13.6	15.3	1620	1850	120.9	>.9	5000	>80

Item Number	Item Description	Unit/Ballast Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (inches)	Diameter/Width (inches)	Base Type	Case Quantity
-------------	------------------	--------------------	---------------------------------	----------------	--------------	-----	---------------------	-------------------------	-----------	---------------

12,000 HOUR CFL PRO SERIES
TCP PRO SERIES T3 FULL SPRINGLAMPS®, NPF

48909	9 Watt Full SpringLamp	9	40W	600	2700	82	3.6	1.8	E26	12
48913	13 Watt Full SpringLamp	13	60W	925	2700	82	3.9	1.8	E26	12
48913C	13 Watt Full SpringLamp, E12	13	60W	925	2700	82	3.8	1.8	E12	12
48918	18 Watt Full SpringLamp	18	75W	1300	2700	82	4.0	2.4	E26	12
48923	23 Watt Full SpringLamp	23	100W	1650	2700	82	4.4	2.4	E26	12
48927	27 Watt Full SpringLamp	27	100W	1850	2700	82	5.1	2.4	E26	12
48932	32 Watt Full SpringLamp	32	125W	2150	2700	82	5.1	2.7	E26	12
48942	42 Watt Full SpringLamp	42	150W	2850	2700	82	5.7	2.7	E26	12

Call for other color temperatures



TCP PRO SERIES T2 FULL SPRINGLAMPS®, NPF

4T213	13 Watt T2 Full SpringLamp	13	60W	825	2700	82	3.6	1.5	E26	12
4T213C	13 Watt T2 Full SpringLamp E12	13	60W	825	2700	82	3.5	1.5	E12	12
4T223	23 Watt T2 Full SpringLamp	23	100W	1625	2700	82	4.5	2.0	E26	12

Call for other available color temperatures



10,000 HOUR E26 BASE AND MOGUL BASE SPRINGLAMPS®
SPRINGLAMPS®, ELECTRONIC, NPF, <150% THD

28968	68 Watt SpringLamp	68	300W	4200	2700	82	9.5	4.1	E26	6
-------	--------------------	----	------	------	------	----	-----	-----	-----	---



SPRINGLAMPS®, ELECTRONIC, NPF, MOGUL BASE, <150% THD

28968H	68 Watt SpringLamp Mogul Base	68	300W	4200	2700	82	9.8	4.1	Mogul	6
--------	-------------------------------	----	------	------	------	----	-----	-----	-------	---



SPRINGLAMPS®, ELECTRONIC, NPF, MOGUL BASE, 277V, <150% THD

28968H277	68 Watt SpringLamp Mogul Base 277 Volt	68	300W	4200	2700	82	9.8	4.1	Mogul	6
-----------	--	----	------	------	------	----	-----	-----	-------	---



Item Number	Item Description	Unit/Ballast Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (inches)	Diameter/Width (inches)	Base Type	Case Quantity
-------------	------------------	--------------------	---------------------------------	----------------	--------------	-----	---------------------	-------------------------	-----------	---------------

10,000 HOUR SPRINGLIGHT™

SPRINGLIGHT™ SPRINGLAMP®



9w SpringLamp

801009	9W SpringLamp 27K	9	40	550	2700	82	4.0	1.8	E26	12
80100935	9W SpringLamp 35K	9	40	550	3500	82	4.0	1.8	E26	12
80100941	9W SpringLamp 41K	9	40	550	4100	82	4.0	1.8	E26	12
80100950	9W SpringLamp 50K	9	40	500	5000	82	4.0	1.8	E26	12



14w SpringLamp

801014	14W SpringLamp 27K	14	60	900	2700	82	4.4	1.8	E26	12
8010143	14W SpringLamp 27K 3PK	14	60	900	2700	82	4.4	1.8	E26	12
80101435	14W SpringLamp 35K	14	60	900	3500	82	4.4	1.8	E26	12
80101441	14W SpringLamp 41K	14	60	900	4100	82	4.4	1.8	E26	12
801014413	14W SpringLamp 41K 3PK	14	60	900	4100	82	4.4	1.8	E26	12
80101450	14W SpringLamp 50K	14	60	850	5000	82	4.4	1.8	E26	12
80101465	14W SpringLamp 65K	14	60	850	6500	82	4.4	1.8	E26	12



19w SpringLamp

801019	19W SpringLamp 27K	19	75	1225	2700	82	4.4	2.3	E26	12
8010193	19W SpringLamp 27K 3PK	19	75	1225	2700	82	4.4	2.3	E26	12
80101935	19W SpringLamp 35K	19	75	1225	3500	82	4.4	2.3	E26	12
80101941	19W SpringLamp 41K	19	75	1225	4100	82	4.4	2.3	E26	12
801019413	19W SpringLamp 41K 3PK	19	75	1225	4100	82	4.4	2.3	E26	12
80101950	19W SpringLamp 50K	19	75	1225	5000	82	4.4	2.3	E26	12
80101965	19W SpringLamp 65K	19	75	1225	6500	82	4.4	2.3	E26	12



23w SpringLamp

801023	23W SpringLamp 27K	23	100	1600	2700	82	4.8	2.3	E26	12
8010233	23W SpringLamp 27K 3PK	23	100	1600	2700	82	4.8	2.3	E26	12
80102335	23W SpringLamp 35K	23	100	1600	3500	82	4.8	2.3	E26	12
80102341	23W SpringLamp 41K	23	100	1600	4100	82	4.8	2.3	E26	12
801023413	23W SpringLamp 41K 3PK	23	100	1600	4100	82	4.8	2.3	E26	12
80102350	23W SpringLamp 50K	23	100	1500	5000	82	4.8	2.3	E26	12
80102365	23W SpringLamp 65K	23	100	1500	6500	82	4.8	2.3	E26	12



27w SpringLamp

801027	27W SpringLamp 27K	27	100	1750	2700	82	5.5	2.4	E26	12
8010273	27W SpringLamp 27K 3PK	27	100	1750	2700	82	5.5	2.4	E26	12
80102735	27W SpringLamp 35K	27	100	1750	3500	82	5.5	2.4	E26	12
80102741	27W SpringLamp 41K	27	100	1750	4100	82	5.5	2.4	E26	12
801027413	27W SpringLamp 41K 3PK	27	100	1750	4100	82	5.5	2.4	E26	12
80102750	27W SpringLamp 50K	27	100	1750	5000	82	5.5	2.4	E26	12
80102765	27W SpringLamp 65K	27	100	1750	6500	82	5.5	2.4	E26	12



32w SpringLamp

801032	32W SpringLamp 27K	32	125	2100	2700	82	6.0	2.8	E26	12
80103241	32W SpringLamp 41K	32	125	2000	4100	82	6.0	2.8	E26	12



42w SpringLamp

801042	42W SpringLamp 27K	42	150	2750	2700	82	7.0	2.8	E26	12
80104241	42W SpringLamp 41K	42	150	2650	4200	82	7.0	2.8	E26	12

SpringLight™ WARRANTY

801 Series – 10,000 hours – 9 Years – LIMITED WARRANTY*

This product is warranted for a period of 9 YEARS* from date of original purchase against defects in materials and workmanship. If this product should fail to operate due to defects in material or workmanship, simply call 1-800-771-9335 within WARRANTED TIME of purchase. This product will be repaired or replaced, at TCP's option. This warranty is expressly limited to repair or replacement of the product. This warranty gives the consumer specific legal rights, which vary from state to state. WARRANTY IS VOID IF PRODUCT IS NOT USED FOR THE PURPOSE FOR WHICH THIS PRODUCT IS MANUFACTURED.

Item Number	Item Description	Unit/Ballast Watts	Lamp Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (inches)	Diameter/Width (inches)	Replacement Bracket	Replacement Lamp	Base Type	Replacement Ballast	Case Quantity
-------------	------------------	--------------------	------------	---------------------------------	----------------	--------------	-----	---------------------	-------------------------	---------------------	------------------	-----------	---------------------	---------------

10,000 HOUR CIRCLINE

T6 CIRCLINE LAMPS, 2700K

32027	27 Watt Circline Lamp	NA	27	120	2000	2700	82	0.8	7.5	13827B	N/A	N/A	N/A	20
32032	32 Watt Circline Lamp	NA	32	130	2200	2700	82	0.8	9.0	13832B	N/A	N/A	N/A	20
32040	40 Watt Circline Lamp	NA	40	150	2800	2700	82	0.8	7.5	13818B	N/A	N/A	N/A	20



T9 CIRCLINE LAMPS, 2700K

32030	30 Watt Circline Lamp	NA	30	120	2000	2700	NA	1.0	9.0	13830B	N/A	N/A	N/A	20
-------	-----------------------	----	----	-----	------	------	----	-----	-----	--------	-----	-----	-----	----



CIRCLINE BALLASTS, NPF

17030	30 Watt Circline Ballast	30	NA	NA	NA	NA	NA	NA	NA	NA	N/A	E26	N/A	50
17040Q2	40 Watt Circline Ballast	40	NA	NA	NA	NA	NA	NA	NA	NA	N/A	E26	N/A	50



Add suffix "Q" for Snap-in Version.
Item #4001 for Hard-wire base only.

Item Number	Item Description	Unit/Ballast Watts	Incandescent Comparison (Watts)	Initial Lumens	CCT (Kelvin)	CRI	MOL/Height (inches)	Diameter/Width (inches)	Input Line	Base Type	Case Quantity
-------------	------------------	--------------------	---------------------------------	----------------	--------------	-----	---------------------	-------------------------	------------	-----------	---------------

10,000 HOUR GU 24 BASES

GU24 SPRINGLAMPS

33109SP	9 Watt SpringLamp	9	45	550	2700	82	3.4	1.8	.15A	GU24	12
33113SP	13 Watt SpringLamp	13	60	900	2700	82	3.6	1.8	.22A	GU24	12
33118SP	18 Watt SpringLamp	18	75	1200	2700	82	3.8	2.3	.30A	GU24	12
33123SP	23 Watt SpringLamp	23	100	1600	2700	82	4.4	2.4	.43A	GU24	12
33127SP	27 Watt SpringLamp	27	100	1850	2700	82	4.8	2.4	.45A	GU24	12
33132SP	32 Watt SpringLamp	32	120	2200	2700	82	5.1	2.7	.53A	GU24	12
33213SSP	13 Watt Low Profile	13	60	900	2700	82	2.3	3.2	.22A	GU24	12



LINEAR FLUORESCENT LAMPS

Item Number	Item Description	Lamp Watts	Lamp Life (hrs) At 3 hours per start	Initial Lumens	Mean Lumens	CCT (Kelvin)	CRI	Diameter (inches)	Length (inches)	Base Type	Case Quantity
-------------	------------------	------------	---	----------------	-------------	--------------	-----	-------------------	-----------------	-----------	---------------

T8 LAMPS

T8 LAMPS, MEDIUM BI-PIN



32W	31032830	F32T8/830	32	24000	2950	2800	3000	85	1	48	Medium Bi-Pin	25
	31032835	F32T8/835	32	24000	2950	2800	3500	85	1	48	Medium Bi-Pin	25
	31032841	F32T8/841	32	24000	2950	2800	4100	85	1	48	Medium Bi-Pin	25
	31032850	F32T8/850	32	24000	2950	2800	5000	85	1	48	Medium Bi-Pin	25
28W	31028830	F28T8/830	28	24000	2650	2520	3000	85	1	48	Medium Bi-Pin	25
	31028835	F28T8/835	28	24000	2650	2520	3500	85	1	48	Medium Bi-Pin	25
	31028841	F28T8/841	28	24000	2650	2520	4100	85	1	48	Medium Bi-Pin	25
	31028850	F28T8/850	28	24000	2650	2520	5000	85	1	48	Medium Bi-Pin	25
25W	31025830	F25T8/830	25	24000	2225	2115	3000	85	1	36	Medium Bi-Pin	25
	31025835	F25T8/835	25	24000	2225	2115	3500	85	1	36	Medium Bi-Pin	25
	31025841	F25T8/841	25	24000	2225	2115	4100	85	1	36	Medium Bi-Pin	25
	31025850	F25T8/850	25	24000	2225	2115	5000	85	1	36	Medium Bi-Pin	25
17W	31017830	F17T8/830	17	24000	1400	1330	3000	85	1	24	Medium Bi-Pin	25
	31017835	F17T8/835	17	24000	1400	1330	3500	85	1	24	Medium Bi-Pin	25
	31017841	F17T8/841	17	24000	1400	1330	4100	85	1	24	Medium Bi-Pin	25
	31017850	F17T8/850	17	24000	1400	1330	5000	85	1	24	Medium Bi-Pin	25

T5 LAMPS


T5HO LAMPS, MINATURE BI-PIN



54W	31054830	F54T5HO/830	54	24000	5000	4750	3000	85	0.625	45.2	Miniature Bi-Pin	40
	31054835	F54T5HO/835	54	24000	5000	4750	3500	85	0.625	45.2	Miniature Bi-Pin	40
	31054841	F54T5HO/841	54	24000	5000	4750	4100	85	0.625	45.2	Miniature Bi-Pin	40
	31054850	F54T5HO/850	54	24000	5000	4750	5000	85	0.625	45.2	Miniature Bi-Pin	40
	31054865	F54T5HO/865	54	24000	5000	4750	6500	85	0.625	45.2	Miniature Bi-Pin	40

T8 LAMPS

T8 LAMPS, MEDIUM BI-PIN



32W, 6" Leg	31032830U6	FB32T8/830/6	32	20000	3000	2850	3000	85	1	22.5	Med. Bi-Pin	10
	31032835U6	FB32T8/835/6	32	20000	3000	2850	3500	85	1	22.5	Med. Bi-Pin	10
	31032841U6	FB32T8/841/6	32	20000	3000	2850	4100	85	1	22.5	Med. Bi-Pin	10
	31032850U6	FB32T8/850/6	32	20000	3000	2850	5000	85	1	22.5	Med. Bi-Pin	10
31W, 1-5/8" Leg	31031830U1	FB31T8/830/1	31	20000	2750	2600	3000	85	1	22.5	Med. Bi-Pin	10
	31031835U1	FB31T8/835/1	31	20000	2750	2600	3500	85	1	22.5	Med. Bi-Pin	10
	31031841U1	FB31T8/841/1	31	20000	2750	2600	4100	85	1	22.5	Med. Bi-Pin	10




LINEAR FLUORESCENT BALLASTS



	Next Generation Item Numbers	Item Description	Ballast Factor	Number of Lamps	Length (inches)	Width (inches)	Height (inches)
32W T8 ELECTRONIC INSTANT START BALLASTS, 5 YEAR WARRANTY, 120-277 VOLTS, <10% THD, NEMA PREMIUM, CEE LISTED							
4 lamp, 32W	E4P32ISUNVHE	T8 4 Lamp Instant Start, High Ballast Factor, High Efficiency	1.18	4 or 3	9.5	1.70	1.20
	E4P32ISUNVE	T8 4 Lamp Instant Start, Normal Ballast Factor, High Efficiency	0.88	4 or 3	9.5	1.70	1.20
	E4P32ISUNVLE	T8 4 Lamp Instant Start, Low Ballast Factor, High Efficiency	0.78	4 or 3	9.5	1.70	1.20
3 lamp, 32W	E3P32ISUNVHE	T8 3 Lamp Instant Start, High Ballast Factor, High Efficiency	1.18	3 or 2	9.5	1.30	1.20
	E3P32ISUNVE	T8 3 Lamp Instant Start, Normal Ballast Factor, High Efficiency	0.88	3 or 2	9.5	1.30	1.20
	E3P32ISUNVLE	T8 3 Lamp Instant Start, Low Ballast Factor, High Efficiency	0.78	3 or 2	9.5	1.30	1.20
2 lamp, 32W	E2P32ISUNVHE	T8 2 Lamp Instant Start, High Ballast Factor, High Efficiency	1.18	2 or 1	9.5	1.30	1.20
	E2P32ISUNVE	T8 2 Lamp Instant Start, Normal Ballast Factor, High Efficiency	0.88	2 or 1	9.5	1.30	1.20
	E2P32ISUNVLE	T8 2 Lamp Instant Start, Low Ballast Factor, High Efficiency	0.78	2 or 1	9.5	1.30	1.20

	Next Generation Item Numbers	Item Description	Ballast Factor	Number of Lamps	Length (inches)	Width (inches)	Height (inches)
32W T8 ELECTRONIC PROGRAM START BALLASTS, 5 YEAR WARRANTY, 120-277 VOLTS, <10% THD, NEMA PREMIUM, CEE LISTED							
4 lamp, 32W	E4P32PSUNVHE	T8 4 Lamp Program Start, High Ballast Factor, High Efficiency	1.18	4 or 3	11.75	1.70	1.20
	E4P32PSUNVE	T8 4 Lamp Program Start, Normal Ballast Factor, High Efficiency	0.87	4 or 3	9.5	1.70	1.20
	E4P32PSUNVLE	T8 4 Lamp Program Start, Low Ballast Factor, High Efficiency	0.77	4 or 3	9.5	1.70	1.20
3 lamp, 32W	E3P32PSUNVHE	T8 3 Lamp Program Start, High Ballast Factor, High Efficiency	1.18	3 or 2	9.5	1.70	1.20
	E3P32PSUNVE	T8 3 Lamp Program Start, Normal Ballast Factor, High Efficiency	0.87	3 or 2	9.5	1.70	1.20
	E3P32PSUNVLE	T8 3 Lamp Program Start, Low Ballast Factor, High Efficiency	0.77	3 or 2	9.5	1.70	1.20
2 lamp, 32W	E2P32PSUNVHE	T8 2 Lamp Program Start, High Ballast Factor, High Efficiency	1.18	2 or 1	9.5	1.70	1.20
	E2P32PSUNVE	T8 2 Lamp Program Start, Normal Ballast Factor, High Efficiency	0.87	2 or 1	9.5	1.30	1.20
	E2P32PSUNVLE	T8 2 Lamp Program Start, Low Ballast Factor, High Efficiency	0.77	2 or 1	9.5	1.30	1.20

	Next Generation Item Numbers	Item Description	Ballast Factor	Number of Lamps	Length (inches)	Width (inches)	Height (inches)
54W T5 ELECTRONIC PROGRAM START BALLASTS, 5 YEAR WARRANTY, 120-277 VOLTS, <10% THD							
2 lamp, 54W	E2P54PRSUNVE	T5 2 Lamp Program Start, High Efficiency	1.00	2 or 1	9.5	1.75	1.20

Item Number	Item Description	Lumens	# of Lamps Supported	Length	Width	Height	Weight (lbs)	Item Number	Item Description	Ballast Included	# of Sockets
LINEAR FLUORESCENT EMERGENCY BALLASTS, 120 OR 277 VOLTS											
				T8	T5	CFL					
 20B100	Emergency Ballast 500 Lumens T8 Only	500	1	none	1	9.4	2.4	1.5	1.4		
 20B60	Emergency Ballast 700 Lumens T8 Only	700	1 or 2	none	1 or 2	9.4	2.4	1.5	2.5		
 20B50	Emergency Ballast 1400 Lumens T8 or T5	1400	1 or 2	1	1 or 2	13.3	2.4	1.5	2.5		
PRE-WIRED REPLACEMENT BALLASTS											
High Ballast Factor	RETROBALHARNWD1	4Ft, 1-Lamp Retro Ballast, High Ballast Factor	E2P32ISUNVHE	2							
	RETROBALHARNWD2	4 or 8Ft, 2-Lamp Retro Ballast, High Ballast Factor	E2P32ISUNVHE	4							
	RETROBALHARNWD3	4Ft, 3-Lamp Retro Ballast, High Ballast Factor	E3P32ISUNVHE	6							
	RETROBALHARNWD4	4 or 8Ft, 4-Lamp Retro Ballast, High Ballast Factor	E4P32ISUNVHE	8							
Normal Ballast Factor	RETROBALHARNWD1N	4Ft, 1-Lamp Retro Ballast, Normal Ballast Factor	E2P32ISUNVE	2							
	RETROBALHARNWD2N	4 or 8Ft, 2-Lamp Retro Ballast, Normal Ballast Factor	E2P32ISUNVE	4							
	RETROBALHARNWD3N	4Ft, 3-Lamp Retro Ballast, Normal Ballast Factor	E3P32ISUNVE	6							
	RETROBALHARNWD4N	4 or 8Ft, 4-Lamp Retro Ballast, Normal Ballast Factor	E4P32ISUNVE	8							
Low Ballast Factor	RETROBALHARNWD1L	4Ft, 1-Lamp Retro Ballast, Low Ballast Factor	E2P32ISUNVLE	2							
	RETROBALHARNWD2L	4 or 8Ft, 2-Lamp Retro Ballast, Low Ballast Factor	E2P32ISUNVLE	4							
	RETROBALHARNWD3L	4Ft, 3-Lamp Retro Ballast, Low Ballast Factor	E3P32ISUNVLE	6							
	RETROBALHARNWD4L	4 or 8Ft, 4-Lamp Retro Ballast, Low Ballast Factor	E4P32ISUNVLE	8							

Item Number	Item Description	Voltage	Lamp Count	Lamp Type	Ballast Type	Ballast Factor	Distribution	Power Cord	Options
-------------	------------------	---------	------------	-----------	--------------	----------------	--------------	------------	---------

ELITE FLUORESCENT HIGH BAY (CONSULT SPEC SHEET FOR ORDERING MATRIX)

ELITE - STOCKING PROGRAM




EL4SA432UNIH10CSP	Elite, 4 Lamp T8, Universal, Non-Dimming	120-277V	4	T8	Instant Start	High	Narrow	10'	Lamps sold separately
EL4SA454UNIV10CSP	Elite, 4 Lamp T5H0, Universal, Non-Dimming	120-277V	4	T5H0	PRS	High	Narrow	10'	Lamps sold separately
EL4SA632UNIH10CSP	Elite, 6 Lamp T8, Universal, Non-Dimming	120-277V	6	T8	Instant Start	High	Narrow	10'	Lamps sold separately
EL4SA654UNIV10CSP	Elite, 6 Lamp T5H0, Universal, Non-Dimming	120-277V	6	T5H0	PRS	High	Narrow	10'	Lamps sold separately

ELITE - ASSEMBLED TO ORDER

Consult spec sheet for full product line offering and options.

ENCLOSED & GASKETED FIXTURES (CONSULT SPEC SHEET FOR ORDERING MATRIX) NSF, IP65 AND IP67 CERTIFIED

WET LOCATION FIXTURE - STOCKING PROGRAM



WL4WA254UNIVSP	Wet Location, 2 Lamp T5H0, Universal, Non-Dimming	120-277V	2	T5H0	PRS	High	Wide	-	Lamps sold separately
WL4WA332UNIHSP	Wet Location, 3 Lamp T8, Universal, Non-Dimming	120-277V	3	T8	Instant Start	High	Wide	-	Lamps sold separately

WET LOCATION FIXTURE - ASSEMBLED TO ORDER

Consult spec sheet for full product line offering and options.

ENCLOSED & GASKETED FIXTURES CONTINUED (CONSULT SPEC SHEET FOR ORDERING MATRIX) NSF, IP65 AND IP67 CERTIFIED

POLAR BAY FIXTURE - ASSEMBLED TO ORDER



PL4WA432UNIH	Polar Bay, 4 Lamp T8, Universal, Non-Dimming	120-277V	4	T8	Instant Start	High	Wide	-	Lamps sold separately
PL4WA454UNIV	Polar Bay, 4 Lamp T5H0, Universal, Non-Dimming	120-277V	4	T5H0	PRS	High	Wide	-	Lamps sold separately
PL4WA632UNIH	Polar Bay, 6 Lamp T8, Universal, Non-Dimming	120-277V	6	T8	Instant Start	High	Wide	-	Lamps sold separately
PL4WA654UNIV	Polar Bay, 6 Lamp T5H0, Universal, Non-Dimming	120-277V	6	T5H0	PRS	High	Wide	-	Lamps sold separately

STAIRWELL FIXTURES (CONSULT SPEC SHEET FOR ORDERING MATRIX)

STAIRWELL FIXTURE - ASSEMBLED TO ORDER



ST4N2NML	Stairwell, 3 Lamp T8, Universal, Non-Dimming	120-277V	3	T8	PRS / IS	Normal / Normal	Perforated Metal	-	Lamps sold separately
ST4N2NML120B6	Stairwell, 3 Lamp T8, Universal, Non-Dimming, Emergency Back-Up	120-277V	3	T8	PRS / IS	Normal / Normal	Perforated Metal	-	Lamps sold separately

Consult spec sheet for full product line offering and options.

LED PL LAMPS

44 - 45

LED DIMMABLE VERTICAL BR30 PL LAMPS.....	44
LED DIMMABLE VERTICAL BR40 PL LAMPS.....	44
LED NON DIMMABLE QUAD PL LAMPS	45
LED NON DIMMABLE PL 3U LAMPS	45
LED NON DIMMABLE PL 2U LAMPS	45

LED 120-277V LAMPS

46

LED NON DIMMABLE 120-277V A23 LAMPS.....	46
LED NON DIMMABLE 120-277V A21 LAMPS.....	46
LED NON DIMMABLE 120-277V A19 LAMPS.....	46
LED NON DIMMABLE 120-277V BR30 LAMPS.....	46
LED NON DIMMABLE 120-277V PAR38 LAMPS.....	46

LED STARLIGHT SERIES LAMPS

47

LED DIMMABLE STARLIGHT SERIES SL13 LAMPS	47
LED DIMMABLE STARLIGHT SERIES SL16 LAMPS	47
LED DIMMABLE STARLIGHT SERIES SL19 LAMPS	47
LED DIMMABLE STARLIGHT SERIES SL22 LAMPS	47
STARLIGHT MATCHING PENDANT MOUNTS.....	47

LED HID REPLACEMENT LAMPS

48 - 49

LED NEW HID REPLACEMENT LAMP, 20W AND E26 BASE.....	48
LED NEW HID REPLACEMENT LAMP, 25W AND E26 BASE.....	48
LED NEW HID REPLACEMENT LAMP, 40W AND E26 BASE.....	48
LED NEW HID REPLACEMENT LAMP, 65W AND EX39 BASE.....	48
LED NEW HID REPLACEMENT LAMP, 90W AND EX39 BASE.....	48
LED HID REPLACEMENT LAMP, 19W AND E26 BASE.....	49
LED HID REPLACEMENT LAMP, 24W AND E26 BASE.....	49
LED HID REPLACEMENT LAMP, 45W AND E26 BASE.....	49
LED HID REPLACEMENT LAMP, 45W AND EX39 BASE.....	49
LED HID REPLACEMENT LAMP, 80W AND EX39 BASE.....	49
LED HID REPLACEMENT LAMP, 100W AND EX39 BASE.....	49

LED BALLAST BYPASS TUBES

50 - 52

LIBERAT8™ LED BALLAST BYPASS 4 FT GLASS TUBES.....	50
LIBERAT8™ LED BALLAST BYPASS 4 FT PET COATED GLASS TUBES.....	50
LIBERAT8™ LED BALLAST BYPASS 3 FT PET COATED GLASS TUBES.....	50
LIBERAT8™ LED BALLAST BYPASS 2 FT PET COATED GLASS TUBES.....	50
LIBERAT8™ LED BYPASS 8 FT GLASS TUBES, R17D BASE.....	50
LIBERAT8™ LED BYPASS 8 FT GLASS TUBES, FA8 BASE.....	50
LIBERAT8™ LED BALLAST BYPASS 2 FT U-BEND PLASTIC TUBES.....	50
LIBERAT8™ LED HIGH OUTPUT BALLAST BYPASS 4 FT GLASS TUBES.....	51
LIBERAT5™ LED HIGH OUTPUT BALLAST BYPASS 2 FT GLASS TUBES.....	51
LIBERAT5™ LED HIGH OUTPUT BALLAST BYPASS 3 FT GLASS TUBES.....	51
LIBERAT5™ LED HIGH OUTPUT BALLAST BYPASS 4 FT GLASS TUBES.....	51
LIBERAT5™ LED BALLAST BYPASS 2 FT GLASS TUBES.....	52
LIBERAT5™ LED BALLAST BYPASS 3 FT GLASS TUBES.....	52
LIBERAT5™ LED BALLAST BYPASS 4 FT GLASS TUBES.....	52

LED DIRECT8 IS TUBES

52 - 53

DIRECT8™ LED INSTANT START 4 FT GLASS TUBES.....	52
DIRECT8™ LED IS HIGH CRI 4 FT GLASS TUBES.....	52
DIRECT8™ LED IS HIGH EFFICACY 4 FT GLASS TUBES.....	53
DIRECT8™ LED IS HIGH EFFICACY 4 FT GLASS TUBES BULK.....	53
DIRECT8™ LED IS/RS HIGH EFFICACY 3 FT GLASS TUBES.....	53
DIRECT8™ LED IS/RS HIGH EFFICACY 2 FT GLASS TUBES.....	53
DIRECT8™ LED IS/RS U-BEND 4 FT PLASTIC TUBES.....	53
DIRECT8™ LED IS 4 FT SHATTERPROOF PLASTIC TUBES BULK.....	53
DIRECT8™ LED IS/RS 4 FT SHATTERPROOF GLASS TUBES.....	53

LED DIRECT5 TUBES

54

DIRECT5™ LED ELECTRONIC BALLAST 4 FT GLASS TUBES.....	54
---	----

LED T8 TYPE AB TUBES

54

LED T8 TYPE AB 4 FT GLASS TUBES.....	54
LED T8 TYPE AB 4 FT PLASTIC TUBES.....	54

CFL LAMPS

55 - 57

CFL PRO SERIES T3 FULL SPRINGLAMPS®.....	55
CFL PRO SERIES T2 FULL SPRINGLAMPS®.....	55
CFL SPRINGLAMPS®, E26 BASE.....	55
CFL SPRINGLAMPS®, MOGUL BASE.....	55
CFL SPRINGLAMPS®, 277V, MOGUL BASE.....	55
CFL SPRINGLIGHT™ SPRINGLAMPS®.....	56
CFL SPRINGLAMPS®, GU24 BASE.....	57

CIRCLINE LAMPS AND BALLASTS

57

T6 CIRCLINE LAMPS.....	57
T9 CIRCLINE LAMPS.....	57
CIRCLINE BALLASTS.....	57

FLUORESCENT LAMPS

58

T8 FLUORESCENT LAMPS, MEDIUM BI-PIN.....	58
T5HO FLUORESCENT LAMPS, MINIATURE BI-PIN.....	58
T8 U-BEND FLUORESCENT LAMPS, MEDIUM BI-PIN.....	58

FLUORESCENT BALLASTS

59

T8 ELECTRONIC INSTANT START BALLASTS.....	59
T8 ELECTRONIC PROGRAM START BALLASTS.....	59
T5 ELECTRONIC PROGRAM START BALLASTS.....	59
LINEAR EMERGENCY BALLASTS.....	59
PRE-WIRED REPLACEMENT BALLASTS.....	59

LINEAR FLUORESCENT FIXTURES

60

ELITE FLUORESCENT HIGH BAY FIXTURE.....	60
ENCLOSED AND GASKETED WET LOCATION FIXTURE.....	60
ENCLOSED/GASKETED WET LOCATION POLAR BAY FIXTURE.....	60
FLUORESCENT STAIRWELL FIXTURE.....	60

Technology Cast in a Beautiful Light

For more information on the quality and care that TCP® can deliver, call us at
800.324.1496 or visit tcsi.com

325 Campus Drive | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516

