



LEDicated Soft**LED**



Wall Mount



Pendant Mount

The Nautilus DuraLED Post Top Luminaire combines contemporary aesthetics and installer-friendly features for roadway, area, and walkway lighting projects. Its historically inspired traditional form uses smooth sweeping arms with articulated base fitter, and provides delivered lumens exceeding typical 250W MH fixtures. The IP66 sealed LED light engine offers excellent optical control and heat dissipation for long life. Open frame full cutoff optics control glare and an optional opal LumaLens provide visually soft illumination. The Nautilus is perfect for multi-family residential projects, retail centers, town center streets, and institutional projects.

- Diecast aluminum Luminaire 21" diameter x 27.75" high
- Optional one-piece polycarbonate opal LumaLens available
- Open frame has zero uplight to minimize light pollution and protect the night skies
- 37-140 Array watts – 4,300 to 18,600 delivered lumens, 3K, 4K, 5K CCT
- LED array is mounted in an IP66 sealed rotatable Light Engine with integral diecast aluminum heat sink
- Light Engine includes Integral Optics clear polycarbonate lens, IES Types I, II, III, IV and V
- IP67 fully potted 120-277VAC or 347-480VAC driver
- Diecast aluminum slip fitter for 3" x 3" tenon
- Twist-lock photocell, fusing, surge protection and battery backup available



Available in two sizes

Catalog Number: WM21QF1X140U*KC0; *3K, 4K, 5K; 0Color
 Available Q3 2021

Preliminary, specifications subject to change. Refer to published specification sheet for most current information.

Rev. 062121