enel **X way**



Commercial Charging Stations

An all-purpose charging station with flexible payment options and configurations

JuicePedestal offers best-in-class smart charging for businesses, municipalities, property owners and fleet managers that want to offer EV charging to their employees, customers and tenants. UL Certified with universal EV compatibility, JuicePedestal is an all-purpose commercial charging station for EV drivers. Affordably priced, JuicePedestal offers flexible charging port configurations and multiple payment options.

- · Allows multiple user authentication methods
- · Enables open network and flexible payment option
- · Connects to the internet via cellular or Wi-Fi
- Optimizes energy costs by managing charging times and avoiding demand charges with our JuiceNet[®] smart charging platform
- · Keeps charging stations organized and easily accessible with a retractable cable management system
- Ships with two JuiceBox Pro charging stations assembled to pedestal to reduce installation costs

Why JuicePedestal?

Versatile Power Options

Choose between a 32 amp, 40 amp, 48 amp and 80 amp output to charge electric vehicles quickly and easily

Easy Cable Management

Turnkey solution with built-in cable management for plug and play deployment

Flexible Payment

Allow drivers to access and pay via mobile device or optional credit card terminal

Industrial Design

Designed for durability in all-weather conditions

Universal Compatibility

SAE-J1772 [™] Compliance ensures compatibility with all EVs

Smart Charging Platform

JuiceNet smart charging platform offers a web-based portal to monitor usage and configure charging settings



enel : way

JuicePedestal Specifications

Robust, Convenient Mounting Solution	> > > >	Ships with two JuiceBox Pro chargers assembled to unit to reduce installation costs Easy, quick installation: ground-mounted with 4 bolts, concrete pad recommended Cable management: retractable weight pulley cables system Powder coated stainless steel construction	
Weight & Dimensions	> > >	Height: 74 in/188 cm Width: 19.88 in/50.50 cm by 8.00 in /20.32 cm deep Weight: 175 lbs/79.38 kg (without charging units- add 15-17 lbs/6.80-7.71 kg per JuiceBox)	
Safety and certifications	>	UL, cUL and ENERGY STAR® compliant	
Warranty	>	3-year limited warranty, optional 2 additional years	
Made in North America	>	From domestic & imported parts	

JuiceBox Pro Charging Stations

-							
Electrical Characteristics	 Choose between four power configurations: 32A, 7.7 kW; 40A, 9.6 kW; 48A, 11.2kW; and 80A, 19.2 kW Single phase input: nominal voltage 208-240 VAC ~60 Hz 						
Input Cables	Internal junction box for two circuits to power chargers						
Output Cable & Connector	20 ft/6.1m cables, each rated 240VAC with a J1772 Plug						
JuiceNet® Smart Charging Platform	Precision measurement of power, energy, voltage & current Web-based portal: set payment rates and charging hours; monitor charging status and consumption data for individual or groups of devices; control station access; manage EV load Driver app to monitor and pay for charging (iOS & Android) Refer to the JuiceNet Business and JuiceNet Enterprise datasheets for more on the capabilities of each dashboard						
Connectivity & Authentication	 WiFi: 802.11 b/g/n 2.4 GHz JuiceRouter: Connect up to 16 chargers with WiFi with an LTE Router (optional) Integrated Cellular: LTE (optional via JuiceBox LTE charging stations, JuiceRouter or the UPT) RFID authentication enabled and QR Code payment option 						
Firmware	 End-to-end AES-256-based encrypted protocols 90-day, 15-minute interval data storage Persistent data storage upon power interruption Over-the-air (OTA) upgradeable firmware 						
Enclosure	 > Dynamic LED lights show charging status: network connectivity, charging in progress, delaying charging, standby, charge complete/EV not drawing power > IP66 Weatherproof, dust-tight, polycarbonate enclosure > IK10: resistant polycarbonate case > Quick-release wall mounting bracket included > Built-in security lock and integrated cable management > Minimum and Maximum Operating temperature: -40°F to 140°F (-40°C to 60°C) > Minimum and Maximum Operating temperature with UPT: -4°F to 140°F (-20°C to 50°C) **Please refer to each JuiceBox Datasheet to confirm the operating temperature by power level and optional 						
Codes & Standards	andards FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR® OCPP 1.6J and OpenADR 2.0b compliant						

Refer to the JuiceBox Pro 32, 40, 48 and 80 datasheets for more information.

Customer Support +1-844-584-2329 Commercial Sales +1-844-885-5850 🎐 @enelxwayna

f EnelXWayNA

in enelxway

O @enelxwayna

enel쑸way

JuicePedestal Configurations

	JuicePedestal	JuicePedestal LTE	JuicePedestal upgraded with JuiceRouter ¹	JuicePedestal upgraded with Universal Payment Terminal (UPT) ¹
Assembly Options	Fully assembled with 2 wifi-enabled JuiceBoxes Choice of 4 power variants	Fully assembled with 2 LTE- enabled JuiceBoxes Choice of 4 power variants	2 wifi-enabled JuiceBoxes and a JuiceRouter (ordered separately) Choice of 4 power variants *JuiceRouter also offered as a field upgrade as needs evolve*	2 wifi-enabled JuiceBoxes and a UPT (ordered separately) Choice of 4 power variants *UPT also offered as a field upgrade as needs evolve*
Network (Provider varies by geography)	Installation site Wi-Fi Network	LTE data plan required – ordered separately	LTE - Wi-Fi Network enabled from JuiceRouter JuiceRouter data plan required – ordered separately*	LTE – Network enabled from UPT UPT Data plan required – ordered separately*
Connectivity	Cloud connection via customers' Wi-Fi network	Cloud connection via LTE	Cloud connection via LTE Serves as a Wi-Fi access point for up to 7 JuicePedestals	Cloud connection via LTE
Authentication and Payment	QR Code and RFiD, optional upgrade to UPT If upgraded with UPT, WiFi connectivity is no longer required	QR Code and RFiD, optional upgrade to UPT If upgraded, LTE data plan will not be required and replaced by UPT or JuiceRouter data plan	QR Code and RFiD, optional upgrade to UPT If upgraded to UPT, JuiceRouter will be dismounted (connected stations will lose connectivity)	UPT Credit Card Reader, QR Code and RFiD
Management Software	JuiceNet Business or JuiceNet Enterprise**	JuiceNet Enterprise**	JuiceNet Enterprise**	JuiceNet Enterprise**

¹Router and UPT ordered separate from the JuicePedestal

*LTE data plan required – ordered separately

**Annual Subscription per device

***Shaded Columns indicate configurations with additional JuiceRouter or UPT Upgrades

JUICEBOX and JUICENET are registered trademarks of Enel X North America, an Enel Group company. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

evcharging.enelx.com/contact

Customer Support +1-844-584-2329 Commercial Sales +1-844-885-5850 🎔 @enelxwayna

f EnelXWayNA

in enelxway

O @enelxwayna