

# Control Unit

## uniVision Image

# BB1C503

Part Number



- Compact housing in 86 × 227 × 260 mm format
- Configurable uniVision software for evaluating images from machine vision cameras
- Control unit with installed uniVision Image software
- Wear and noise reduction thanks to passive, fan-less cooling

The control unit is a CPU for evaluating data from image processing products. Its compact design ensures the necessary flexibility for easy, space-saving installation, for example in a control cabinet or on a wall. Quick initial start-up is made possible by the pre-installed software. Various standard interfaces are available for the output of results. An extensive range of optional accessories is also available including monitor, keyboard and switch.

## Technical Data

### Electrical Data

Supply Voltage	9...48 V DC
Current Consumption (U <sub>b</sub> = 24 V)	< 5 A
Temperature Range	0...45 °C
Number of RJ45 Industrial Ethernet ports	2
Number of USB 2.0 interfaces	2
Number of USB 3.0 interfaces	6
Number of Gigabit Ethernet RJ45	2
Number of display port interfaces	2
Number of VGA ports	1
Number of HDMI ports	1
Number of PS/2 ports	1

### Mechanical Data

Housing Material	Aluminum
Degree of Protection	IP40
Wall mounting	yes

### Function

Image analysis	yes
Software	uniVision Image
Processor	Intel® Core i7
Clock Frequency	4,4 GHz
RAM	16 GB
Hard disk	128 GB SSD

Ethernet	●
PROFINET-I/O, CC-C	●
EtherNet/IP™	●
USB Interface	●
PS/2 (mouse/key pad)	●
VGA Connection	●
Display port connection	●

## Complementary Products

Control unit license upgrade
Key Pad Z0044
Machine vision camera BBZK
Monitor ZNNG026
Switch EHSS001

