KVT-ER | Split cable gland

for cables with connectors, M25 - M63 / IP66 / IP68 / UL Type 12/4X*





KVT-ER are split cable glands for routing and sealing cables with connectors, with diameters from 1 to 16 mm ($\underline{\text{KT}}$ 1 - 15) and 13 to 35 mm ($\underline{\text{KTG}}$ 13 - $\underline{\text{KT}}$ 34). But also electric, pneumatic or hydraulic lines without terminals or connectors as well as corrugated conduits can be easily routed (e.g. into control panels, enclosures or machinery), sealed and strain relieved acc. to EN 62444.

The KVT-ER sizes are based on metric standard cut-outs M25, M32, M50 and M63. Hexagonal locknuts are included in the shipment. For assembly, we recommend to tighten the cover lid screws with max. 2 Nm.

Due to the injected gasket and if single-hole grommets are used, the KVT-ER provides certified protection ratings IP66/IP68 and UL type 12 & 4X*.

*4X for indoor use only


Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X*
Material	Body: Polypropylene Integrated sealing lip: Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 110 C°
Properties	halogen free, silicone free
Mounting options	Fasten with locknut

Advantages & Benefits

- Certified protection IP66/IP68 (acc. to EN 60529)
- Strain relief according to EN 62444
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- High stability, vibration resistant
- Hygienic design free of dirt-collecting recesses

Product types & Sizes




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
External diameter

Mounting height
Cut-out size, metric
Thread
Thread length
Suitable for grommets

20 mm M25 M25 × 1,5 18 mm 1 x KT small


KVT-ER 32



Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
External diameter

Mounting height Cut-out size, metric Thread Thread length Suitable for grommets 20 mm M32 M32 × 1,5 18 mm 1 x KT small

KVT-ER 50|2



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color

External diameter


5 2 16 mm schwarz 63 mm

4251269318917

45454

Mounting height Cut-out size, metric Thread Thread length Suitable for grommets 20 mm M50 M50 × 1,5 20,5 mm 2 x KT small

KVT-ER 63|4



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color External diameter

45456 4251269318931 5 4 16 mm


schwarz

75 mm

45455

Mounting height 20 mm Cut-out size, metric M63 M63 × 1,5 Thread Thread length 20,5 mm Suitable for grommets 4 x KT small

KVT-ER 63|1



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color External diameter

4251269318924 5 1 35 mm schwarz 75 mm

Mounting height 20 mm M63 Cut-out size, metric Thread M63 × 1,5 20,5 mm Thread length Suitable for grommets 1 x KT large

